

Twist-Lock® Devices  
**20 Ampere, 125, 250 Volts and 277 Volts AC**  
 2 Pole, 3 Wire Grounding  
**Insulgrip® Connector Bodies and Receptacles**



**20A 125V**  
 NEMA L5-20R  
 UL/CSA  
 1 HP



**20A 250V**  
 NEMA L6-20R  
 UL/CSA  
 2 HP



**20A 277V AC**  
 NEMA L7-20R  
 UL/CSA  
 2 HP

**Connector Bodies**

<b>Watertight Safety-Shroud®</b>		<b>IP66 SUITABILITY</b>		
Description	Cord Dia.	Catalog Numbers		
Black Valox® housing, white Valox® clamps.	.360"-.930" (9-24)	<b>HBL2313SW</b>	<b>HBL2323SW</b>	<b>HBL2333SW</b>



**HBL2323SW**


<b>Insulgrip</b>		<b>IP20 SUITABILITY</b>		
Description	Cord Dia.	Catalog Numbers		
Black and white nylon.	.360"-.930" (9-24)	<b>HBL2313</b>	<b>HBL2323</b>	<b>HBL2333</b>
Corrosion resistant, yellow nylon.	.360"-.930" (9-24)	<b>HBL23CM13</b>	<b>HBL23CM23</b>	-
All black nylon.	.360"-.930" (9-24)	<b>HBL2313BK</b>	<b>HBL2323BK</b>	-
Cord clamps with removable inserts. All black nylon.	.360"-.930" (9-24)	<b>HBL2313EBK</b>	<b>HBL2323EBK</b>	-



**HBL2313**

Accessories on page B-51.

<b>Valise®</b>		<b>IP20 SUITABILITY</b>		
Description	Cord Dia.	Catalog Numbers		
Yellow nylon.	.325"-.720" (8.26-18.3)	<b>HBL2313VY</b>	<b>HBL2323VY</b>	-
Black nylon.	.325"-.720" (8.26-18.3)	<b>HBL2313VBK</b>	<b>HBL2323VBK</b>	<b>HBL2333VBK</b>




**HBL2313VY**

Accessories on page B-51.

**Receptacles**

<b>Watertight Safety-Shroud, Back Wired</b>		<b>IP66 SUITABILITY</b>		
Description	Catalog Numbers			
Gray Valox® housing and flange.	<b>HBL2310SW</b> <b>HBL2320SW</b> <b>HBL2330SW</b>			



**HBL2320SW**

<b>Safety-Shroud Twist-Lock, Back Wired</b>		<b>IP20 SUITABILITY</b>		
Description	Catalog Numbers			
Gray Valox® angle housing, one gang.	<b>HBL2310AR</b> <b>HBL2320AR</b> <b>HBL2330AR</b>			
Gray Valox® surface mounting, one gang.	<b>HBL2310SR</b> <b>HBL2320SR</b> <b>HBL2330SR</b>			
Gray Valox® semi-flush, two gang.	<b>HBL2310SR2</b> <b>HBL2320SR2</b> <b>HBL2330SR2</b>			

Accessories on page B-54.

<b>Single Flush, Back and Side Wired</b>		<b>IP20 SUITABILITY</b>		
Description	Catalog Numbers			
Black nylon face.	<b>HBL2310</b> <b>HBL2320</b> <b>HBL2330</b>			
Isolated ground, orange nylon face.	<b>IG2310</b> <b>IG2320</b> -			
Corrosion resistant, yellow nylon face.	<b>HBL23CM10</b> -   -			
Ring terminal connection.	<b>HBL2310RT</b> <b>HBL2320RT</b> -			

Accessories on page B-50.




**HBL2320AR**


**Insulgrip Flanged Receptacles**

Description	Catalog Numbers		
Nylon casing, back wired.	<b>HBL2316</b>	<b>HBL2326</b>	<b>HBL2336</b>


Accessories on page B-50.



**HBL2316**



**HBL2310**



**HBL2320SR2**



**HBL2320SR**

Valox® is a trademark of SABIC Innovative Plastics, acquired from General Electric Company.

