

## Straight Blade Devices 20 Ampere, 125/250 Volts and 3Ø 250 Volts AC

3 Pole, 3 Wire Non-Grounding; 3 Pole, 4 Wire Grounding; 4 Pole 4 Wire Non-Grounding  
Receptacles and Plugs



### 20A, 125/250V 3 Pole, 3 Wire Non-Grounding Receptacles and Plugs

**IP20**  
SUITABILITY




20A 125V/250V  
NEMA 10-20R  
UL Listed  
2(1) HP



20A 125V/250V  
NEMA 10-20P  
UL Listed  
2(1) HP

Description	Cord Diameter	Catalog Numbers
Receptacle, black phenolic.	-	<b>HBL6810</b>
Plug, Insulgrip®, nylon.	.385"-.780" (9.8-19.8)	<b>HBL9977C</b>

Notes: Horsepower ratings listed above are AC only.  
Horsepower ratings not in parentheses are phase to phase (208 to 240V AC).  
Those in parentheses are phase to neutral (120V AC).  
See page A-44 for accessories.



**HBL6810**



**HBL9977C**



### 20A, 125/250V 3 Pole, 4 Wire Grounding Receptacles and Plugs

**IP20**  
SUITABILITY




20A 125V/250V  
NEMA 14-20R  
UL CSA  
2(1) HP



20A 125V/250V  
NEMA 14-20P  
UL CSA  
2(1) HP

Description	Cord Diameter	Catalog Numbers
Receptacle, black nylon body, back & side wired.	-	<b>HBL8410</b>
Plug, nylon, angle 4-position.	.390"-.775" (9.9-19.7)	<b>HBL8411C</b>

Note: See page A-44 for accessories.



**HBL8410**



### 20A, 3Ø 250V AC 3 Pole, 4 Wire Grounding Receptacles and Plugs

**IP20**  
SUITABILITY




20A 3Ø 250V AC  
NEMA 15-20R  
UL CSA  
3 HP




20A 3Ø 250V AC  
NEMA 15-20P  
UL CSA  
3 HP

Description	Cord Diameter	Catalog Numbers
Receptacle, black nylon body, back & side wired.	-	<b>HBL8420</b>
Plug, nylon, angle 4-position.	.390"-.775" (9.9-19.7)	<b>HBL8421C</b>

Notes: See page A-44 for accessories.  
Horsepower ratings listed above are AC only.  
Horsepower ratings not in parentheses are phase to phase (208 to 240V AC).  
Horsepower ratings in parentheses are phase to neutral (120V AC).



**HBL8411C**



**HBL8420**



### 20A, 3ØY 120/208V AC 4 Pole, 4 Wire Non-Grounding Receptacles and Plugs

**IP20**  
SUITABILITY




20A 3ØY 120/208V AC  
NEMA 18-20R  
UL Listed  
2 HP



20A 3ØY 120/208V AC  
NEMA 18-20P  
UL Listed  
2 HP

Description	Cord Diameter	Catalog Numbers
Receptacle, black nylon body.	-	<b>HBL7250</b>
Plug, nylon, angle, 4-position.	.390"-.775" (9.9-19.7)	<b>HBL7251C</b>

Notes: Horsepower ratings are phase to phase (208 to 240V AC).  
Weatherproof boots for plugs not available.  
See page A-44 for accessories.



**HBL7250**



**HBL7251C**