


1827236-4 Product Details

Have a Question?

Chat with a Product Information Specialist



Memory Sockets

Always EU RoHS/ELV Compliant ([Statement of Compliance](#))

Product Highlights:

- Socket Type = Memory Card
- Socket Style = SO DIMM
- Gold Flash Contact Plating, Mating Area, Material
- 200 Positions
- DRAM Type = Double Data Rate (DDR) II

[View all Features](#)

1827236-4
(1827236)

TE Internal Number: 1827236-4

Active

[View 3D PDF](#)

[Add to My Part List](#) [Request Sample](#) [Find Similar Products](#) [Buy Product](#)

Quick Links

- ▶ [Check Pricing & Availability](#)
- ▶ [Search for Tooling](#)
- ▶ [Product Feature Selector](#)
- ▶ [Contact Us About This Product](#)

Documentation & Additional Information

Product Drawings:

- [DDR1 & DDR2 SODIMM SOCKET 0.6mm PITCH 200POS LOW PRO...](#) (PDF, English)

Catalog Pages/Data Sheets:

- None Available

Product Specifications:

- [DDR S.O.DIMM Socket 200 Positions](#) (PDF, English)

Application Specifications:

- None Available

Instruction Sheets:

- None Available

CAD Files: ([CAD Format & Compression Information](#))

- [2D Drawing](#) (DXF, Version F)
- [3D Model](#) (IGES, Version F)
- [3D Model](#) (STEP, Version F)

Additional Information:

- [Product Line Information](#)

Related Products:

- [Tooling](#)

[List all Documents](#)

Product Features (Please use the Product Drawing for all design activity)

Product Type Features:

- [Socket Style](#) = SO DIMM
- [DRAM Type](#) = Double Data Rate (DDR) II
- [PCB Mount Style](#) = Surface Mount
- [Module Orientation](#) = Right Angle
- [Profile](#) = Low
- [Comment](#) = Latch direct soldering type.; See drawing for additional product information.

Mechanical Attachment:

- [Keying](#) = Standard

Electrical Characteristics:

- [DRAM Voltage](#) = 1.8 V

Termination Related Features:

- [Solder Tail Contact Plating](#) = Gold Flash over Nickel

Body Related Features:

- [Socket Type](#) = Memory Card
- [Number of Positions](#) = 200
- [Row-to-Row Spacing \(mm \[in\]\)](#) = 5.60 [0.220]
- [Centerline \(mm \[in\]\)](#) = 0.60 [0.024]
- [Number of Rows](#) = Dual
- [Ejector Type](#) = Locking
- [Ejector Location](#) = Both Ends
- [Number of Keys](#) = 1
- [Latch Material](#) = Stainless Steel
- [Latch Plating](#) = Tin
- [Boss](#) = With
- [Mount Type](#) = Printed Circuit Board

Contact Related Features:

- [Contact Plating, Mating Area, Material](#) = Gold Flash
- [Contact Base Material](#) = Copper Alloy

Housing Related Features:

- [Housing Material](#) = High Temperature Thermoplastic
- [UL Flammability Rating](#) = UL 94V-0

Configuration Related Features:

- [Stack Height \(mm \[in\]\)](#) = 4.60 [0.180]
- [Insertion Style](#) = Cam-In
- [Center Key \(mm \[in\]\)](#) = None

Industry Standards:

- [RoHS/ELV Compliance](#) = RoHS compliant, ELV compliant
- [Lead Free Solder Processes](#) = Reflow solder capable to 245°C, Reflow solder capable to 260°C
- [RoHS/ELV Compliance History](#) = Always was RoHS compliant

Operation/Application:

- [Application Type](#) = DDR SDRAM

Packaging Related Features:

- [Packaging Method](#) = Tray

Other:

- [Brand](#) = AMP

BOOKMARK

Corporate Information

[Who We Are](#)
[Investors](#)
[News Room](#)
[Supplier Portal](#)
[Careers](#)

Quick Links

[Check Distributor Inventory](#)
[Cross Reference](#)
[Find Documents & Drawings](#)
[Product Compliance Support Center](#)
[Site Map](#)

Customer Support

[Email or Chat with Us](#)
[Find a Phone Number](#)
[Search Knowledge Base](#)
[Manage Your Account](#)

Sign up for our eNewsletter

Enter your email address

Follow us on: