

Search

Parts

Inventory

[Home](#)[About Us](#)[Jobs](#)[Products](#)**Sharp Microelectronics of the Americas**

- [Product Groups](#)
- [System Solutions](#)
- [Support](#)
- [Where to Buy](#)
- [Press Room](#)
- [Jobs](#)
- [About Us](#)
- [Legal](#)

LH28F640BFHE - PBTL DY Sales and Technical Information

PRODUCT DETAIL INFORMATION	
Attribute Name	Attribute Data
Access Time	90ns ns
Compatible with SHARP MCUs	LH7A4xx, LH754xx, LH7952x
Description	64M,Smart,Bottom Boot Block, 60ns
Device ID	B1H
Family	LH28F640BFHE -PBTL DY
Flash Density	64 Mb
Lead Frame Type	Alloy 42
Life cycle	Sunset
New Part Name	LH28F640BFHE -PBTL70A
Organization	x16
Package Type	48 TSOP
Plating Material	SnPb
Process Size	0.18 μ m
Read Supply Voltage (VCC)	3V
RoHS	Yes
Status	Not for New Design
Supply Style	Dual
Temperature Range	-40C 85C
Type	Bottom Bootblock

DISTRIBUTOR INVENTORY			
Part Number	Distributor	Quantity	Inv. Date
LH28F640BFHE -PBTL DY	NU HORIZONS ELECTRONICS	2409	2/25/2009
LH28F640BFHE -PBTL DY	AVNET ELECTRONICS MARKETING	954	2/25/2009

[Products](#) | [System Solutions](#) | [Support](#) | [Where To Buy](#) | [Press](#)[Privacy Policy](#) | [Sales Terms](#) | [Limited Warranty](#) | [Important Restrictions](#)

© 2009 Sharp Electronics Corporation. All Rights Reserved.