

This document was generated on 05/13/2011

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: 0022	150620	
Status: Activ	<u>150620</u> /e	
Overview: picoflex	(
Description: Picoflex	x® PF-50 IDT-to-IDT, 6 Circuits, 0.20m (7.87") Length	S Service
Documents:		
3D Model	Product Specification PS-99020-0011 (PDF)	
Drawing (PDF)	RoHS Certificate of Compliance (PDF)	Cast 1
		e a son
General		Series
Product Family	Cable Assemblies	image - Reference only
Series	<u>92315</u>	
Connector to Connector	Picoflex® IDT-to-IDT	EU RoHS China RoHS
Overview	picoflex	ELV and RoHS
Product Name	Picoflex®	Compliant
Dhysical		REACH SVHC Contains SVHC: No
Physical		
Cable Length	0.20m (7.87")	Low-Halogen Status
Circuits (Loaded)	6	Not Low-Halogen
Color - Resin	Natural	Need more information on product
Gender Lock to Mating Part	Female-Female None	environmental compliance?
Material - Metal	Phosphor Bronze	
Material - Plating Mating	Tin	Email productcompliance@molex.com
Material - Plating Mating	Tin	For a multiple part number RoHS Certificate of
Material - Resin	Polyester	Compliance, <u>click here</u>
Packaging Type	Bag	Please visit the Contact Us section for any
Pitch - Mating Interface	1.27mm (.050")	non-product compliance questions.
Plating min - Mating	2.032µm (80µ")	
Plating min - Termination	2.032µm (80µ")	
Single Ended	No	
Termination Interface: Style	IDT or Pierce	Search Parts in this Series
Waterproof / Dustproof	No	92315Series
Wire Insulation Diameter	N/A	
Wire Size AWG	28	Mates With
Wire/Cable Type	PVC, Ribbon Cable	Picoflex® PF-50 Header <u>90325</u> , <u>90800</u> , 90779, 90715, 90814
Electrical		<u>30113</u> , <u>30113</u> , <u>30014</u>
Current - Maximum per Contac	t 1.2A	
Shielded	No	
Voltage - Maximum	250V	

Material Info

Reference - Drawing Numbers Product Specification Sales Drawing

PS-99020-0011 SD-92315-001

This document was generated on 05/13/2011 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION