


## T92P11D22-12 Product Details



### T92P11D22-12 (5-1393211-3)

TE Internal Number: 5-1393211-3

Active

[Add to Part List](#)

### Industrial Relays (General Purpose)

Converted to EU RoHS but not ELV Compliant ([Statement of Compliance](#))

#### Product Highlights:

- T92 Series
- Contact Arrangement = 2 Form C, DPDT, 2 C/O
- Contact Current Rating = 30 Amps.
- Monostable Coil Magnetic System
- Without Coil Suppression Diode

[View all Features](#) | [Find Similar Products](#)

### Quick Links

- [Check Pricing & Availability](#)
- [Search for Tooling](#)
- [Product Feature Selector](#)
- [Contact Us About This Product](#)
- [Request Samples](#)

NEW!

### Documentation & Additional Information

#### Product Drawings:

- None Available

#### Catalog Pages/Data Sheets:

- [T92 Two-Pole, 30 Amp, PC Board or Panel Mount Relay](#) (PDF, English)

#### Product Specifications:

- None Available

#### Application Specifications:

- None Available

#### Instruction Sheets:

- None Available

#### CAD Files:

- None Available

#### Additional Information:

- [Product Line Information](#)

#### Additional Product Images:

- [Schematic](#)
- [PCB Layout](#)
- [Wiring Diagram](#)

#### Related Products:

- [Tooling](#)

[List all Documents](#)

### Product Features (Please use the Product Drawing for all design activity)

#### Product Type Features:

- [Termination Type](#) = .250 x .032 Quick Connect Terminals

#### Electrical Characteristics:

- [Contact Current Rating \(Amps.\)](#) = 30
- [Coil Resistance \(Ω\)](#) = 86
- [Actuating System](#) = DC
- [Coil Power, Nominal \(W\)](#) = 1.70
- [Input Voltage \(VDC\)](#) = 12

#### Body Related Features:

- [Series](#) = T92
- Polarized = No

#### Contact Related Features:

- [Mounting Options](#) = Flange Mount
- [Enclosure](#) = Dust Cover
- FCC Part 68 Isolation = No
- Relay Type = PCB
- [Contact Material](#) = Silver Cadmium Oxide
- Approx. Dimensions (L x W x H) (mm [in]) = 52.30 x 34.50 x 30.70 [2.060 x 1.359 x 1.209]
- Wiring Diagram = 2 Form C
- Approved Standards = UL Recognized, CSA Component Acceptance, UL Listed, VDE Component Mark, CSA Certified

#### Configuration Related Features:

- [Contact Arrangement](#) = 2 Form C, DPDT, 2 C/O
- [Coil Magnetic System](#) = Monostable
- [Coil Suppression Diode](#) = Without
- [Coil Selection Criteria](#) = Nominal Voltage
- Coil Latching = Without
- [LED Indicator](#) = Without

#### Industry Standards:

- [RoHS/ELV Compliance](#) = RoHS/Not ELV Compliant
- [Lead Free Solder Processes](#) = Wave solder capable to 240°C, Wave solder capable to 260°C
- RoHS/ELV Compliance History = Converted to comply with RoHS not ELV directives
- Coil Insulation Classification = UL Class F

#### Other:

- Brand = Potter & Brumfield