

QO2L30TTS

LOADCTR QO MLO 120V 30A 1PH 2SP NEMA 1



by Schneider Electric

List Price \$51.00 USD

Availability **Stock Item: This item is normally stocked in our distribution facility.**

Technical Characteristics

Ampere Rating	30A
Approvals	CSA Certified
Application	Designed to meet manufactured housing requirements to protect electrical systems, equipment and people.
Enclosure Type	Indoor
Cover Type	Surface (without door)
Box Number	1
Bus Material	Tin Plated Aluminum
Short Circuit Current Rating	10kA
Maximum Tandem Circuit Breakers	0
Phase	1-Phase
Main Type	Fixed Mains - Lugs
Spaces	2
Enclosure Rating	NEMA 1
Maximum Single Pole Circuits	2
Grounding Bar	Factory Installed
Voltage Rating	120 Vac
Wiring Configuration	2-Wire
Wire Size	#12-10 AWG(Al); #14-10 AWG(Cu)
Ampere Rating	30A
Approvals	CSA Certified
Application	Designed to meet manufactured housing requirements to protect electrical systems, equipment and people.
Enclosure Type	Indoor
Cover Type	Surface (without door)
Box Number	1
Bus Material	Tin Plated Aluminum
Short Circuit Current Rating	10kA
Maximum Tandem Circuit Breakers	0
Phase	1-Phase
Main Type	Fixed Mains - Lugs
Spaces	2
Enclosure Rating	NEMA 1
Maximum Single Pole Circuits	2

Generated: 09/26/2011 01:50:30

Grounding Bar	Factory Installed
Voltage Rating	120 Vac
Wiring Configuration	2-Wire
Wire Size	#12-10 AWG(Al); #14-10 AWG(Cu)

Notes: Will not accept Qwik-Gard QO-GFI circuit breaker.

Shipping and Ordering

Category	00101 - Load Centers, 1 Phase, NEMA1 & 3R, 2 - 8 Circuit, Type QO
Discount Schedule	DE3A
GTIN	00785901785088
Package Quantity	1
Weight	1.92 lbs.
Availability Code	Stock Item: This item is normally stocked in our distribution facility.
Returnability	Y
Country of Origin	MX

As standards, specifications, and designs change from time to time, please ask for confirmation of the information given in this document.