



**TENMA®**

### 72-8710 PRODUCT SPECIFICATIONS

| Feature                         |                                      |
|---------------------------------|--------------------------------------|
| Bandwidth                       | 100 MHz                              |
| Rise Time                       | ≤3.5 ns                              |
| Real-time Sampling Rate         | 1GS/s                                |
| Equivalent Sampling Range       | 50GS/s                               |
| Vertical Sensitivity            | 1mV ~ 20V/div                        |
| Record Length (Max)             | 2 x 600k                             |
| Scan Time Base                  | 2ns ~ 50s/div                        |
| Trigger Type                    | Edge, Pulse, Alternate               |
| Automatic Waveform Measurements | 28                                   |
| Frequency Counter               | 6 digits frequency counter           |
| Ports                           | USB OTG                              |
| Mathematics                     | Add, Subtract, Multiply, Divide, FFT |
| Other Features                  | Special Print Screen Feature         |

### GENERAL CHARACTERISTICS

|                              |   |
|------------------------------|---|
| Power                        | 100 - 240VACRMS, 45Hz -440Hz, CAT II  |
| LCD Size                     | Diagonal 178mm (7 inches)   |
| Product Net Weight           | 2.2kg   |
| Product Size                 | 306mm x 147mm x 122mm   |
| Accessories                  | Probe x 2 (1x, 10x switchable),<br>Power Cord and English Manual<br>UT-D05 USB Cable, PC Communication Software |
| Standard Individual Packing  | Gift Box  |
| Standard Quantity Per Carton | 2 pcs   |
| Standard Carton Measurement  | 445 x 410 x 270mm (0.055 CBM Per Export Carton)   |
| Standard Carton Gross Weight | Around 8.5kg  |

Specifications and other information are subject to change without further notice