




This is issued in strict confidence on condition that it is not used as a basis for manufacture or sale, and that it is not copied, reprinted or disclosed to a third party either wholly or in part without prior written consent of ITT Cannon.



No mounting hardware selected
with 3,05 (.120) mounting hole



A ± 0,38 (.015)	B ± 0,13 (.005)	C ± 0,13 (.005)	D ± 0,13 (.005)	E ± 0,38 (.015)	L ± 0,25 (.010)	W ± 0,41 (.016)	K ± 0,32 (.013)
30,81 (1.213)	16,92 (.666)	24,99 (.984)	8,36 (.329)	12,55 (.494)	0,76 (.030)	6,69 (.264)	1,21 (.048)

9 crimp signal contacts, part number 330-5291-097 kitted with each connector

DESCRIPTION	MATERIAL	FINISH
Insulator	DAP 2 Picoe, (Color White), Copper alloy retention c	
Shells	Steel	Yellow Chromate over Zinc
Signal Contacts	Copper alloy	50 microinches Gold over Nickel
Unless otherwise specified, dimensions are in mm & (in.) Tolerances are (.XXX = mm) Decimals Angles .X ± 0,20 (.008) X° ± 1,0° .XX ± 0,10 (.004) .XXX ± 0,05 (.002)	Issue Date: 26-Aug-99	Cannon ITT Industries
	CONNECTOR, PLUG, ELECTRICAL D-SUBMINIATURE 9 POSITION CRIMP	
	PART NO.	DEMAM9P