


## 2, 4, 5 and 6-Wire M12 eurofast® Receptacles, Front Mount, 1/2-14 NPT Threads

- Male Receptacles
- NEMA 1, 3, 4, 6P
- IEC IP 68 Protection



Drawing Number	Part Number	Lead Specs.	Application	Pinout
<p>7 FS .. /14.5/NPT</p>	FS 4.2-*/14.5/NPT	UL, CSA 2x22 AWG 105°C 250 V 4 A	Mates with 2-pin Cordsets	1. N/C 2. N/C 3. BN 4. BU
	FS 4.22-*/14.5/NPT	UL, CSA 2x22 AWG 105°C 250 V 4 A	Mates with 2-pin Cordsets	1. BN 2. N/C 3. BU 4. N/C
	FS 4.4-*/14.5/NPT	UL, CSA 4x22 AWG 105°C 250 V 4 A	Mates with 4-pin Cordsets	1. BN 2. WH 3. BU 4. BK
	FS 4.4-*/14.5/NPT/S613	UL, CSA 4x18 AWG 105°C 250 V 4 A	Mates with 4-pin Cordsets	1. BN 2. WH 3. BU 4. BK
	FS 4.5-*/14.5/NPT	UL, CSA 5x22 AWG 105°C 250 V, 4 A	Mates with 5-pin Cordsets	1. BN 2. WH 3. BU 4. BK 5. GY
	FS 4.6-*/14.5/NPT	UL, CSA 6x22 AWG 105°C 250 V 4 A	Mates with 6-pin Cordsets	1. BN 2. WH 3. BU 4. BK 5. GY 6. PK
	FS 6-*/14.5/NPT	UL, CSA 6x24 AWG 105°C 60 VAC/75 VDC 2 A	Mates with 6-pin Cordsets	

Receptacles

See page D113 for dimensional drawings.

\* Length in meters. Standard lead length is 0.5 Meters. Consult factory for other lengths. Standard housing material is nickel plated brass "FS."; "FSV.." indicates 316 stainless steel. To specify PVC jacketed cable, add "/S717" to the end of the part number.