





Optical and Mechanical Encoders

**SPECIFICATIONS**

**Electrical Ratings**

Switching Loads: 1.5 mA at 115 Vac, resistive; 150 mA at 14 Vdc, resistive  
 Current Carrying Capacity: 250 mA maximum at 28 Vdc, resistive load  
 Contact Resistance: 75 mΩ, typical  
 Insulation Resistance: 1000 mΩ minimum between terminals  
 Voltage Breakdown: 1000 Vac minimum between terminals  
 Life Expectancy: 100,000 cycles of operation at rated loads. One cycle of operation is a rotation through all of the active positions and a return to the starting position.

**Mechanical Ratings**

Rotational Torque: 2 to 6 in-oz  
 Operating Temperature Range: -40 C° to +85 C°  
 Storage Temperature Range: -65 C° to +85 C°  
 Continuous Rotation: All standard switches are continuous rotation. Desired stop locations supplied upon request.  
 Anti-Rotation Device: Integral non-turn tab, flattened bushing, .375" diameter, .320 double "D" across flats.  
 Termination: Standard is PC style, parallel to shaft, facing rear. Options include PC, parallel to shaft, facing front.  
 Panel Mounting Torque: 10 in-lbs maximum

**Materials and Finishes**

Bushing/Housing and Shaft/Rotor: Reinforced thermoplastic  
 Detent Ball: Stainless steel, nickel-plated  
 Detent Spring: Tinned music wire  
 Contacts: Beryllium copper, gold plate over nickel  
 Terminals: Copper alloy, #725, 100% tin plate over nickel plate  
 Output Board: FR-4, copper/nickel-plated  
 Mounting Nut: Brass, tin/zinc-plated hex nut  
 Mounting Bracket: Stainless Steel, tin-plated

**ORDERING INFORMATION**

25LB10-Q-Z

Series: 25L = Economical, single deck encoder  
 Housing Color: B = Black housing; R = Red housing  
 Angle of Throw: 10 = 10°, 36 positions; 11 = 11.25°, 32 positions;  
 15 = 15°, 24 positions; 18 = 18°, 20 positions;  
 22 = 22.5°, 16 positions; 30 = 30°, 12 positions;  
 45 = 45°, 8 positions

Mounting Bracket: Z = with bracket, Blank = no bracket  
 Code Output: H = Hexadecimal available only in 22.5°  
 G = Gray available only in 22.5°  
 Q = Quadrature (2-bit)

Custom materials, styles, color and markings are available. Custom knobs available.  
 Available from your local Grayhill Distributor. For prices and discounts, contact a local Sales Office, an authorized local Distributor or Grayhill.  
 For custom codes, termination, rotational torque, angles of throw, call Grayhill for more information.