


Capacitor, tantalum, 10 uF, +/-10% Tol, 50V@85C



Dimensions (mm)

Specifications

ID	Dimension	Tolerance	Manufacturer:	KEMET
D	7.34	+/-0.25	Value:	10 uF
L1	17.42	+/-0.79	Voltage DC @ 85C:	50V
L2	20.88	+0	Voltage DC @ 125C:	33V
F	0.64	+/-0.05	Tolerance:	+/-10%
LL	38.1	+/-6.35	Application:	Military ER/General Purpose
			Body Type:	Axial Hermetic ('cs13-style')
			Temperature Range:	-55/+125C
			ESR:	1.6 Ohm
			ESR Frequency @ 25C:	100kHz
			Leakage Current:	2.5 uA
			Dissipation Factor:	4%
			Package Kind:	Bulk
			Package Type:	Tray

Notes:

-Dimensions include insulating sleve (standard)

-(



Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.