

# Tiny Micropower Precision Series References in 2mm × 2mm DFN

## FEATURES

- No Output Capacitor Required
- Low Drift: 20ppm/°C Max
- High Accuracy: 0.2% Max
- Low Supply Current
- 20mA Output Current Guaranteed
- Reverse-Battery Protection
- Low IR Reflow Induced Stress: 0.02% Typ
- Voltage Options: 2.5V, 3V, 3.3V, 5V and 10V
- Space-Saving Alternative to the LT1460
- 3-Lead 2mm × 2mm × 0.75mm DFN Package

## APPLICATIONS

- Handheld Instruments
- Precision Regulators
- A/D and D/A Converters
- Power Supplies
- Hard Disk Drives
- Sensor Modules



## DESCRIPTION

The LT<sup>®</sup>6660 is a family of micropower series references that combine high accuracy and low drift with low power dissipation and extremely small package size. These series references use curvature compensation to obtain low temperature coefficient, and laser trimmed precision thin-film resistors to achieve high output accuracy. The LT6660 will supply up to 20mA with excellent line regulation characteristics, making it ideal for precision regulator applications.

The LT6660 family of series references provide supply current and power dissipation advantages over shunt references that must idle the entire load current to operate. Additionally, the LT6660 does not require an output compensation capacitor. This feature is important in applications where PC board space is a premium, fast settling is demanded, or total capacitance must be kept to a minimum, as in intrinsic safety applications. Reverse-battery protection keeps these references from conducting reverse current.

**LT**, LT, LTC and LTM are registered trademarks of Linear Technology Corporation. All other trademarks are the property of their respective owners.

## TYPICAL APPLICATION




## ABSOLUTE MAXIMUM RATINGS

(Note 1)

|   |             |  |                |
|---|-------------|--|----------------|
| Input Voltage.....  | 30V         | Operating Temperature Range                |                |
| Reverse Voltage .....   | -15V        | (Note 2) .....                             | -40°C to 85°C  |
| Output Short-Circuit Duration, $T_A = 25^\circ\text{C}$ ..... | 5 sec       | Storage Temperature Range (Note 3).....    | -65°C to 150°C |
| Specified Temperature Range .....                             | 0°C to 70°C | Lead Temperature (Soldering, 10 sec) ..... | 300°C          |

## PACKAGE/ORDER INFORMATION

| <p style="text-align: center;">TOP VIEW</p>  <p style="text-align: center;">DC PACKAGE<br/>3-LEAD (2mm × 2mm) PLASTIC DFN<br/><math>T_{JMAX} = 125^\circ\text{C}</math>, <math>\theta_{JA} = 102^\circ\text{C/W}</math><br/>EXPOSED PAD IS GND, MUST BE SOLDERED TO PCB</p> | ORDER PART NUMBER | DFN PART MARKING* |
|--|-------------------|-------------------|
|  | LT6660HCDC-2.5    | LBXN              |
|  | LT6660JCDC-2.5    | LBXN              |
|  | LT6660KCDC-2.5    | LBXN              |
|  | LT6660HCDC-3      | LBVY              |
|  | LT6660JCDC-3      | LBVY              |
|  | LT6660KCDC-3      | LBVY              |
|  | LT6660HCDC-3.3    | LBYW              |
|  | LT6660JCDC-3.3    | LBYW              |
|  | LT6660KCDC-3.3    | LBYW              |
|  | LT6660HCDC-5      | LBYT              |
|  | LT6660JCDC-5      | LBYT              |
|  | LT6660KCDC-5      | LBYT              |
|  | LT6660HCDC-10     | LBXY              |
|  | LT6660JCDC-10     | LBXY              |
| LT6660KCDC-10  | LBXY              |                   |
| <p><b>Order Options</b> Tape and Reel: Add #TR<br/>Lead Free: Add #PBF Lead Free Tape and Reel: Add #TRPBF<br/>Lead Free Part Marking: <a href="http://www.linear.com/leadfree/">http://www.linear.com/leadfree/</a></p>   |                   |                   |

Consult LTC Marketing for parts specified with wider operating temperature ranges. \*The temperature grade is identified by a label on the shipping container.

## AVAILABLE OPTIONS

| OUTPUT VOLTAGE (V) | SPECIFIED TEMPERATURE RANGE | ACCURACY (%) | TEMPERATURE COEFFICIENT (ppm/°C) | PART ORDER NUMBER |
|--------------------|-----------------------------|--------------|----------------------------------|-------------------|
| 2.5                | 0°C to 70°C                 | 0.2          | 20                               | LT6660HCDC-2.5    |
| 2.5                | 0°C to 70°C                 | 0.4          | 20                               | LT6660JCDC-2.5    |
| 2.5                | 0°C to 70°C                 | 0.5          | 50                               | LT6660KCDC-2.5    |
| 3                  | 0°C to 70°C                 | 0.2          | 20                               | LT6660HCDC-3      |
| 3                  | 0°C to 70°C                 | 0.4          | 20                               | LT6660JCDC-3      |
| 3                  | 0°C to 70°C                 | 0.5          | 50                               | LT6660KCDC-3      |
| 3.3                | 0°C to 70°C                 | 0.2          | 20                               | LT6660HCDC-3.3    |
| 3.3                | 0°C to 70°C                 | 0.4          | 20                               | LT6660JCDC-3.3    |
| 3.3                | 0°C to 70°C                 | 0.5          | 50                               | LT6660KCDC-3.3    |

## AVAILABLE OPTIONS

| OUTPUT VOLTAGE (V) | SPECIFIED TEMPERATURE RANGE | ACCURACY (%) | TEMPERATURE COEFFICIENT (ppm/°C) | PART ORDER NUMBER |
|--------------------|-----------------------------|--------------|----------------------------------|-------------------|
| 5                  | 0°C to 70°C                 | 0.2          | 20                               | LT6660HCDC-5      |
| 5                  | 0°C to 70°C                 | 0.4          | 20                               | LT6660JCDC-5      |
| 5                  | 0°C to 70°C                 | 0.5          | 50                               | LT6660KCDC-5      |
| 10                 | 0°C to 70°C                 | 0.2          | 20                               | LT6660HCDC-10     |
| 10                 | 0°C to 70°C                 | 0.4          | 20                               | LT6660JCDC-10     |
| 10                 | 0°C to 70°C                 | 0.5          | 50                               | LT6660KCDC-10     |

## ELECTRICAL CHARACTERISTICS

The ● denotes the specifications which apply over the full operating temperature range, otherwise specifications are at  $T_A = 25^\circ\text{C}$ .  $V_{IN} = V_{OUT} + 2.5\text{V}$ ,  $I_{OUT} = 0$  unless otherwise specified.

| PARAMETER                                       | CONDITIONS   | MIN  | TYP  | MAX          | UNITS                          |
|---|--|------|------|--------------|--------------------------------|
| Output Voltage Tolerance                        | LT6660HCDC   | -0.2 |      | 0.2          | %                              |
|   | LT6660JCDC   | -0.4 |      | 0.4          | %                              |
|   | LT6660KCDC   | -0.5 |      | 0.5          | %                              |
| Output Voltage Temperature Coefficient (Note 4) | LT6660HCDC ●   |      | 10   | 20           | ppm/°C                         |
|   | LT6660JCDC ●   |      | 10   | 20           | ppm/°C                         |
|   | LT6660KCDC ●   |      | 25   | 50           | ppm/°C                         |
| Line Regulation                                 | $V_{OUT} + 0.9\text{V} \leq V_{IN} \leq V_{OUT} + 2.5\text{V}$ ●             |      | 150  | 800<br>1000  | ppm/V<br>ppm/V                 |
|   | $V_{OUT} + 2.5\text{V} \leq V_{IN} \leq 20\text{V}$ ●                        |      | 50   | 100<br>130   | ppm/V<br>ppm/V                 |
| Load Regulation Sourcing (Note 5)               | $I_{OUT} = 100\mu\text{A}$ ●   |      | 1000 | 3000<br>4000 | ppm/mA<br>ppm/mA               |
|   | $I_{OUT} = 10\text{mA}$ ●  |      | 50   | 200<br>300   | ppm/mA<br>ppm/mA               |
|   | $I_{OUT} = 20\text{mA}$ ●  |      | 20   | 70<br>100    | ppm/mA<br>ppm/mA               |
| Thermal Regulation (Note 6)                     | $\Delta P = 200\text{mW}$  |      | 2.5  | 10           | ppm/mW                         |
| Dropout Voltage (Note 7)                        | $V_{IN} - V_{OUT}$ , $\Delta V_{OUT} \leq 0.2\%$ , $I_{OUT} = 0$ ●           |      |      | 0.9          | V                              |
|   | $V_{IN} - V_{OUT}$ , $\Delta V_{OUT} \leq 0.2\%$ , $I_{OUT} = 10\text{mA}$ ● |      |      | 1.3<br>1.4   | V<br>V                         |
| Output Current                                  | Short $V_{OUT}$ to GND   |      | 40   |              | mA                             |
| Reverse Leakage                                 | $V_{IN} = -15\text{V}$ ●   |      | 0.5  | 10           | $\mu\text{A}$                  |
| Output Voltage Noise (Note 8)                   | $0.1\text{Hz} \leq f \leq 10\text{Hz}$                                       |      | 4    |              | ppm (P-P)                      |
|   | $10\text{Hz} \leq f \leq 1\text{kHz}$  |      | 4    |              | ppm (RMS)                      |
| Long-Term Stability of Output Voltage (Note 9)  |  |      | 100  |              | ppm/ $\sqrt{\text{kHr}}$       |
| Hysteresis (Note 10)                            | $\Delta T = 0^\circ\text{C}$ to $70^\circ\text{C}$ ●                         |      | 50   |              | ppm                            |
|   | $\Delta T = -40^\circ\text{C}$ to $85^\circ\text{C}$ ●                       |      | 250  |              | ppm                            |
| Supply Current                                  | LT6660-2.5 ●   |      | 115  | 145<br>175   | $\mu\text{A}$<br>$\mu\text{A}$ |
|   | LT6660-3 ●   |      | 145  | 180<br>220   | $\mu\text{A}$<br>$\mu\text{A}$ |
|   | LT6660-3.3 ●   |      | 145  | 180<br>220   | $\mu\text{A}$<br>$\mu\text{A}$ |
|   | LT6660-5 ●   |      | 160  | 200<br>240   | $\mu\text{A}$<br>$\mu\text{A}$ |
|   | LT6660-10 ●  |      | 215  | 270<br>350   | $\mu\text{A}$<br>$\mu\text{A}$ |

## ELECTRICAL CHARACTERISTICS

**Note 1:** Stresses beyond those listed under Absolute Maximum Ratings may cause permanent damage to the device. Exposure to any Absolute Maximum Rating condition for extended periods may affect device reliability and lifetime.

**Note 2:** The LT6660 is guaranteed functional over the operating temperature range of  $-40^{\circ}\text{C}$  to  $85^{\circ}\text{C}$ .

**Note 3:** If the parts are stored outside of the specified temperature range, the output may shift due to hysteresis.

**Note 4:** Temperature coefficient is measured by dividing the change in output voltage by the specified temperature range. Incremental slope is also measured at  $25^{\circ}\text{C}$ .

**Note 5:** Load regulation is measured on a pulse basis from no load to the specified load current. Output changes due to die temperature change must be taken into account separately.

**Note 6:** Thermal regulation is caused by die temperature gradients created by load current or input voltage changes. This effect must be added to normal line or load regulation. This parameter is not 100% tested.

**Note 7:** Excludes load regulation errors.

**Note 8:** Peak-to-peak noise is measured with a single pole highpass filter at 0.1Hz and 2-pole lowpass filter at 10Hz. The unit is enclosed in a still-air environment to eliminate thermocouple effects on the leads. The test time

is 10 sec. RMS noise is measured with a single pole highpass filter at 10Hz and a 2-pole lowpass filter at 1kHz. The resulting output is full wave rectified and then integrated for a fixed period, making the final reading an average as opposed to RMS. A correction factor of 1.1 is used to convert from average to RMS and a second correction of 0.88 is used to correct for the nonideal bandpass of the filters.


**Note 9:** Long-term stability typically has a logarithmic characteristic and therefore, changes after 1000 hours tend to be much smaller than before that time. Total drift in the second thousand hours is normally less than one third that of the first thousand hours with a continuing trend toward reduced drift with time. Long-term stability will also be affected by differential stresses between the IC and the board material created during board assembly.

**Note 10:** Hysteresis in output voltage is created by package stress that differs depending on whether the IC was previously at a higher or lower temperature. Output voltage is always measured at  $25^{\circ}\text{C}$ , but the IC is cycled to  $70^{\circ}\text{C}$  or  $0^{\circ}\text{C}$  before successive measurements. Hysteresis is roughly proportional to the square of the temperature change. For instruments that are stored at well-controlled temperatures (within 20 or 30 degrees of operational temperature) hysteresis is not a problem.

## TYPICAL PERFORMANCE CHARACTERISTICS


Characteristic curves are similar for all voltage options of the LT6660. Curves from the LT6660-2.5 and the LT6660-10 represent the extremes of the voltage options. Characteristic curves for other output voltages fall between these curves, and can be estimated based on their voltage output.

**2.5V Minimum Input-Output Voltage Differential**




6660 G01

**2.5V Load Regulation, Sourcing**



6660 G02


**2.5V Load Regulation, Sinking**



6660 G03


**TYPICAL PERFORMANCE CHARACTERISTICS** Characteristic curves are similar for all voltage options of the LT6660. Curves from the LT6660-2.5 and the LT6660-10 represent the extremes of the voltage options. Characteristic curves for other output voltages fall between these curves, and can be estimated based on their voltage output.

**2.5V Output Voltage Temperature Drift**




6660 G04

**2.5V Supply Current vs Input Voltage**




6660 G05

**2.5V Line Regulation**




6660 G06

**2.5V Power Supply Rejection Ratio vs Frequency**




6660 G07

**2.5V Output Impedance vs Frequency**




6660 G08

**2.5V Transient Response**




6660 G09

**2.5V Output Voltage Noise Spectrum**



6660 G10

**2.5V Output Noise 0.1Hz to 10Hz**




6660 G11

## TYPICAL PERFORMANCE CHARACTERISTICS


Characteristic curves are similar for all voltage options of the LT6660. Curves from the LT6660-2.5 and the LT6660-10 represent the extremes of the voltage options. Characteristic curves for other output voltages fall between these curves, and can be estimated based on their voltage output.

**10V Minimum Input-Output Voltage Differential**




6660 G12

**10V Load Regulation, Sourcing**




6660 G13

**10V Load Regulation, Sinking**




6660 G14

**10V Output Voltage Temperature Drift**




6660 G15

**10V Supply Current vs Input Voltage**



6660 G16


**10V Line Regulation**




6660 G17

**TYPICAL PERFORMANCE CHARACTERISTICS** Characteristic curves are similar for all voltage options of the LT6660. Curves from the LT6660-2.5 and the LT6660-10 represent the extremes of the voltage options. Characteristic curves for other output voltages fall between these curves, and can be estimated based on their voltage output.


**10V Power Supply Rejection Ratio vs Frequency**




**10V Output Impedance vs Frequency**




**10V Transient Response**



**10V Output Voltage Noise Spectrum**



**10V Output Noise 0.1Hz to 10Hz**



## APPLICATIONS INFORMATION

### Longer Battery Life

Series references have a large advantage over older shunt style references. Shunt references require a resistor from the power supply to operate. This resistor must be chosen to supply the maximum current that can ever be demanded by the circuit being regulated. When the circuit being controlled is not operating at this maximum current, the shunt reference must always sink this current, resulting in high dissipation and short battery life.

The LT6660 series references do not require a current setting resistor and can operate with any supply voltage from  $V_{OUT} + 0.9V$  to 20V. When the circuitry being regulated does not demand current, the LT6660s reduce their dissipation and battery life is extended. If the references are not delivering load current, they dissipate only several mW, yet the same connection can deliver 20mA of load current when demanded.

### Capacitive Loads

The LT6660 family of references are designed to be stable with a large range of capacitive loads. With no capacitive load, these references are ideal for fast settling or applications where PC board space is a premium. The test circuit shown in Figure 1 is used to measure the response time and stability of various load currents and load capacitors. This circuit is set for the 2.5V option. For other voltage options, the input voltage must be scaled up and the output voltage generator offset voltage must be adjusted. The 1V step from 2.5V to 1.5V produces a current step of 10mA or 1mA for  $R_L = 100\Omega$  or  $R_L = 1k$ . Figure 2 shows the response of the reference to these 1mA and 10mA load steps with no load capacitance, and Figure 3 shows a 1mA and 10mA load step with a  $0.1\mu F$  output capacitor. Figure 4 shows the response to a 1mA load step with  $C_L = 1\mu F$  and  $4.7\mu F$ .




Figure 1. Response Time Test Circuit




Figure 2.  $C_L = 0\mu F$




Figure 3.  $C_L = 0.1\mu F$




Figure 4.  $I_{OUT} = 1mA$



## APPLICATIONS INFORMATION


Table 1 gives the maximum output capacitance for various load currents and output voltages to avoid instability. Load capacitors with low ESR (effective series resistance) cause more ringing than capacitors with higher ESR such as polarized aluminum or tantalum capacitors.

**Table 1. Maximum Output Capacitance**

| VOLTAGE OPTION | I <sub>OUT</sub> = 100μA | I <sub>OUT</sub> = 1mA | I <sub>OUT</sub> = 10mA | I <sub>OUT</sub> = 20mA |
|----------------|--------------------------|------------------------|-------------------------|-------------------------|
| 2.5V           | >10μF                    | >10μF                  | 2μF                     | 0.68μF                  |
| 3V             | >10μF                    | >10μF                  | 2μF                     | 0.68μF                  |
| 3.3V           | >10μF                    | >10μF                  | 1μF                     | 0.68μF                  |
| 5V             | >10μF                    | >10μF                  | 1μF                     | 0.68μF                  |
| 10V            | >10μF                    | 1μF                    | 0.15μF                  | 0.1μF                   |

### Long-Term Drift

**Long-term drift cannot be extrapolated from accelerated high temperature testing. This erroneous technique gives drift numbers that are wildly optimistic. The only way long-term drift can be determined is to measure it over the time interval of interest.** The LT6660 long-term drift data was taken on over 100 parts that were soldered into PC boards similar to a “real world” application. The boards were then placed into a constant temperature oven with T<sub>A</sub> = 30°C, their outputs were scanned regularly and measured with an 8.5 digit DVM. Figure 5 shows typical long-term drift of the LT6660s.




**Figure 5. Typical Long-Term Drift**

### Hysteresis


Hysteresis data shown in Figure 6 and Figure 7 represents the worst-case data taken on parts from 0°C to 70°C and from -40°C to 85°C. The output is capable of dissipating relatively high power, i.e., for the LT6660-2.5, P<sub>D</sub> = 17.5V • 20mA = 350mW. The thermal resistance of the DFN package is 102°C/W and this dissipation causes a 36°C internal rise. This elevated temperature may cause the output to shift due to thermal hysteresis. **For highest performance in precision applications, do not let the LT6660’s junction temperature exceed 85°C.**

### Input Capacitance

It is recommended that a 0.1μF or larger capacitor be added to the input pin of the LT6660. This can help with stability when large load currents are demanded.



**Figure 6. 0°C to 70°C Hysteresis**



**Figure 7. -40°C to 85°C Hysteresis**

## APPLICATIONS INFORMATION

### Output Accuracy

Like all references, either series or shunt, the error budget of the LT6660s is made up of primarily three components: initial accuracy, temperature coefficient and load regulation. Line regulation is neglected because it typically contributes only 150ppm/V. The LT6660s typically shift 0.02% when soldered into a PCB, so this is also neglected. The output errors are calculated as follows for a 100µA load and 0°C to 70°C temperature range:

LT6660HCDC

Initial Accuracy = 0.2%

For  $I_{OUT} = 100\mu\text{A}$

$$\Delta V_{OUT} = (4000\text{ppm/mA})(0.1\text{mA}) = 0.04\%$$

For Temperature 0°C to 70°C the maximum  $\Delta T = 70^\circ\text{C}$

$$\Delta V_{OUT} = (20\text{ppm}/^\circ\text{C})(70^\circ\text{C}) = 0.14\%$$

Total worst-case output error is:

$$0.2\% + 0.04\% + 0.14\% = 0.380\%$$


Table 2 gives the worst-case accuracy for LT6660HC, LT6660JC and LT6660KC from 0°C to 70°C, and shows that if the LT6660HC is used as a reference instead of a regulator, it is capable of 8 bits of absolute accuracy over temperature without a system calibration.

**Table 2. Worst-Case Output Accuracy over Temperature**


| $I_{OUT}$ | LT6660HCDC | LT6660JCDC | LT6660KDC |
|-----------|------------|------------|-----------|
| 0µA       | 0.340%     | 0.540%     | 0.850%    |
| 100µA     | 0.380%     | 0.580%     | 0.890%    |
| 10mA      | 0.640%     | 0.840%     | 1.15%     |
| 20mA      | 0.540%     | 0.740%     | 1.05%     |

# PACKAGE DESCRIPTION

**DC Package**  
**3-Lead Plastic DFN (2mm × 2mm)**  
 (Reference LTC DWG # 05-08-1717 Rev 0)



RECOMMENDED SOLDER PAD PITCH AND DIMENSIONS




NOTE:

1. DRAWING TO BE MADE A JEDEC PACKAGE OUTLINE M0-229 VARIATION OF (W-TBD)
2. DRAWING NOT TO SCALE
3. ALL DIMENSIONS ARE IN MILLIMETERS
4. DIMENSIONS OF EXPOSED PAD ON BOTTOM OF PACKAGE DO NOT INCLUDE MOLD FLASH. MOLD FLASH, IF PRESENT, SHALL NOT EXCEED 0.15mm ON ANY SIDE
5. EXPOSED PAD SHALL BE SOLDER PLATED
6. SHADED AREA IS ONLY A REFERENCE FOR PIN 1 LOCATION ON THE TOP AND BOTTOM OF PACKAGE

## TYPICAL APPLICATION

### Handling Higher Load Currents




\*SELECT R1 TO DELIVER 80% OF TYPICAL LOAD CURRENT. LT6660 WILL THEN SOURCE AS NECESSARY TO MAINTAIN PROPER OUTPUT. DO NOT REMOVE LOAD AS OUTPUT WILL BE DRIVEN UNREGULATED HIGH. LINE REGULATION IS DEGRADED IN THIS APPLICATION

$$R1 = \frac{V^+ - V_{OUT}}{40mA}$$


6660 TA02

### Boosted Output Current with No Current Limit



6660 TA03

### Boosted Output Current with Current Limit



6660 TA04

## RELATED PARTS

| PART NUMBER | DESCRIPTION   | COMMENTS  |
|-------------|---|---|
| LT1019      | Precision Bandgap Reference                             | 0.05% Max, 5ppm/°C Max                              |
| LT1027      | Precision 5V Reference                                  | 0.02%, 2ppm/°C Max                                  |
| LT1236      | Precision Low Noise Reference                           | 0.05% Max, 5ppm/°C Max, SO Package                  |
| LT1460      | Micropower Series References                            | 0.075% Max, 10ppm/°C Max, 20mA Output Current       |
| LT1461      | Micropower Precision Low Dropout                        | 0.04% Max, 3ppm/°C Max, 50mA Output Current         |
| LT1634      | Micropower Precision Shunt Reference 1.25V, 2.5V Output | 0.05%, 25ppm/°C Max                                 |
| LT1790      | Micropower Precision Series References                  | 0.05% Max, 10ppm/°C Max, 60µA Supply, SOT23 Package |
| LTC®1798    | Micropower Low Dropout Reference, Fixed or Adjustable   | 0.15% Max, 40ppm/°C, 6.5µA Max Supply Current       |