
Bench Kits, Rack Mount Kits



Model 2000-Benchkit: Benchtop Restore Kit. Rubber feet and carrying handles are removed during rack mounting. These items can be used with any of the following models to convert it back to benchtop instrument.


For use with: 428-PROG, Series 2000, 2182A, Series 2300, Series 2400, Series 2500, 2700, 2701, 6220, 6221, 6430, 6485, 6487, 6514, 6517A, 6517B, 7001, Series 2600, Series 2600A



Model 248-RMK-* Fixed Rack Mount Kit: Enables rack mounting of Model 248. 248-RMK-1 rack mounts one Model 248. 248-RMK-2 (not pictured) rack mounts two Model 248s side by side.

For use with: 248

Bench kits. rack mount kits



Model 1938 Fixed Rack Mount Kit: Consists of two flanged brackets and hardware for mounting the Model 237 in a standard 48.3cm 19 in) equipment cabinet. Can be used with Models 8000, 8000-10, or 8000-14. 89mm (3¹/₂ in) height.

www.keithley.com

For use with: 237

ACCESSORIES

1.888.KEITHLEY (U.S. only)

SELECTOR GUIDE: RACK MOUNT KITS

Instrumen	t		Single Fixed	Single Slide ¹	Dual Fixed	Type of Mount
428-PROG Series 2000 2182A Series 2300 Series 2500	2700 2701 6220 6221 6485	6487 6514 6517A 6517B 7001	4288-1		$\begin{array}{c} 4288 \cdot 2^2 \\ 4288 \cdot 4^3 \\ 4288 \cdot 5^4 \\ 4288 \cdot 9^4 \end{array}$	Side Shelf Shelf Shelf
Series 2100	Series 2400	6430	4299-3		4299-4	Side
Series 2600	Series 2600A		4299-1		4299-2	Side
2750			4288-7			Rear bracket
Series 3700			4288-10			Rear bracket
237			1938	1939		Bracket w/handles
248			248-RMK-1		248-RMK-2	Side
707A			Included	7079		Side
708A			Included			Side
4200-SCS/C or /F			4200-RM			
7002			7002-RMK-1	7002-RMK-2		Bracket w/handles

NOTES

1. Slide rack mount kits are not compatible with equipment cabinet Models 8000-10, 8000-14, and 8000-17.

2. Model 4288-2 mounts any two of the listed models, except 776.

3. Model 4288-4 mounts: ANY ONE plus ANY ONE

230, 230-1 428-PROG, 486, 487, Series 2000, 2182A, Series 2300, Series 2400, Series 2500, 2700, 2701, 6220, 6221, 6430, 6485, 6487, 6514, 6517A, 6517B, 7001

4. Models 4288-5 and 4288-9 mount any one or two of the listed models on a shelf-type mount.



Model 1939 Slide Rack Mount Kit: Consists of two sets of flanged brackets, equipment slides, and hardware for mounting the Model 237 in a standard 48.3cm (19 in) equipment cabinet. Can be used with Model 8000. 89mm (31/4 in) height.

For use with: 237




Model 4200-KEY-RM: Rack mount kit for cabinet mounting of standard keyboard and pointing devices.

For use with: 4200-SCS



Model 4200-RM: Fixed rack mount kit for cabinet mounting of the 4200-SCS.

For use with: 4200-SCS



Model 4288-1 Fixed Rack Mount Kit: Singleunit rack mount kit. Height: 88mm (3¹/₂ in).

For use with: See Selector Guide.



Rack Mount Kits



Model 4288-2 Fixed Rack Mount Kit: Height: 88mm (3¹/₂ in).

For use with: See Selector Guide.




Model 4288-4 Fixed Rack Mount Kit: Enables rack mounting of one Model 220, 224, 230, 263, or 595 next to one 428-PROG, 486, 487, 776, Series 2000, 2182A, Series 2300, Series 2400, Series 2600, 2700, 2701, 6220, 6221, 6514, 6485, 6487, 6517A, 6517B, or 7001.

For use with: See Selector Guide.



Model 4288-5 Fixed Rack Mount Kit: The single- and dual-instrument front panels included enable rack mounting of either one or two 3½-inch instruments. Height: 132mm (5¼ in). Depth: 457mm(18 in).

For use with: See Selector Guide.



Model 4288-7 Rear Support Mount Kit: For rack mount applications where more than one or two card modules are installed to provide added support for the rear of the mainframe. Note that front rack mounting hardware is supplied with the Model 2750 mainframe. 88mm (3.5 in) height.

For use with: 2750, System 46, System 46T



Model 4288-9 Fixed Rack Mount Kit: Shelf style rack mount kit with single- and dualinstrument front plates provided. Also included are extended rear support brackets and hardware for installation.

For use with: See Selector Guide.




Model 4288-10 Rear Support Mount Kit: For rack mount applications where more than one or two card modules are installed to provide added support for the rear of the mainframe. Note that front rack mounting hardware is supplied with the Model 3706 mainframe. 88mm (3.5 in) height.

For use with: 3706, 3706-NFP, 3706-S, 3706-SNFP



Model 4299-1: Heavy duty, single rack mount kit with front and rear support. Height: 88mm (3.5 in).

For use with: Series 2600, Series 2600A



Model 4299-2: Heavy duty, dual rack mount kit with front and rear support. Height: 88mm (3.5 in).

For use with: Series 2600, Series 2600A



Rack mount kits

ACCESSORIES

1.888.KEITHLEY (U.S. only) www.keithley.com

Rack Mount Kits



Model 4299-3 Universal Single Unit Rack Mount Kit: Includes all required hardware to rack mount a single Keithley or Agilent half rack instrument using front panel only mounting into a standard 19 inch equipment rack. Not compatible with Series 2600A. 88mm (3.5 in) height.

For use with: Half rack instruments (excluding Series 2600 and Series 2600A)



Model 4299-4 Universal Dual Unit Rack Mount Kit: Includes all required hardware to rack mount two Keithley and/or Agilent half rack instruments together using front panel only mounting into a standard 19 inch equipment rack. Not compatible with Series 2600. 88mm (3.5 in) height.

For use with: Half rack instruments (excluding Series 2600 and Series 2600A)




Model 4299-5: 1U vent panel. For use with: Series 2600A




Model 7002-RMK-1 Fixed Rack Mount Kit: Two 7 in. flanged brackets and hardware for mounting the Model 7002 in a standard 48.3cm (19 in) equipment cabinet. Can be used with Models 8000, 8000-10, 8000-14, or 8000-17.

For use with: 7002




Model 7002-RMK-2 Slide Rack Mount Kit: Two sets of flanged brackets, slides, and hardware to mount Model 7002 in standard 48.3cm (19 in) equipment cabinet. Can be used with Model 8000.

For use with: 7002



Model 7079 Slide Rack Mount Kit: Two sets of flanged brackets, slides, and hardware to mount Model 707A in standard 48.3cm (19 in) equipment cabinet. Can be used with Model 8000.

For use with: 707A, 707B



Model 7768: Single fixed rack kit for mounting Model 776. Height: 88mm (3¹/₂ in).

For use with: 776

Rack mount kits





Cabinets, Other Accessories

Cabinets



Model 8000: A 28-inch high equipment cabinet that is open on both ends. It accepts all Keithley rack mounting kits as well as most rack kits provided with other instrumentation. The dark brown 8000 comes fully assembled, with handles permanently installed on each side. One hundred chrome Phillips head screws with mylar washers and clip nuts are provided for instrument mounting. Rack mounting kits are available separately.

DIMENSIONS: 711mm high \times 483mm wide \times 533mm deep (28 in \times 19 in \times 21 in).



Model 8000-10: A standard 10-inch high, 19-inch wide equipment cabinet for enclosing instrumentation for bench or automated test system application. The Model 8000-10 accepts most Keithley mainframe models and fixed rack mount kits. The cabinet is supplied with rubber feet for benchtop applications, and the sturdy steel construction will support additional instrumentation stacked on top.

DIMENSIONS: 254mm high \times 483mm wide \times 533mm deep (10 in \times 19 in \times 21 in).



Model 8000-14A: A standard 14-inch high, 19-inch wide equipment cabinet for enclosing instrumentation for bench or automated test system application. The Model 8000-14A accepts all Keithley mainframe models and fixed rack mount kits. The cabinet is supplied with rubber feet for benchtop applications including enclosure of the 707B Switching Matrix, and the sturdy steel construction will support additional instrumentation stacked on top.

DIMENSIONS: 356mm high \times 483mm wide \times 648mm deep (14 in \times 19 in \times 25.5 in).



Model 8000-17A: A standard 17-inch high, 19-inch wide equipment cabinet for enclosing instrumentation for bench or automated test system application. The Model 8000-17A accepts all Keithley mainframe models and fixed rack mount kits. The cabinet is supplied with rubber feet for benchtop applications including enclosure of the 707B Switching Matrix, and the sturdy steel construction will support additional instrumentation stacked on top.

DIMENSIONS: 444mm high \times 483mm wide \times 457mm deep (17¹/₂ in \times 19 in \times 18 in).

Remote PreAmp Mounting Accessories



Model 4200-MAG-BASE: Magnetic base for mounting the Model 4200-PA remote PreAmp option onto a probe station platen. (Two included with 4200-PIV-A to mount the remote bias tees onto a prober platen.)

For use with: 4200-SCS

Model 4200-TMB: Triax mounting bracket for mounting the Model 4200-PA remote PreAmp option onto a probe station or onto the triax mounting panel of a text fixture.

For use with: 4200-SCS



Model 4200-VAC-BASE: Vacuum base for mounting the Model 4200-PA remote PreAmp option onto a probe station platen.

For use with: 4200-SCS





Other Accessories

Carrying Case



ACCESSORIES

Model 4200-CASE: Transport case for 4200-SCS.

For use with: 4200-SCS

Power Splitter



Model EM-50A: Modified power splitter For use with: 4200-PIV-A

Computer Accessories Keyboard



Model EM-23B: Keyboard with integrated trackball mouse.

For use with: 4200-SCS

Monitors



Model 4200-FPD-RM: High resolution, 1U (17 inch) TFT display with keyboard and trackball pointing device. Includes 4200-KEY-RM slide rack mounting kit as well as cables and accessories to connect directly to embedded KPXI controllers or the Model 4200-SCS. **Note:** Unit is not CE marked for sale in EEC countries.

For use with: 4200-SCS

Mouse



Model 4200-MOUSE: Microsoft ambidextrous 2 button mouse (Note: a pointing device is integrated with the 4200-SCS keyboard.)

For use with: 4200-SCS

Other Accessories



Model 4200-CART: This roll-around cart for the 4200-SCS is 1.5m (60.7 in) high, 0.7m (27.4 in) wide, and 0.73m (28.8 in) deep. **For use with: 4200-SCS**

