


Capacitor, ceramic, 0.1 uF, +/-10% Tol, 50V, BX, Lead Spacing=0.2"



Dimensions (in)

Specifications

ID	Dimension	Tolerance	Manufacturer:	KEMET
W	0.09	+/-0.01	Capacitance:	0.1 uF
Н	0.19	+0.01/-0.055	Lead Spacing:	0.2"
L	0.19	+/-0.01	Voltage:	50V
S	0.2	+/-0.03	Temperature Coefficient:	BX
LL	1.25	min	Tolerance:	+/-10%
F	0.025	+0.004/-0.002	Body Type:	Radial Molded
K	0.2	nom	Lead Type:	Standard Leads
G	0.045	max	Lead Form:	Hockey Stick
			Package Kind:	Bulk
			Package Type:	Bag
			Package Quantity:	100

Notes:

- -Note A: Center line of the leads will be within 0.03 in [0.76 mm] of the center line of the body.
- -Lead length shown is for parts supplied in bulk. See packaging specifications for lead lengths when not provided in bulk



Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.