

Current refinements (click  to remove)

[Search Tips](#)

Region USA  Product Family Adhesive Lined Grommet Edging Polyethylene Solid Wall Text Search: 'GES62FA-C'  
Your search criteria matched only one product, shown below.

[Click here to see image](#)

Protects and insulates wires and cables from chafing against edges

- General purpose material for indoor use up to 122°F (50°C)
- Provided in .030" (0.8mm) thick material making it highly fl
- Use on straight edges
- Adhesive ensures product stays in place

‡Reel packaging may contain splices.  
\* Order the number of reels required.

Related Products

- [Slotted Wall](#)
- [Flame Retardant Grommet Edging R...](#)
- [Grommet Edging Nylon -- Slotte...](#)
- [Grommet Edging Polyethylene --...](#)
- [Grommet Edging](#)

Part Number: GES62FA-C  
 RoHS Compliancy Status Compliant  
 Part Description: Solid Wall Polyethylene Grommet Edging with adhesive product will stay where it is installed on straight edges.  
 Product Type: Grommet Edging  
 Material: Polyethylene  
 Color: Natural  
 Height (In.): .16  
 Height (mm): 4.1  
 Length (ft.): 100  
 Length (m): 30.5  
 Width (In.): .13  
 Width (mm): 3.3  
 Flammability Rating: UL HB  
 Ft. Per Pkg.: 100  
 Outside Depth (In.): .160  
 Outside Depth (mm): 4.1  
 Outside Width (In.): .131  
 Outside Width (mm): 3.3  
 Panel Thickness Range ( .036– .062  
 Panel Thickness Range ( 0.9– 1.6  
 Temperature Range: -40°F to 122°F (-40°C to 50°C)  
 Min. Order UOM: RL  
 Min. Order Qty.: 1  
 BOM Qty. (# of Pkgs.)   
 Add to My Catalog

Please [register](#) to utilize the 'Bill of Materials', 'Submit Quotes' and 'My Catalog' fe

[View Content Details](#)

[Evaluate](#)

[Design a Solution](#)

[Install & Maintain](#)

Product Bulletins:

[Adhesive Lined Grommet Edging Sa101n...](#)