

Product Navigation	Home Abou	t Us Products	Investor Relations	News	Contact Us	Secure EAX
Circuit Board Indicators						
Panel Mount Indicators	Circuit Boa	ard Indicators - Throu	gh Hole Indicators			
	P/N# 5501007F	5 mm Le	ens Single Color			
Traffic Signals	Description	5 mm CBI Right Angle B				
Vehicle Lighting	Package Options 100 Pieces Per Bag Product Type Through Hole Indicators Sub Product Type with Single Housing Configuration 5 mm Lens					
Rail						
Obstruction Lighting	Lamp Type	Single Color				
Hazardous Area Lighting	Viewing Viewing Angle	Right Angle 30				
Heliport Lighting	Test Current (mA)	20mA				
	Absolute Maximum	Ratings (Ta = :	25 °)		Pi-Lil.	
how to purchase						tor Stock Che
sales contacts	Solder Temp	260° for 5 sec			Check stock wit	n our distributo
- stock check	Operating Temp Storage Temp	-40 to +80° C -40 to +100° C			5501007F	
Q search	burdge remp	40 10 1100 C			check stock 🔇	,
Product Line Search		RoHS /pB Fr				
Please select a Product Line to search.	Operating Charac			-	_	
Circuit Board Indicators find	LED Position					
□ Part # / Text Search	Color	Blue				
	Lamp Type	Single Color				
Part No.:	LED Type	High Efficiency				
Text Search:	Intensity Min (mcd)	520				
search ()	Intensity Typ (mcd)	1000.0				
guick links	Intensity Max (mcd)	1500.0				
	Fwd Voltage Min					
Dialight Corporate Video	Fwd Voltage Typ					
Presentation at LightFair 2007 - "Presentation of White LEDs" : by Ian Ferguson, Georgia Tech in conjunction with Dialight Corp. View PDF File	Fwd Voltage Max					
	Dom Wavelength Min (nm)	472				
	Dom Wavelength Typ (nm)					
	Dom Wavelength Max (nm)					
Application Notes FAQs	Power Dissipation Max (mW)	120				
	Backlighting					
Dialight Ltd (UK) Dialight Garufo Dialight BLP LumiDrives	Pitch Between Vertical					
	Pitch Between Horizontal					
	Lum Intensity Min					
	Lum Intensity Typ					
	Lum Intensity Max					