

| CONFIGURATION | PART NUMBER | LENGTH |
|---------------------------|-------------|--------|
| 3 PIN MINI, FEMALE RECEPT | MN32PW02M | NA |

DIMENSIONS

| TOLERANCE |
|------------------------|
| 0-2.99 M = ±100.0 mm |
| 3-8.99 M = ±150.0 mm |
| 9-14.99 M = ±300.0 mm |
| 15-29.99 M = ±450.0 mm |
| 30-45.99 M = ±600.0 mm |

WIRING DIAGRAM

TECHNICAL DATA

| | |
|----------------------------|--|
| TEMPERATURE RANGE: | -20C to +105C |
| PROTECTION: | IP 68, NEMA 6P |
| VOLTAGE RATING: | 600VAC/600VDC |
| AMPERAGE: | 10A |
| BODY: | OIL RESISTANT PVC |
| CONTACTS: | COPPER ALLOY |
| CONTACT PLATING: | 5 INCHES (MIN) GOLD, OVER 25 INCHES (MIN) NICKEL |
| CONNECTOR FACE: | PVC |
| COUPLER: | MACHINED ALUMINUM, ANODIZED |
| WIRE TYPE: | 16 AWG, 600 V, MTW OR UL 1015 |
| RECEPTACLE HOUSING: | MACHINED ALUMINUM, ANODIZED |

