



by Schneider Electric

List Price \$246.00 USD

Availability **Stock Item: This item is normally stocked in our distribution facility.**

Technical Characteristics

| | |
|------------------------------|--|
| Ampere Rating | 20A |
| General Application | Short circuit and overcurrent protection |
| For Use With | OEM Panels and Enclosures |
| Circuit Breaker Type | Standard |
| Voltage Rating | 240VAC - 125VDC |
| HACR Rated | Yes |
| Terminal Type | Line: Box Lug - Load: Box Lug |
| Mounting Type | Flush, Surface or DIN Rail (35mm) |
| Weight | 8.70 Ounces |
| Number of Poles | 2-Pole |
| Approvals | UL489 Listed - CSA 22.2 #5.1 Certified - IEC Rated 60947-2 |
| Marketing Trade Name | Multi 9 |
| Enclosure Rating | IP40 |
| Short Circuit Current Rating | 10kA@240VAC |
| Type | C60N |
| Wire Size | #18 to #4 AWG |
| Depth | 3.00 Inches (76mm) |
| Height | 4.21 Inches (107mm) |
| Trip Curve | C Curve - Magnetic operates between 7 to 10 times |
| Width | 1.42 Inches (36mm) |

Shipping and Ordering

| | |
|-------------------|---|
| Category | 00915 - |
| Discount Schedule | DE2 |
| GTIN | 00785901208679 |
| Package Quantity | 1 |
| Weight | 0.56 lbs. |
| Availability Code | Stock Item: This item is normally stocked in our distribution facility. |
| Returnability | Y |
| Country of Origin | FR |

As standards, specifications, and designs change from time to time, please ask for confirmation of the information given in this document.

Generated: 10/26/2011 01:12:03