



by Schneider Electric

List Price \$122.00 USD

Availability **Non-Stock Item: This item is not normally stocked in our distribution facility.**

Technical Characteristics

Ampere Rating	13A
General Application	Short circuit and overcurrent protection
HACR Rated	Yes
Terminal Type	Line: Ring Tongue - Load: Ring Tongue
Mounting Type	Flush, Surface or DIN Rail (35mm)
Approvals	UL489 Listed - CSA 22.2 #5.1 Certified - IEC Rated 60947-2
Weight	5.20 Ounces
Marketing Trade Name	Multi 9
Enclosure Rating	IP40
Number of Poles	1-Pole
Short Circuit Current Rating	5kA@240VAC - 10kA@120VAC
Circuit Breaker Type	Standard
Voltage Rating	120VAC - 60VDC
For Use With	OEM Panels and Enclosures
Type	C60N
Height	4.86 Inches (124mm)
Depth	3.00 Inches (76mm)
Trip Curve	C Curve - Magnetic operates between 7 to 10 times
Width	0.71 Inches (18mm)

Shipping and Ordering

Category	00915 -
Discount Schedule	DE2
GTIN	00785901409878
Package Quantity	1
Weight	0.3 lbs.
Availability Code	Non-Stock Item: This item is not normally stocked in our distribution facility.
Returnability	N
Country of Origin	FR

As standards, specifications, and designs change from time to time, please ask for confirmation of the information given in this document.

Generated: 10/26/2011 01:14:04