


August 2011

MMBZ5221B-MMBZ5257B Zeners



Absolute Maximum Ratings * $T_A = 25$ °C unless otherwise noted

Symbol	Parameter	Value	Units
P _D	Power Dissipation	350	mW
T _{STG}	Storage Temperature Range	-55 to +150	°C
TJ	Operating Junction Temperature	+150	°C

^{*} These ratings are limiting values above which the serviceability of the diode may be impaired.

NOTES:

- 1) These ratings are based on a maximum junction temperature of 150 degrees C.
- 2) These are steady state limits. The factory should be consulted on applications involving pulsed or low duty cycle operations.

Electrical Characteristics $T_A = 25^{\circ}C$ unless otherwise noted


Device	Mark	V _Z (V)	Z _Z (Ω) @ I _Z (mA)		Z _{ZK} (Ω) @ I _{ZK} (mA)		I _R (μA) @ V _R (V)	
MMBZ5221B	18A	2.4	30	20	1,200	0.25	100	1.0
MMBZ5223B	18C	2.7	30	20	1,300	0.25	75	1.0
MMBZ5226B	8A	3.3	28	20	1,600	0.25	25	1.0
MMBZ5227B	8B	3.6	24	20	1,700	0.25	15	1.0
MMBZ5228B	8C	3.9	23	20	1,900	0.25	10	1.0
MMBZ5229B	8D	4.3	22	20	1,000	0.25	5.0	1.0
MMBZ5230B	8E	4.7	19	20	1,900	0.25	5.0	2.0
MMBZ5231B	8F	5.1	17	20	1,600	0.25	5.0	2.0
MMBZ5232B	8G	5.6	11	20	1,600	0.25	5.0	3.0
MMBZ5233B	8H	6.0	7.0	20	1,600	0.25	5.0	3.5
MMBZ5234B	8J	6.2	7.0	20	1,000	0.25	5.0	4.0
MMBZ5235B	8K	6.8	5.0	20	750	0.25	3.0	5.0
MMBZ5236B	8L	7.5	6.0	20	500	0.25	3.0	6.0
MMBZ5237B	8M	8.2	8.0	20	500	0.25	3.0	6.5
MMBZ5238B	8N	8.7	8.0	20	600	0.25	3.0	6.5
MMBZ5239B	8P	9.1	10	20	600	0.25	3.0	7.0
MMBZ5240B	8Q	10	17	20	600	0.25	3.0	8.0
MMBZ5241B	8R	11	22	20	600	0.25	2.0	8.4
MMBZ5242B	8S	12	30	20	600	0.25	1.0	9.1
V _F Forward Voltage = 0.9V Maximum @ I _F = 10mA for all MMBZ5200 series								

© 2011 Fairchild Semiconductor Corporation MMBZ5221B-MMBZ5257B Rev. A3 www.fairchildsemi.com


Electrical Characteristics (Continued) $T_A = 25$ °C unless otherwise noted

Device	Mark	V _Z (V)	Z _Z (Ω) @ I _Z (mA)		Z _{ZK} (Ω) @ I _{ZK} (mA)		I _R (μA) @ V _R (V)	
MMBZ5243B	8T	13	13	9.5	600	0.25	500	9.9
MMBZ5244B	8U	14	15	9.0	600	0.25	100	10
MMBZ5245B	8V	15	16	8.5	600	0.25	100	11
MMBZ5246B	8W	16	17	7.8	600	0.25	100	12
MMBZ5247B	8X	17	19	7.4	600	0.25	100	13
MMBZ5248B	8Y	18	21	7.0	600	0.25	100	14
MMBZ5249B	8Z	19	23	6.6	600	0.25	100	14
MMBZ5250B	81A	20	25	6.2	600	0.25	100	15
MMBZ5251B	81B	22	29	5.6	600	0.25	100	17
MMBZ5252B	81C	24	33	5.2	600	0.25	100	18
MMBZ5253B	81D	25	35	5.0	600	0.25	100	19
MMBZ5254B	81E	27	41	4.6	600	0.25	100	21
MMBZ5255B	81F	28	44	4.5	600	0.25	100	21
MMBZ5256B	81G	30	49	4.2	600	0.25	100	23
MMBZ5257B	81H	33	58	3.8	600	0.25	100	25


Typical Performance Characteristics




Zener Current vs. Zener Voltage




Zener Current vs. Zener Impedence




3.3 Zener Voltage vs. Temperature



5.1 Zener Voltage vs. Temperature



12 Zener Voltage vs. Zener Temperature



33 Zener Voltage vs. Zener Temperature





TRADEMARKS

The following includes registered and unregistered trademarks and service marks, owned by Fairchild Semiconductor and/or its global subsidiaries, and is not intended to be an exhaustive list of all such trademarks.

2Cool™ FPS™ AccuPower™ F-PES™ FRFET® Auto-SPM™ Global Power ResourceSM AX-CAP™* Green FPS™ BitSiC[®] Build it Now™ Green FPS™ e-Series™ CorePLUS™ Gmax™ GTO™ CorePOWER™ IntelliMAX™ CROSSVOLT™ ISOPLANAR™ CTL™

Current Transfer Logic™ Making Small Speakers Sound Louder
DELIXPEED® and Better™

DEUXPEED® and Better™

Dual Cool™ MegaBuck™

EcoSPARK® MICROCOUPLER™

EfficientMax™ MicroPet™

ESBC™ MicroPak™

MicroPak²™

MilerDrive™

MillerDrive™

 T
 MillerDrive™

 Fairchild® Semiconductor®
 MotionMax™

 FACT Quiet Series™
 Motion-SPM™

 FACT®
 OptoHiT™

 FAST®
 OPTOLOGIC®

 FastvCore™
 OPTOPLANAR®

PDP SPMTM
Power-SPMTM
PowerTrench[®]
PowerXSTM

Programmable Active Droop™

QFET[®] QS™ Quiet Series™ RapidConfigure™

Saving our world, 1mW/W/kW at a time™ SignalWise™

SmartMax™
SMART START™
SPM®
STEALTH™
SuperFET®
SuperSOT™-8
SuperSOT™-6
SuperSOT™-6
SuperSOT™-8
SupreMOS®
SyncFET™
Sync-Lock™
■ SYSTEM
■ GENERAL®-+

Franchise
TinyBoost™
TinyBuck™

The Power Franchise®

TinyBuck™
TinyCalc™
TinyLogic®
TINYOPTO™
TinyPower™
TinyPWM™
TinyWire™
TranSic®
TriFault Detect

TriFault Detect™ TRUECURRENT®* μSerDes™

Scroes"
UHC®
Ultra FRFET™
UniFET™
VCX™
VisualMax™
VoltagePlus™
XS™

* Trademarks of System General Corporation, used under license by Fairchild Semiconductor.

DISCLAIMER

FAIRCHILD SEMICONDUCTOR RESERVES THE RIGHT TO MAKE CHANGES WITHOUT FURTHER NOTICE TO ANY PRODUCTS HEREIN TO IMPROVE RELIABILITY, FUNCTION, OR DESIGN. FAIRCHILD DOES NOT ASSUME ANY LIABILITY ARISING OUT OF THE APPLICATION OR USE OF ANY PRODUCT OR CIRCUIT DESCRIBED HEREIN; NEITHER DOES IT CONVEY ANY LICENSE UNDER ITS PATENT RIGHTS, NOR THE RIGHTS OF OTHERS. THESE SPECIFICATIONS DO NOT EXPAND THE TERMS OF FAIRCHILD'S WORLDWIDE TERMS AND CONDITIONS, SPECIFICALLY THE WARRANTY THEREIN, WHICH COVERS THESE PRODUCTS.

LIFE SUPPORT POLICY

FAIRCHILD'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF FAIRCHILD SEMICONDUCTOR CORPORATION.

s used herein:

- Life support devices or systems are devices or systems which, (a)
 are intended for surgical implant into the body or (b) support or
 sustain life, and (c) whose failure to perform when properly used in
 accordance with instructions for use provided in the labeling, can be
 reasonably expected to result in a significant injury of the user.
- A critical component in any component of a life support, device, or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

ANTI-COUNTERFEITING POLICY

Fairchild Semiconductor Corporation's Anti-Counterfeiting Policy. Fairchild's Anti-Counterfeiting Policy is also stated on our external website, www.fairchildsemi.com, under Sales Support.

Counterfeiting of semiconductor parts is a growing problem in the industry. All manufacturers of semiconductor products are experiencing counterfeiting of their parts. Customers who inadvertently purchase counterfeit parts experience many problems such as loss of brand reputation, substandard performance, failed applications, and increased cost of production and manufacturing delays. Fairchild is taking strong measures to protect ourselves and our customers from the proliferation of counterfeit parts. Fairchild strongly encourages customers to purchase Fairchild parts either directly from Fairchild or from Authorized Fairchild Distributors who are listed by country on our web page cited above. Products customers buy either from Fairchild directly or from Authorized Fairchild's quality standards for handling and storage and provide access to Fairchild's full range of up-to-date technical and product information. Fairchild and our Authorized Distributors will stand behind all warranties and will appropriately address any warranty issues that may arise. Fairchild will not provide any warranty coverage or other assistance for parts bought from Unauthorized Sources. Fairchild is committed to combat this global problem and encourage our customers to do their part in stopping this practice by buying direct or from authorized distributors.

PRODUCT STATUS DEFINITIONS

Definition of Terms

Definition of Terms				
Datasheet Identification	Product Status	Definition		
Advance Information	Formative / In Design	Datasheet contains the design specifications for product development. Specifications may change in any manner without notice.		
Preliminary	First Production	Datasheet contains preliminary data; supplementary data will be published at a later date. Fairchild Semiconductor reserves the right to make changes at any time without notice to improve design.		
No Identification Needed	Full Production	Datasheet contains final specifications. Fairchild Semiconductor reserves the right to make changes at any time without notice to improve the design.		
Obsolete	Not In Production	Datasheet contains specifications on a product that is discontinued by Fairchild Semiconductor. The datasheet is for reference information only.		

Rev. 157