

This document was generated on 08/22/2011

## PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number:	<u>0022272021</u>		
Status:	Active		
Overview:	kk		
Description:		h KK® Wire-to-Board Header, Vertical, with Friction Lock, 2	
	Circuits, Tin (Sn) Pl		
	, , ,	<u> </u>	
Documents:			
3D Model		Product Specification PS-99020-0088 (PDF)	
Drawing (PDF)		RoHS Certificate of Compliance (PDF)	
			Series
Agency Certifie	cation		image - Reference only
CSA		LR19980	
UL		E29179	EU RoHS China RoHS
			ELV and RoHS
General			Compliant
Product Family		PCB Headers	REACH SVHC
Series		<u>6410</u>	Contains SVHC: No
Application		Signal, Wire-to-Board	Low-Halogen Status
Overview		<u>kk</u>	Low-Halogen
Product Name		KK®	Need more information on product
Physical			environmental compliance?
Breakaway		No	Emoil productoompliance@moley.com
Circuits (Loaded)		2	Email productcompliance@molex.com For a multiple part number RoHS Certificate of
Circuits (maximum	)	2	Compliance, <u>click here</u>
Color - Resin		Natural (White)	
First Mate / Last Break		No	Please visit the Contact Us section for any
Flammability		94V-0	non-product compliance questions.
Glow-Wire Complia	ant	No	
Guide to Mating Part		No	
Keying to Mating Part		None	
Lock to Mating Part		Yes	Search Parts in this Series
Material - Metal		Brass	<u>6410</u> Series
Material - Plating Mating		Tin —	
Material - Plating Termination		Tin	Mates With
Material - Resin		Nylon	KK® Crimp Terminal Housing 2695, 6471
Number of Rows Orientation		1 Vertical	
PC Tail Length		3.56mm (.140")	
PCB Locator		No	
PCB Retention		None	
PCB Thickness - R	Recommended	1.60mm (.063")	
Packaging Type		Bag	
Pitch - Mating Interface		2.54mm (.100")	
Pitch - Termination Interface		2.54mm (.100")	
Plating min - Matin	g	5.080µm (200µ")	
Plating min - Termi		5.080µm (200µ")	
Polarized to Mating	g Part	Yes	
Polarized to PCB		No	
Shrouded		Partial	
Stackable		No	
Surface Mount Cor		No	
Temperature Rang		0°C to +75°C	
Termination Interfa	ice: Style	Through Hole	

Electrical

Current - Maximum per Contact Voltage - Maximum	4A 250V
Solder Process Data Duration at Max. Process Temperature (seconds) Lead-free Process Capability Max. Cycles at Max. Process Temperature Process Temperature max. C	5 Wave Capable (TH only) 3 230
Material Info Old Part Number	AE-6410-02A(102)
Reference - Drawing Numbers Product Specification Sales Drawing	PS-99020-0088 SDAE-6410-N

## This document was generated on 08/22/2011 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION