


T92 Series Two-pole 30A PCB or Panel Mount Relay

- 30A, 2 form A (NO) and 2 form C (CO) switching capability
- Designed to control compressor loads to 3.5 tons, 110LRA / 25.3FLA
- Meets requirements of UL 508 and UL 873 spacings - 8mm through air, 9.5mm over surface
- Meets requirements of VDE 8mm spacing, 4kV dielectric coil-to-contact
- Meets requirements of UL Class F construction
- UL approved for 600VAC switching (1.5HP)
- New screw terminal version (consult factory for availability, ratings)



Typical applications
HVAC, residential / commercial appliances, industrial controls



Approvals

UL E22575 (Recognized and Listed); CSA LR15734; VDE REG.Nr. 5386
Technical data of approved types on request

Contact Data

Contact arrangement	2 form A (NO), 2 form C (CO)
Rated voltage	277VAC
Max. switching voltage	600VAC
Rated current	30A NO; 3A NC
Limiting continuous current	30A NO; 3A NC
Limiting making current	30A NO; 3A NC
Limiting breaking current	30A NO; 3A NC
Contact material	AgSnOInO, AgCdO
Min. recommended contact load	500ma (NO)/ 100ma (NC), 12VAC
Frequency of operation, with load	360hr
Operate/release time max., including bounce	15/15ms

Contact ratings ¹⁾

Type	Load	Cycles
UL508		
AgCdO		
NO	40A, 277VAC, resistive (flange mount only)	6x10 ³
NO	30A, 120/277VAC, resistive	100x10 ³
NO	10A, 600VAC, general purpose	100x10 ³
NO	1HP, 120VAC	100x10 ³
NO	3HP, 240VAC	1x10 ³
NO	1.5HP, 480 or 600VAC	100x10 ³
NO	110LRA/25.3FLA, 240VAC (DC coil only)	100x10 ³
NO	60LRA/14FLA, 240VAC (AC coil only)	100x10 ³
NO	3A, 240VAC, pilot duty	100x10 ³
NO	20A, 28VDC, resistive	100x10 ³
NO	TV10, 120VAC	100x10 ³
NC	3A, 277VAC	100x10 ³
NC	2A, 480VAC	100x10 ³
NC	1A, 600VAC	100x10 ³
AgSnOInO		
NO	30A, 120/277VAC, resistive (DC coil only)	200x10 ³
NO	30A, 120/277VAC, resistive (AC coil only)	100x10 ³
NO	20A, 480VAC, resistive	100x10 ³
NO	1.5HP, 120VAC, 2 pole making/breaking (Fig.1)	100x10 ³
NO	3HP, 240VAC, 3 phase (DC coil only)	100x10 ³
NO	3HP, 480VAC, 3 phase (DC coil only)	100x10 ³
NO	2HP, 600VAC, 3 phase (DC coil only)	100x10 ³
VDE		
AgCdO, flange mount relays		
NO	20A, 400VAC	100x10 ³
NC	3A, 400VAC	30x10 ³
CO	20A, 400VAC	30x10 ³
AgCdO, PC mount relays		
NO	30A, 400VAC	100x10 ³
NC	3A, 400VAC	30x10 ³
CO	30A, 400VAC	30x10 ³

Contact ratings ¹⁾ (continued)

ARI 780-86 Endurance Test (section 6.6):
HVAC Definite Purpose Contactor Standard
Normally Open Contacts
Single Phase/Two Pole (Both poles together switching a single load)
110 LRA, 25.3 FLA, 200K operations (DC Coil)




Figure 1
Single Phase Per Pole (Single load per pole)
110 LRA, 18 FLA, 200K operations (DC Coil).
60 LRA, 14 FLA, 200K operations (AC Coil).




Figure 2
¹⁾ Contact ratings at 25°C (unless otherwise noted) with relay properly vented.
FLA, LRA ratings are compatible with 3.5 ton compressor applications.

Mechanical endurance	10x10 ⁶ ops.
----------------------	-------------------------

Coil Data

Coil voltage range	5 to 110VDC; 12 to 240VAC
Max. coil power	1.7W; 4.0VA
Max. coil temperature	155°C
Coil insulation system according UL	Class F

Coil versions, DC coil

Coil code	Rated voltage VDC	Operate voltage VDC	Release voltage VDC	Coil resistance Ω±10%	Rated coil power W
6	6	4.5	0.6	22	1.7
9	9	6.75	0.9	48	1.7
12	12	9	1.2	86	1.7
18	18	13.5	1.8	197	1.7
24	24	18	2.4	350	1.7
48	48	36	4.8	1390	1.7
110	110	82.5	11	7255	1.7

Coil versions, AC coil

Coil code	Rated voltage VAC	Frequency Hz	Operate voltage VAC	Release voltage VAC	Coil resistance Ω±10%	Rated coil power VA
12	12	60	9.6	1.2	9.1	4
24	24	60	19.2	2.4	36.6	4
120	110/120	50/60	96	12	950	4
240	220/240	50/60	192	24	3800	4
277	250/277	50/60	222	28	5485	4

All figures are given for coil without preenergization, at ambient temperature +23°C.


T92 Series Two-pole 30A PCB or Panel Mount Relay (Continued)

Coil Data (continued)

Ambient temperature vs. coil voltage

Assumptions:

1. Thermal resistance = 35°C per Watt (DC only.)
2. Still air.
3. Nominal coil resistance.
4. Max. mean coil temperature = 155°C (change of resistance method).
5. Coil temperature rise due to load = 6.3°C @ 30 amps.
6. Curves are based on 1.7W at 25°C (DC only.).




Insulation Data

Initial dielectric strength	
between open contacts	1500V _{rms}
between contact and coil	4000V _{rms}
between adjacent contact	2000V _{rms}
Initial surge withstand voltage	
between contact and coil	6kV
Initial insulation resistance	
between insulated elements	1x10 ⁹ Ω
Clearance/creepage	
between contact and coil	8mm clearance/9.5mm creepage

Dimensions

T92 – Mounting and termination code 1




Other Data

Material compliance: EU RoHS/ELV, China RoHS, REACH, Halogen content refer to the Product Compliance Support Center at www.te.com/customer-support/rohssupportcenter

Ambient temperature	
DC coil	-55°C to 85°C
AC coil	-55°C to 65°C
Category of environmental protection	IEC 61810
	RTI - dust protected, RTII - flux proof, RTIII - wash tight
Vibration resistance (functional)	1.65mm max excursions, 10-55 Hz
Shock resistance (functional)	10g for 11msec
Shock resistance (destructive)	100g
Terminal type	pcb-tht or quick connect
Weight	86g
Resistance to soldering heat THT	250°C
IEC 60068-2-20	
Packaging/unit	tray/30 pcs., box/120 pcs.

T92 – Mounting and termination code 2, 3 and 4



T92 Series Two-pole 30A PCB or Panel Mount Relay (Continued)

Product Code	Enclosure	Contacts	Coil	Mounting	Contact Material	Coil	Part Number
T92P7A22-24	Plastic dust cover	2 form A, 2 NO	AC	Panel mount + quick conn.	AgCdO	24 VAC	6-1393211-0
120 VAC						5-1393211-7	
T92P7A22-120						240 VAC	6-1393211-2
T92P7A22-240						277 VAC	6-1393211-3
T92P7A22-277						240 VAC	3-1423008-3
T92P7A24-240					AgSnOInO	240 VAC	1423008-8
T92P7A52-120					AgCdO	240 VAC	1-1423008-2
T92P7A52-240						12 VDC	6-1393211-5
T92P7D12-12			DC	PCB terminals		24 VDC	6-1393211-6
T92P7D12-24						12VDC	6-1393211-9
T92P7D22-12				Panel mount + quick conn.		24 VDC	7-1393211-1
T92P7D22-24						48 VDC	7-1393211-2
T92P7D22-48						12VDC	2-1423008-2
T92P7D24-12					AgSnOInO	24 VDC	1423008-9
T92P7D24-24						12 VDC	1-1423008-0
T92P7D42-24				Panel mount + screw term.		24 VDC	1423967-1
T92P7D52-12						120 VAC	3-1393211-8
T92P7D52-24						12 VAC	3-1393211-9
T92P11A12-120		2 form C, 2 CO	AC	PCB terminals		24 VAC	4-1393211-3
T92P11A22-12				Panel mount + quick conn.		120 VAC	4-1393211-0
T92P11A22-24						240 VAC	4-1393211-4
T92P11A22-120						277 VAC	4-1393211-6
T92P11A22-240						240 VAC	3-1423008-7
T92P11A22-277						120VAC	4-1393211-8
T92P11A24-240					AgSnOInO	12 VDC	5-1393211-0
T92P11A42-120					AgCdO	24 VDC	5-1393211-3
T92P11D12-12			DC	PCB terminals		110 VDC	1393212-7
T92P11D22-12				Panel mount + quick conn.		24 VDC	5-1393211-4
T92P11D22-24						12 VDC	3-1423008-5
T92P11D24-12					AgSnOInO	24 VDC	3-1423008-6
T92P11D24-24						24 VAC	9-1393211-8
T92S7A12-24	Wash tight	2 form A, 2 NO	AC	PCB terminals	AgCdO	24 VAC	9-1393211-7
T92S7A12-120						120 VAC	9-1393211-9
T92S7A12-240						240 VAC	1393212-4
T92S7A22-24	Top sealed			Panel mount + quick conn.		120 VAC	1393212-2
T92S7A22-120						240 VAC	1393212-5
T92S7A22-240						12 VDC	1393212-8
T92S7D12-12	Wash tight		DC	PCB terminals		24 VDC	1-1393212-0
T92S7D12-24						48 VDC	1-1393212-1
T92S7D12-48						110 VDC	1393212-7
T92S7D12-110						24 VDC	1-1423008-8
T92S7D14-24					AgSnOInO	12 VDC	1-1393212-4
T92S7D22-12	Top sealed			Panel mount + quick conn.	AgCdO	18 VDC	1-1393212-5
T92S7D22-18						24 VDC	1-1393212-7
T92S7D22-24						110 VDC	1-1393212-3
T92S7D22-110						24 VAC	8-1393211-1
T92S11A12-24	Wash tight	2 form C, 2 CO	AC	PCB terminals		120 VAC	8-1393211-0
T92S11A12-120							240 VAC
T92S11A12-240						12 VAC	8-1393211-3
T92S11A22-12	Top sealed			Panel mount + quick conn.		24 VAC	8-1393211-6
T92S11A22-24						120 VAC	8-1393211-4
T92S11A22-120						240 VAC	8-1393211-7
T92S11A22-240						12 VDC	8-1393211-9
T92S11D12-12	Wash tight		DC	PCB terminals		24 VDC	9-1393211-0
T92S11D12-24						48 VDC	9-1393211-1
T92S11D12-48						110 VDC	8-1393211-8
T92S11D12-110						12 VDC	9-1393211-3
T92S11D22-12	Top sealed			Panel mount + quick conn.		24 VDC	9-1393211-4
T92S11D22-24							