

MITSUBISHI TRANSISTOR MODULES

QM100HC-M

HIGH POWER SWITCHING USE
NON-INSULATED TYPE

QM100HC-M





- **I_C** Collector current **100A**
- **V_{CEX}** Collector-emitter voltage **350V**
- **h_{FE}** DC current gain **100**
- **Non-Insulated Type**

APPLICATION

Robotics, Forklifts, Welders

OUTLINE DRAWING & CIRCUIT DIAGRAM

Dimensions in mm



Feb.1999

QM100HC-M

HIGH POWER SWITCHING USE
NON-INSULATED TYPEABSOLUTE MAXIMUM RATINGS (T_j=25°C, unless otherwise noted)

Symbol	Parameter	Conditions	Ratings	Unit
V _{CEX} (SUS)	Collector-emitter voltage	I _c =1A, V _{EB} =2V	350	V
V _{CEX}	Collector-emitter voltage	V _{EB} =2V	350	V
V _{CBO}	Collector-base voltage	Emitter open	400	V
V _{EBO}	Emitter-base voltage	Collector open	10	V
I _c	Collector current	DC	100	A
-I _c	Collector reverse current	DC (forward diode current)	100	A
P _C	Collector dissipation	T _c =25°C	420	W
I _B	Base current	DC	3	A
-I _{CSM}	Surge collector reverse current (forward diode current)	Peak value of one cycle of 60Hz (half wave)	1000	A
T _J	Junction temperature		-40~+150	°C
T _{stg}	Storage temperature		-40~+125	°C
V _{iso}	Isolation voltage	Charged part to case, AC for 1 minute	—	V
—	Mounting torque	Main terminal screw M5	1.47~1.96	N·m
			15~20	kg·cm
		Mounting screw M5	1.47~1.96	N·m
			15~20	kg·cm
—	Weight	Typical value	90	g

ELECTRICAL CHARACTERISTICS (T_j=25°C, unless otherwise noted)


Symbol	Parameter	Test conditions	Limits			Unit
			Min.	Typ.	Max.	
I _{CEX}	Collector cutoff current	V _{CE} =350V, V _{EB} =2V	—	—	1.0	mA
I _{CBO}	Collector cutoff current	V _{CB} =400V, Emitter open	—	—	1.0	mA
I _{EBO}	Emitter cutoff current	V _{EB} =10V	—	—	200	mA
V _{CE} (sat)	Collector-emitter saturation voltage	I _c =100A, I _B =1A	—	—	2.0	V
V _{BE} (sat)	Base-emitter saturation voltage		—	—	2.5	V
-V _{CEO}	Collector-emitter reverse voltage	-I _c =100A (diode forward voltage)	—	—	1.5	V
h _{FE}	DC current gain	I _c =100A, V _{CE} =2V/5V	100/200	—	—	—
t _{on}	Switching time	V _{CC} =200V, I _c =100A, I _{B1} =-I _{B2} =2A	—	—	2.0	μs
t _s			—	—	10	μs
t _f			—	—	3.0	μs
R _{th} (j-c) Q	Thermal resistance (junction to case)	Transistor part	—	—	0.3	°C/W
R _{th} (j-c) R		Diode part	—	—	0.5	°C/W
R _{th} (c-f)	Contact thermal resistance (case to fin)	Conductive grease applied	—	—	0.15	°C/W

QM100HC-M


**HIGH POWER SWITCHING USE
NON-INSULATED TYPE**

PERFORMANCE CURVES


COMMON EMITTER OUTPUT CHARACTERISTICS (TYPICAL)




DC CURRENT GAIN VS. COLLECTOR CURRENT (TYPICAL)




COMMON EMITTER INPUT CHARACTERISTIC (TYPICAL)




SATURATION VOLTAGE CHARACTERISTICS (TYPICAL)



COLLECTOR-EMITTER SATURATION VOLTAGE (TYPICAL)




SWITCHING TIME VS. COLLECTOR CURRENT (TYPICAL)




QM100HC-M

HIGH POWER SWITCHING USE
NON-INSULATED TYPE


SWITCHING TIME VS. BASE CURRENT (TYPICAL)




REVERSE BIAS SAFE OPERATING AREA




FORWARD BIAS SAFE OPERATING AREA




DERATING FACTOR OF F. B. S. O. A.



TRANSIENT THERMAL IMPEDANCE CHARACTERISTIC (TRANSISTOR)




REVERSE COLLECTOR CURRENT VS. COLLECTOR-EMITTER REVERSE VOLTAGE (DIODE FORWARD CHARACTERISTICS) (TYPICAL)




QM100HC-M

**HIGH POWER SWITCHING USE
NON-INSULATED TYPE**

**RATED SURGE COLLECTOR REVERSE CURRENT
(DIODE FORWARD SURGE CURRENT)**



**REVERSE RECOVERY CHARACTERISTICS
OF FREE-WHEEL DIODE (TYPICAL)**



**TRANSIENT THERMAL IMPEDANCE
CHARACTERISTIC (DIODE)**

