

(TLP557)

TRANSISTOR INVERTOR
 INVERTER FOR AIR CONDITIONOR
 POWER TRANSISTOR BASE DRIVE

The TOSHIBA TLP557 consists of a GaAlAs light emitting diode and a integrated photodetector.

This unit is 8-lead DIP package.


TLP557 is suitable for base driving circuit of power transistor module up to 20A.

External resistor needs to connect between pin 6 and pin 7.


This is for constant current driving.

- Input Threshold Current : $I_F = 5\text{mA (Max.)}$
- Guaranteed Performance Temperature Range : $-30\sim 70^\circ\text{C}$
- Supply Voltage : 16V (Max.)
- Output Current : $\pm 0.3\text{A (Max.)}$
- Switching Time (t_{pLH} / t_{pHL}) : $5\mu\text{s (Max.)}$
- Isolation Voltage : $2500\text{V}_{\text{rms (Min.)}}$
- UL Recognized : UL1577, File No. E67349

SCHMATIC




Unit in mm



Weight : 0.54g

PIN CONFIGURATION (TOP VIEW)



- 1 : N.C.
- 2 : ANODE
- 3 : CATHODE
- 4 : N.C.
- 5 : GND
- 6 : V_{O2} (OUTPUT)
- 7 : V_{O1} (Rex TERMINAL)
- 8 : V_{CC}

TRUTH TABLE

		Tr1	Tr2
Input LED	ON	ON	OFF
	OFF	OFF	ON

© The information contained herein is presented only as a guide for the applications of our products. No responsibility is assumed by TOSHIBA CORPORATION for any infringements of intellectual property or other rights of the third parties which may result from its use. No license is granted by implication or otherwise under any intellectual property or other rights of TOSHIBA CORPORATION or others.
 © These TOSHIBA products are intended for use in general commercial applications (office equipment, communication equipment, measuring equipment, domestic appliances, etc.), please make sure that you consult with us before you use these TOSHIBA products in equipment which requires extraordinarily high quality and/or reliability, and in equipment which may involve life threatening or critical application, including but not limited to such uses as atomic energy control, airplane or spaceship instrumentation, traffic signals, medical instrumentation, combustion control, all types of safety devices, etc. TOSHIBA cannot accept and hereby disclaims liability for any damage which may occur in case the TOSHIBA products are used in such equipment or applications without prior consultation with TOSHIBA.

①

(TLP557)

ABSOLUTE MAXIMUM RATINGS

CHARACTERISTIC		SYMBOL	RATING	UNIT
LED	Forward Current	I_F	25	mA
	Peak Transient Forward Current (Note 1)	I_{FPT}	1	A
	Reverse Voltage	V_R	5	V
	Junction Temperature	(T_j)	125	°C
DETECTOR	Output Current ($f \leq 5\text{kHz}$, Duty $\leq 50\%$)	I_O	+0.32 / -0.32	A
	Peak Output Current ($P_W \leq 10\mu\text{s}$, $f \leq 5\text{kHz}$)	I_{OP}	+2 / -0.5	A
	Output Voltage	V_O	16	V
	Supply Voltage	V_{CC}	16	V
	O ₁ Terminal to O ₂ Terminal (Pin 7 - Pin 6) Voltage	V_{1-2}	1.5	V
	O ₂ Terminal to O ₁ Terminal (Pin 6 - Pin 7) Voltage	V_{2-1}	5	V
	Power Dissipation (Note 2)	P_o	0.5	W
	Junction Temperature	(T_j)	125	°C
Total Package Power Dissipation (Note 3)	P_{OT}	0.55	W	
Operating Temperature Range	T_{opr}	-30~70	°C	
Storage Temperature Range	T_{stg}	-55~125	°C	
Lead Solder Temperature (10s)	T_{sol}	260	°C	
Isolation Voltage (AC, 1min., R.H. $\leq 60\%$, $T_a = 25^\circ\text{C}$) (Note 4)	BV_S	2500	Vrms	

Note 1 : Pulse width $PW \leq 1\mu\text{s}$, 300pps

Note 2 : $\Delta P_o / ^\circ\text{C} = -6.7\text{mW} / ^\circ\text{C}$ ($T_a \geq 50^\circ\text{C}$)

Note 3 : $\Delta P_{OT} / ^\circ\text{C} = -7.4\text{mW} / ^\circ\text{C}$ ($T_a \geq 50^\circ\text{C}$)

Note 4 : Device considered a two terminal device : pins 1, 2, 3 and 4 shorted together, and pins 5, 6, 7 and 8 shorted together.

TLP557 - 2

1996 - 4 - 8

TOSHIBA CORPORATION

(TLP557)

ELECTRICAL CHARACTERISTICS (Ta = -30~70°C, Unless otherwise specified)

CHARACTERISTIC	SYMBOL	TEST CONDITION	MIN.	TYP.*	MAX.	UNIT	TEST CIRCUIT	
Input Forward Voltage	V _F	I _F =5mA, Ta=25°C	—	1.55	1.7	V		
Temperature Coefficient of Forward Voltage	ΔV _F /ΔTa	I _F =5mA	—	-2.0	—	mV/°C		
Input Reverse Current	I _R	V _R =5V, Ta=25°C	—	—	10	μA		
Input Capacitance	C _T	V=0, f=1MHz, Ta=25°C	—	—	250	pF		
O ₁ Output Leakage Current	I _{O1L}	V _{CC} =16V, V _{O1} =0, V _F =0.8V	—	0.01	200	μA	1	
O ₂ Output Leakage Current	I _{O2L}	V _{CC} =16V, V _{O2} =16V, I _F =5mA	—	0.2	200	μA	2	
O ₁ Output Current	I _O	V ₈₋₆ =2.3V R _{ex} =2.7Ω I _F =5mA, Ta=25°C	V _{CC} =6V	0.22	0.27	0.32	A	3
			V _{CC} =16V	0.22	0.27	0.32		
O ₂ High Level Output Voltage	V _{OH}	V _{CC} =6V, R _{ex} =2.7Ω I _F =5mA	3.5	5.5	—	V	4	
O ₂ Low Level Output Voltage	V _{OL}	V _F =0.8V, R _{ex} =2.7Ω I _O =0.25A, Ta=25°C	V _{CC} =6V	—	0.2	0.4	V	5
			V _{CC} =16V	—	0.2	0.4		
		V _F =0.8V, R _{ex} =2.7Ω I _O =0.5A (*1) Ta=25°C	V _{CC} =6V	—	0.4	—	V	
			V _{CC} =16V	—	0.4	—		
High Level Supply Current	I _{CCH}	V _{CC} =6V, I _F =5mA R _{ex} =2.7Ω, Ta=25°C	V _{CC} =6V	—	3.8	10	mA	
			V _{CC} =6V, I _F =5mA, R _{ex} =2.7Ω	—	—	13		
			V _{CC} =16V, I _F =5mA, R _{ex} =2.7Ω	—	5.2	17		
Low Level Supply Current	I _{CCL}	V _{CC} =6V, I _F =0mA R _{ex} =2.7Ω, Ta=25°C	V _{CC} =6V	—	11	17	mA	
			V _{CC} =6V, I _F =0mA, R _{ex} =2.7Ω	—	—	22		
			V _{CC} =16V, I _F =0mA, R _{ex} =2.7Ω	—	13	25		
“Output L→H” Threshold Input Current	I _{FLH}	R _{ex} =2.7Ω I _O =0.25A V _{O2} >3V	V _{CC} =6V	—	2.5	5	mA	
			V _{CC} =16V	—	—	5		
“Output H→L” Threshold Input Current	V _{FHL}	R _{ex} =2.7Ω I _O =0.25A V _{O2} <0.4V	V _{CC} =6V	0.8	—	—	V	
			V _{CC} =16V	0.8	—	—		
Input Current Hysteresis	I _{HYS}	V _{CC} =6V, R _{ex} =2.7Ω, Ta=25°C	—	0.05	—	mA		
Supply Voltage	V _{CC}		5	—	16	V		
Capacitance (Input-Output)	C _S	V _S =0, f=1MHz, Ta=25°C	—	1.0	2.0	pF		
Resistance (Input-Output)	R _S	V _S =500V, Ta=25°C, R.H.≤60%	5×10 ¹⁰	10 ¹⁴	—	Ω		

* All typical values are at Ta=25°C (*1): Duration of I_O time ≤ 100μs


TLP557 - 3
1996 - 4 - 8
TOSHIBA CORPORATION

(TLP557)

RECOMMENDED OPERATING CONDITION

CHARACTERISTIC	SYMBOL	MIN.	TYP.	MAX.	UNIT
Input Current ON	I_F (ON)	7	8	20	mA
Input Voltage OFF	V_F (OFF)	0	—	0.8	V
Supply Voltage	V_{CC}	5	6	13	V
I_{B1} Drive Current	I_{O1}	—	0.15	0.25	A
I_{B2} Drive Current	I_{O2}	—	—	0.5	A
External Resistance	R_{ex}	2.7	4.3	—	Ω
$V_{CC} - V_{O2}$ (Pin 8 - Pin 6) ON Voltage	V_{8-6}	2.3	3 ($I_{O1}=0.15A$)	2.5 ($I_{O1}=0.25A$)	V
Operating Temperature	T_{opr}	-30	25	70	$^{\circ}C$

(R_{ex} is for constant current driving)



TLP557 - 4

1996 - 4 - 8

TOSHIBA CORPORATION


(TLP557)

SWITCHING CHARACTERISTICS (Ta = -30~70°C Unless otherwise specified)


CHARACTERISTIC	SYMBOL	TEST CONDITION	MIN.	TYP.*	MAX.	UNIT	TEST CIR-CUIT
Propagation Delay Time, L→H	tpLH	VCC=6V, IF=8mA Rex=2.7Ω f=5kHz, Duty=10%	—	1	5	μs	6
Propagation Delay Time, H→L	tpHL		—	1	5	μs	
Output Rise Time	tr		—	0.05	—	μs	
Output Fall Time	tf		—	0.05	—	μs	
Common Mode Transient Immunity at High Level Output	CMH	VCM=600V, IF=8mA VCC=6V, Rex=270Ω R=1kΩ, Ta=25°C	-2000	—	—	V/μs	7
Common Mode Transient Immunity at Low Level Output	CML	VCM=600V, IF=0mA VCC=6V, Rex=270Ω R=1kΩ, Ta=25°C	2000	—	—	V/μs	7

* All typical values are at Ta=25°C.


TEST CIRCUIT 1 : IO1L




TEST CIRCUIT 2 : IO2L




TEST CIRCUIT 3 : IO




TEST CIRCUIT 4 : VOH




TEST CIRCUIT 5 : VOL



TEST CIRCUIT 6 : tpLH, tpHL, tr, tf



TEST CIRCUIT 7 : CMH, CML



CML (CMH) is the maximum rate of rise (fall) of the common mode voltage that can be sustained with the output voltage in the low (high) state.

(TLP557)

