MOS IC



LC89960, 89960M

NTSC 1H Delay Line

Overview

The LC89960 and LC89960M are delay lines and produce a 1H delayed signal for the NTSC format, with an external low-pass filter.

Functions

- 905-stage shift register
- Auto-bias circuit
- Sync tip clamp circuit
- Sample-and-hold circuit
- PLL 4 × frequency multiplier circuit
- VCO (4 fsc) output circuit

Features

- Single 5 V power supply
- The provision of a built-in 4 × frequency multiplier circuit allows the LC89960, 89960M to operate as a high bandwidth delay line from a 3.58 MHz clock input.
- Built-in peripheral circuits allow operation with minimal external circuits.
- Positive phase signal input, reverse phase signal output

Package Dimensions

unit: mm

3003A-DIP14





3034A-MFP14



Specifications

Absolute Maximum Ratings at $Ta = 25^{\circ}C$

Parameter	Symbol	Conditions	Ratings	Unit
Maximum supply voltage	V _{DD} max		-0.3 to +6.0	V
Allowable power dissipation	Pd max	LC89960	450	mW
		LC89960M	250	mW
Operating temperature	Topr		-10 to +60	°C
Storage temperature	Tstg		-55 to +125	°C

SANYO Electric Co., Ltd. Semiconductor Bussiness Headquarters TOKYO OFFICE Tokyo Bldg., 1-10, 1 Chome, Ueno, Taito-ku, TOKYO, 110-8534 JAPAN

53098HA (OT) /42895TH (OT) No. 4544-1/4

LC89960, 89960M

Allowable Operating Ranges at $Ta = 25^{\circ}C$

Parameter	Symbol	Conditions	min	typ	max	Unit
Supply voltage	V _{DD}		4.75	5.00	5.25	V
Clock input amplitude	V _{CLK}	Sine wave	300	500	1000	mVp-p
Clock frequency	F _{CLK}			3.579545		MHz
Signal input amplitude	VIN	*		500	572	mVp-p

Note: * Since sync tip clamping is normally performed, the input signal must be connected in a low impedance state.

Pin Assignment



Pin Functions

Pin No.	Symbol	Function
1	IN	Signal input
2	COMP	Duty correction output
3	NC	
4	OUT	Delayed signal output
5	V _{SS}	GND
6	V _{SS}	GND
7	VCO OUT	VCO output
8	CLK	Clock input
9	V _{DD}	Power supply
10	PC OUT	Phase comparator output
11	VCO IN	VCO input
12	V _{DD}	Power supply
13	RD	High voltage generator output for Reset Drain
14	V _{SS}	GND

Block Diagram



LC89960, 89960M

Electrical Characteristics at Ta = 25 $^{\circ}C,$ V_{DD} = 5.0 V, CLK = 3.579545 MHz; 500 mVp-p

Parameter	Symbol	Conditions	min	typ	max	Linit
Faiallielei	Symbol	Conditions	111111	typ	IIIdX	Unit
Supply current	I _{DD}	No signal input	15	25	35	mA
Voltage gain	GV	With a 200 kHz 0.5 Vp-p input	-2.5	-0.5	+1.5	dB
Frequency response	Gf	3.58 MHz, 0.2 Vp-p/200 kHz, 0.2 Vp-p	-2	-1	0	dB
Differential gain	D _G	*1	0	5	7	%
Differential phase	DP	*1	0	5	7	deg
Linearity (SYNC)	LS	*2	37	40	43	%
Clock leakage	L _{CLK}	No signal input, the 4 fsc component		15	50	mVrms
Noise level	NO	No signal input, 0.2 to 4.2 MHz bandwidth With the fsc trap		1.0	3.0	mVrms
Output impedance	ZO		100	250	500	Ω
Delay time	TD			63.28		μs

Note: 1. Input signal/output signal



A01723

2. Input signal/output signal



Downloaded from **Elcodis.com** electronic components distributor

Sample Application Circuit



- No products described or contained herein are intended for use in surgical implants, life-support systems, aerospace equipment, nuclear power control systems, vehicles, disaster/crime-prevention equipment and the like, the failure of which may directly or indirectly cause injury, death or property loss.
- Anyone purchasing any products described or contained herein for an above-mentioned use shall:
 - ① Accept full responsibility and indemnify and defend SANYO ELECTRIC CO., LTD., its affiliates, subsidiaries and distributors and all their officers and employees, jointly and severally, against any and all claims and litigation and all damages, cost and expenses associated with such use:
- ② Not impose any responsibility for any fault or negligence which may be cited in any such claim or litigation on SANYO ELECTRIC CO., LTD., its affiliates, subsidiaries and distributors or any of their officers and employees jointly or severally.
- Information (including circuit diagrams and circuit parameters) herein is for example only; it is not guaranteed for volume production. SANYO believes information herein is accurate and reliable, but no guarantees are made or implied regarding its use or any infringements of intellectual property rights or other rights of third parties.

This catalog provide information as of May, 1998. Specifications and information herein are subject to change without notice.