

Advance Information

MPC7455ARXPXNS/D
Rev. 1, 7/2003

MPC7455 Part Number
Specification for the
XC7455ARXnnnPx Series



Motorola Part Numbers Affected:

XC7455ARX1000PF
XC7455ARX1250PF
XC7455ARX1333PF

This document describes part-number-specific changes to recommended operating conditions and revised electrical specifications, as applicable, from those described in the general *MPC7455 RISC Microprocessor Hardware Specifications* (Order No. MPC7455EC/D). The products detailed here are PowerPC™ microprocessors.

Specifications provided in this document supersede those in the *MPC7455 RISC Microprocessor Hardware Specifications*, Rev. 2 or later, for the part numbers listed in Table A only. Specifications not addressed herein are unchanged. Because this document is frequently updated, refer to your Motorola sales office for the latest version.

Note that headings and table numbers in this document are not consecutively numbered. They are intended to correspond to the heading or table affected in the general hardware specification.

Part numbers addressed in this document are listed in Table A.

Table A. Part Numbers Addressed by this Data Sheet

Motorola Part Numbers	Operating Conditions			Significant Differences from Hardware Specification
	Max. Core Frequency (MHz)	V _{DD}	T _J (°C)	
XC7455ARX1000PF	1000	1.57 V +30/-50 mV	0 to 65	Modified core voltage, temperature and system bus AC specifications, support for 167-MHz system bus in MPX mode.
XC7455ARX1250PF	1250			
XC7455ARX1333PF	1333			

Note: The X prefix in a Motorola part number designates a "Pilot Production Prototype" as defined by Motorola SOP 3-13. These are from a limited production volume of prototypes manufactured, tested, and Q.A. inspected on a qualified technology to simulate normal production. These parts have only preliminary reliability and characterization data. Before pilot production prototypes may be shipped, written authorization from the customer must be on file in the applicable sales office acknowledging the qualification status and the fact that product changes may still occur while shipping pilot production prototypes.

Features

1.1 Features

This section summarizes changes to the features of the MPC7455 described in the *MPC7455 RISC Microprocessor Hardware Specifications*.

- Power management
 - 1.57-V processor core

1.4 General Parameters

- Core power supply: 1.57 V +30/–50 mV DC nominal

1.5.1 DC Electrical Characteristics

Table 4 provides the recommended operating conditions for the MPC7455 part numbers described herein.

Table 4. Recommended Operating Conditions

Characteristic	Symbol	Recommended Value	Unit
Core supply voltage	V_{DD}	1.57 V +30/–50 mV	V
PLL supply voltage	AV_{DD}	1.57 V +30/–50 mV	V
Die-junction temperature	T_j	0 to 65	°C

Note: These are the recommended and tested operating conditions. Proper device operation outside of these conditions is not guaranteed.

Table 7 provides the power consumption for the MPC7455 part numbers described herein.

Table 7. Power Consumption for MPC7455

	Processor Core Frequency	Unit	Notes
	1000, 1250, 1333 MHz		
Full-Power Mode			
Typical	30.0	W	1, 3
Maximum	40.0	W	1, 2
Doze Mode			
Typical	—	W	1, 2, 4
Nap Mode			
Typical	8.0	W	1, 2
Sleep Mode			
Typical	8.0	W	1, 2
Deep Sleep Mode (PLL Disabled)			
Typical	8.0	W	1, 3

Notes:

1. These values apply for all valid processor bus and L3 bus ratios. The values do not include I/O supply power (OV_{DD} and GV_{DD}) or PLL supply power (AV_{DD}). OV_{DD} and GV_{DD} power is system dependent, but is typically <5% of V_{DD} power. Worst case power consumption for $AV_{DD} < 3$ mW.
2. Maximum power is measured at nominal V_{DD} while running an entirely cache-resident, contrived sequence of instructions which keep the execution units, with or without AltiVec, maximally busy.
3. Typical power is an average value measured at nominal V_{DD} and 65°C in a system while running a typical code sequence.
4. Doze mode is not a user-definable state; it is an intermediate state between Full-power and either Nap or Sleep mode. As a result, power consumption for this mode is not tested.

General Parameters

1.5.2.1 Clock AC Specifications

Table 9. Clock AC Timing Specifications

At recommended operating conditions. See Table 4.

Characteristic	Symbol	Processor Core Frequency						Unit
		1000 MHz		1250 MHz		1333 MHz		
		Min	Max	Min	Max	Min	Max	
Processor frequency	f_{core}	500	1000	500	1250	500	1333	MHz
VCO frequency	f_{VCO}	1000	2000	1000	2500	1000	2666	MHz
SYSCLK frequency	f_{SYSCLK}							MHz
MPX bus mode		33	167	33	167	33	167	
60x bus mode		33	133	33	133	33	133	
SYSCLK cycle time	t_{SYSCLK}							ns
MPX bus mode		6.0	30	6.0	30	6.0	30	
60x bus mode		7.5	30	7.5	30	7.5	30	

1.5.2.2 Processor Bus AC Specifications

Table 10. Processor Bus AC Timing Specifications

At recommended operating conditions. See Table 4.

Parameter	Symbol	MPX bus mode		60x bus mode		Unit
		Min	Max	Min	Max	
Input setup times: A[0:35], AP[0:4], $\overline{\text{GBL}}$, $\overline{\text{TBST}}$, $\overline{\text{TSIZ}}[0:2]$, $\overline{\text{WT}}$, $\overline{\text{CI}}$, D[0:63], DP[0:7]	t_{AVKH}	1.5	—	2.0	—	ns
$\overline{\text{AACK}}$, $\overline{\text{ARTRY}}$, $\overline{\text{BG}}$, $\overline{\text{CKSTP_IN}}$, $\overline{\text{DBG}}$, $\overline{\text{DTI}}[0:3]$, $\overline{\text{HRESET}}$, $\overline{\text{INT}}$, $\overline{\text{MCP}}$, $\overline{\text{QACK}}$, $\overline{\text{SMI}}$, $\overline{\text{SRESET}}$, $\overline{\text{TA}}$, $\overline{\text{TBEN}}$, $\overline{\text{TEA}}$, $\overline{\text{TS}}$, $\overline{\text{EXT_QUAL}}$, $\overline{\text{PMON_IN}}$, $\overline{\text{SHD}}[0:1]$	t_{IVKH}	1.5	—	2.0	—	
Input hold times: A[0:35], AP[0:4], $\overline{\text{GBL}}$, $\overline{\text{TBST}}$, $\overline{\text{TSIZ}}[0:2]$, $\overline{\text{WT}}$, $\overline{\text{CI}}$, D[0:63], DP[0:7]	t_{AXKH}	0	—	0	—	ns
$\overline{\text{AACK}}$, $\overline{\text{ARTRY}}$, $\overline{\text{BG}}$, $\overline{\text{CKSTP_IN}}$, $\overline{\text{DBG}}$, $\overline{\text{DTI}}[0:3]$, $\overline{\text{HRESET}}$, $\overline{\text{INT}}$, $\overline{\text{MCP}}$, $\overline{\text{QACK}}$, $\overline{\text{SMI}}$, $\overline{\text{SRESET}}$, $\overline{\text{TA}}$, $\overline{\text{TBEN}}$, $\overline{\text{TEA}}$, $\overline{\text{TS}}$, $\overline{\text{EXT_QUAL}}$, $\overline{\text{PMON_IN}}$, $\overline{\text{SHD}}[0:1]$	t_{IXKH}	0	—	0	—	
Output valid times: A[0:35], AP[0:4], $\overline{\text{GBL}}$, $\overline{\text{TBST}}$, $\overline{\text{TSIZ}}[0:2]$, $\overline{\text{WT}}$, $\overline{\text{CI}}$ $\overline{\text{TS}}$ D[0:63], DP[0:7] $\overline{\text{ARTRY}}/\overline{\text{SHD0}}/\overline{\text{SHD1}}$ $\overline{\text{BR}}$, $\overline{\text{CKSTP_OUT}}$, $\overline{\text{DRDY}}$, $\overline{\text{HIT}}$, $\overline{\text{PMON_OUT}}$, $\overline{\text{QREQ}}$	t_{KHAV} t_{KHTSV} t_{KHDV} t_{KHARV} t_{KHOV}	—	2.0	—	2.5	ns
		—	2.0	—	2.5	
		—	2.0	—	2.5	
		—	2.0	—	2.5	
		—	2.0	—	2.5	
Output hold times: A[0:35], AP[0:4], $\overline{\text{GBL}}$, $\overline{\text{TBST}}$, $\overline{\text{TSIZ}}[0:2]$, $\overline{\text{WT}}$, $\overline{\text{CI}}$ $\overline{\text{TS}}$ D[0:63], DP[0:7] $\overline{\text{ARTRY}}/\overline{\text{SHD0}}/\overline{\text{SHD1}}$ $\overline{\text{BR}}$, $\overline{\text{CKSTP_OUT}}$, $\overline{\text{DRDY}}$, $\overline{\text{HIT}}$, $\overline{\text{PMON_OUT}}$, $\overline{\text{QREQ}}$	t_{KHAX} t_{KHTSX} t_{KHDX} t_{KHARX} t_{KHOX}	0.5	—	0.5	—	ns
		0.5	—	0.5	—	
		0.5	—	0.5	—	
		0.5	—	0.5	—	
		0.5	—	0.5	—	

1.11 Ordering Information

1.11.1 Part Numbers Addressed by this Specification

Table 20 provides the ordering information for the MPC7455 parts described in this document.

Table 20. Part Marking Nomenclature


XC	7455	A	RX	nnn	x	x
Product Code	Part Identifier	Process Descriptor	Package	Processor Frequency¹	Application Modifier	Revision Level
XC ²	7455	A	RX = CBGA	1000 1250 1333	P: 1.57 V +30/-50 mV 0 to 65°C	F: 3.3; PVR = 8001 0303

Notes:

1. Processor core frequencies supported by parts addressed by this specification only. Parts addressed by other specifications may support other maximum core frequencies.
2. The X prefix in a Motorola part number designates a “Pilot Production Prototype” as defined by Motorola SOP 3-13. These are from a limited production volume of prototypes manufactured, tested, and Q.A. inspected on a qualified technology to simulate normal production. These parts have only preliminary reliability and characterization data. Before pilot production prototypes may be shipped, written authorization from the customer must be on file in the applicable sales office acknowledging the qualification status and the fact that product changes may still occur while shipping pilot production prototypes.

1.11.3 Part Marking

Parts are marked as the example shown in Figure 27.



Notes:

- MMMMMM is the 6-digit mask number.
- ATWLYYWWA is the traceability code.
- CCCCC is the country of assembly. This space is left blank if parts are assembled in the United States.

Figure 27. Motorola Part Marking for BGA Device

Document Revision History

Table B provides a revision history for this part number specification.

Table B. Document Revision History

Rev. No.	Substantive Change(s)
0	Initial release.
1	Removed 1400 MHz speed grade from all specifications; this was a documentation error only and does not reflect a change in the test regime or supported core frequencies.
	Corrected core frequency specifications and column headings in Table 9.

HOW TO REACH US:

USA/EUROPE/LOCATIONS NOT LISTED:

Motorola Literature Distribution
P.O. Box 5405, Denver, Colorado 80217
1-480-768-2130
(800) 521-6274

JAPAN:

Motorola Japan Ltd.
SPS, Technical Information Center
3-20-1, Minami-Azabu Minato-ku
Tokyo 106-8573 Japan
81-3-3440-3569

ASIA/PACIFIC:

Motorola Semiconductors H.K. Ltd.
Silicon Harbour Centre, 2 Dai King Street
Tai Po Industrial Estate, Tai Po, N.T., Hong Kong
852-26668334

TECHNICAL INFORMATION CENTER:

(800) 521-6274

HOME PAGE:

www.motorola.com/semiconductors

Information in this document is provided solely to enable system and software implementers to use Motorola products. There are no express or implied copyright licenses granted hereunder to design or fabricate any integrated circuits or integrated circuits based on the information in this document.

Motorola reserves the right to make changes without further notice to any products herein.

Motorola makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does Motorola assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation consequential or incidental damages. "Typical" parameters which may be provided in Motorola data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. Motorola does not convey any license under its patent rights nor the rights of others. Motorola products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the Motorola product could create a situation where personal injury or death may occur. Should Buyer purchase or use Motorola products for any such unintended or unauthorized application, Buyer shall indemnify and hold Motorola and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that Motorola was negligent regarding the design or manufacture of the part.



Motorola and the Stylized M Logo are registered in the U.S. Patent and Trademark Office. digital dna is a trademark of Motorola, Inc. The described product is a PowerPC microprocessor. The PowerPC name is a trademark of IBM Corp. and used under license. All other product or service names are the property of their respective owners. Motorola, Inc. is an Equal Opportunity/Affirmative Action Employer.

© Motorola, Inc. 2003

MPC7455ARXPXNS/D