


# SN74LS245

## Octal Bus Transceiver

The SN74LS245 is an Octal Bus Transmitter/Receiver designed for 8-line asynchronous 2-way data communication between data buses. Direction Input (DR) controls transmission of Data from bus A to bus B or bus B to bus A depending upon its logic level. The Enable input ( $\bar{E}$ ) can be used to isolate the buses.

- Hysteresis Inputs to Improve Noise Immunity
- 2-Way Asynchronous Data Bus Communication
- Input Diodes Limit High-Speed Termination Effects
- ESD > 3500 Volts

### LOGIC AND CONNECTION DIAGRAMS DIP (TOP VIEW)



### TRUTH TABLE

| INPUTS    |     | OUTPUT              |
|-----------|-----|---------------------|
| $\bar{E}$ | DIR |                     |
| L         | L   | Bus B Data to Bus A |
| L         | H   | Bus A Data to Bus B |
| H         | X   | Isolation           |

H = HIGH Voltage Level  
L = LOW Voltage Level  
X = Immaterial


### GUARANTEED OPERATING RANGES

| Symbol   | Parameter                           | Min  | Typ | Max  | Unit |
|----------|-------------------------------------|------|-----|------|------|
| $V_{CC}$ | Supply Voltage                      | 4.75 | 5.0 | 5.25 | V    |
| $T_A$    | Operating Ambient Temperature Range | 0    | 25  | 70   | °C   |
| $I_{OH}$ | Output Current – High               |      |     | -3.0 | mA   |
|          |                                     |      |     | -15  | mA   |
| $I_{OL}$ | Output Current – Low                |      |     | 24   | mA   |




**ON Semiconductor**  
Formerly a Division of Motorola  
<http://onsemi.com>

**LOW  
POWER  
SCHOTTKY**



PLASTIC  
N SUFFIX  
CASE 738



SOIC  
DW SUFFIX  
CASE 751D

### ORDERING INFORMATION

| Device      | Package    | Shipping         |
|-------------|------------|------------------|
| SN74LS245N  | 16 Pin DIP | 1440 Units/Box   |
| SN74LS245DW | 16 Pin     | 2500/Tape & Reel |

# SN74LS245

## DC CHARACTERISTICS OVER OPERATING TEMPERATURE RANGE (unless otherwise specified)

| Symbol                           | Parameter                               | Limits          |       |      | Unit | Test Conditions                                  |
|----------------------------------|---|-----------------|-------|------|------|--|
|                                  |   | Min             | Typ   | Max  |      |  |
| V <sub>IH</sub>                  | Input HIGH Voltage                      | 2.0             |       |      | V    | Guaranteed Input HIGH Voltage for All Inputs     |
| V <sub>IL</sub>                  | Input LOW Voltage                       |                 |       | 0.8  | V    | Guaranteed Input LOW Voltage for All Inputs      |
| V <sub>T+</sub> -V <sub>T-</sub> | Hysteresis                              | 0.2             | 0.4   |      | V    | V <sub>CC</sub> = MIN                            |
| V <sub>IK</sub>                  | Input Clamp Diode Voltage               |                 | -0.65 | -1.5 | V    | V <sub>CC</sub> = MIN, I <sub>IN</sub> = -18 mA  |
| V <sub>OH</sub>                  | Output HIGH Voltage                     | 2.4             | 3.4   |      | V    | V <sub>CC</sub> = MIN, I <sub>OH</sub> = -3.0 mA |
|                                  |   | 2.0             |       |      | V    | V <sub>CC</sub> = MIN, I <sub>OH</sub> = MAX     |
| V <sub>OL</sub>                  | Output LOW Voltage                      |                 | 0.25  | 0.4  | V    | I <sub>OL</sub> = 12 mA                          |
|                                  |   |                 | 0.35  | 0.5  | V    | I <sub>OL</sub> = 24 mA                          |
| I <sub>OZH</sub>                 | Output Off Current HIGH                 |                 |       | 20   | μA   | V <sub>CC</sub> = MAX, V <sub>OUT</sub> = 2.7 V  |
| I <sub>OZL</sub>                 | Output Off Current LOW                  |                 |       | -200 | μA   | V <sub>CC</sub> = MAX, V <sub>OUT</sub> = 0.4 V  |
| I <sub>IH</sub>                  | Input HIGH Current                      | A or B, DR or E |       | 20   | μA   | V <sub>CC</sub> = MAX, V <sub>IN</sub> = 2.7 V   |
|                                  |   | DR or E         |       | 0.1  | mA   | V <sub>CC</sub> = MAX, V <sub>IN</sub> = 7.0 V   |
|                                  |   | A or B          |       | 0.1  | mA   | V <sub>CC</sub> = MAX, V <sub>IN</sub> = 5.5 V   |
| I <sub>IL</sub>                  | Input LOW Current                       |                 |       | -0.2 | mA   | V <sub>CC</sub> = MAX, V <sub>IN</sub> = 0.4 V   |
| I <sub>OS</sub>                  | Output Short Circuit Current (Note 1)   | -40             |       | -225 | mA   | V <sub>CC</sub> = MAX                            |
| I <sub>CC</sub>                  | Power Supply Current Total, Output HIGH |                 |       | 70   | mA   | V <sub>CC</sub> = MAX                            |
|                                  | Total, Output LOW                       |                 |       | 90   |      |  |
|                                  | Total at HIGH Z                         |                 |       | 95   |      |  |

Note 1: Not more than one output should be shorted at a time, nor for more than 1 second.


## AC CHARACTERISTICS (T<sub>A</sub> = 25°C, V<sub>CC</sub> = 5.0 V, T<sub>RISE</sub>/T<sub>FALL</sub> ≤ 6.0 ns)

| Symbol                               | Parameter                           | Limits |            |          | Unit | Test Conditions                                    |
|--------------------------------------|-------------------------------------|--------|------------|----------|------|--|
|                                      |                                     | Min    | Typ        | Max      |      |  |
| t <sub>PLH</sub><br>t <sub>PHL</sub> | Propagation Delay, Data to Output   |        | 8.0<br>8.0 | 12<br>12 | ns   | C <sub>L</sub> = 45 pF,<br>R <sub>L</sub> = 667 Ω  |
| t <sub>PZH</sub>                     | Output Enable Time to HIGH Level    |        | 25         | 40       |      |  |
| t <sub>PZL</sub>                     | Output Enable Time to LOW Level     |        | 27         | 40       |      |  |
| t <sub>PLZ</sub>                     | Output Disable Time from LOW Level  |        | 15         | 25       | ns   | C <sub>L</sub> = 5.0 pF,<br>R <sub>L</sub> = 667 Ω |
| t <sub>PHZ</sub>                     | Output Disable Time from HIGH Level |        | 15         | 25       |      |  |

# SN74LS245

## PACKAGE DIMENSIONS


### N SUFFIX PLASTIC PACKAGE CASE 738-03 ISSUE E



- NOTES:
1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
  2. CONTROLLING DIMENSION: INCH.
  3. DIMENSION L TO CENTER OF LEAD WHEN FORMED PARALLEL.
  4. DIMENSION B DOES NOT INCLUDE MOLD FLASH.


| DIM | INCHES    |       | MILLIMETERS |       |
|-----|-----------|-------|-------------|-------|
|     | MIN       | MAX   | MIN         | MAX   |
| A   | 1.010     | 1.070 | 25.66       | 27.17 |
| B   | 0.240     | 0.260 | 6.10        | 6.60  |
| C   | 0.150     | 0.180 | 3.81        | 4.57  |
| D   | 0.015     | 0.022 | 0.39        | 0.55  |
| E   | 0.050 BSC |       | 1.27 BSC    |       |
| F   | 0.050     | 0.070 | 1.27        | 1.77  |
| G   | 0.100 BSC |       | 2.54 BSC    |       |
| J   | 0.008     | 0.015 | 0.21        | 0.38  |
| K   | 0.110     | 0.140 | 2.80        | 3.55  |
| L   | 0.300 BSC |       | 7.62 BSC    |       |
| M   | 0°        | 15°   | 0°          | 15°   |
| N   | 0.020     | 0.040 | 0.51        | 1.01  |

### D SUFFIX PLASTIC SOIC PACKAGE CASE 751D-05 ISSUE F



- NOTES:
1. DIMENSIONS ARE IN MILLIMETERS.
  2. INTERPRET DIMENSIONS AND TOLERANCES PER ASME Y14.5M, 1994.
  3. DIMENSIONS D AND E DO NOT INCLUDE MOLD PROTRUSION.
  4. MAXIMUM MOLD PROTRUSION 0.15 PER SIDE.
  5. DIMENSION B DOES NOT INCLUDE DAMBAR PROTRUSION. ALLOWABLE PROTRUSION SHALL BE 0.13 TOTAL IN EXCESS OF B DIMENSION AT MAXIMUM MATERIAL CONDITION.

| DIM | MILLIMETERS |       |
|-----|-------------|-------|
|     | MIN         | MAX   |
| A   | 2.35        | 2.65  |
| A1  | 0.10        | 0.25  |
| B   | 0.35        | 0.49  |
| C   | 0.23        | 0.32  |
| D   | 12.65       | 12.95 |
| E   | 7.40        | 7.60  |
| e   | 1.27 BSC    |       |
| H   | 10.05       | 10.55 |
| h   | 0.25        | 0.75  |
| L   | 0.50        | 0.90  |
| θ   | 0°          | 7°    |

**ON Semiconductor** and  are trademarks of Semiconductor Components Industries, LLC (SCILLC). SCILLC reserves the right to make changes without further notice to any products herein. SCILLC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does SCILLC assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. "Typical" parameters which may be provided in SCILLC data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. SCILLC does not convey any license under its patent rights nor the rights of others. SCILLC products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the SCILLC product could create a situation where personal injury or death may occur. Should Buyer purchase or use SCILLC products for any such unintended or unauthorized application, Buyer shall indemnify and hold SCILLC and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that SCILLC was negligent regarding the design or manufacture of the part. SCILLC is an Equal Opportunity/Affirmative Action Employer.

## PUBLICATION ORDERING INFORMATION

### North America Literature Fulfillment:

Literature Distribution Center for ON Semiconductor  
P.O. Box 5163, Denver, Colorado 80217 USA  
**Phone:** 303-675-2175 or 800-344-3860 Toll Free USA/Canada  
**Fax:** 303-675-2176 or 800-344-3867 Toll Free USA/Canada  
**Email:** ONlit@hibbertco.com

**N. American Technical Support:** 800-282-9855 Toll Free USA/Canada

**EUROPE:** LDC for ON Semiconductor – European Support

**German Phone:** (+1) 303-308-7140 (M-F 2:30pm to 5:00pm Munich Time)

**Email:** ONlit-german@hibbertco.com

**French Phone:** (+1) 303-308-7141 (M-F 2:30pm to 5:00pm Toulouse Time)

**Email:** ONlit-french@hibbertco.com

**English Phone:** (+1) 303-308-7142 (M-F 1:30pm to 5:00pm UK Time)

**Email:** ONlit@hibbertco.com

**ASIA/PACIFIC:** LDC for ON Semiconductor – Asia Support

**Phone:** 303-675-2121 (Tue-Fri 9:00am to 1:00pm, Hong Kong Time)  
Toll Free from Hong Kong 800-4422-3781

**Email:** ONlit-asia@hibbertco.com

**JAPAN:** ON Semiconductor, Japan Customer Focus Center

4-32-1 Nishi-Gotanda, Shinagawa-ku, Tokyo, Japan 141-8549

**Phone:** 81-3-5487-8345

**Email:** r14153@onsemi.com

**Fax Response Line:** 303-675-2167

800-344-3810 Toll Free USA/Canada

**ON Semiconductor Website:** <http://onsemi.com>

For additional information, please contact your local  
Sales Representative.