

Photointerrupters(Transmissive)

KODENSHI

SG - 260

The SG - 260 photointerrupter high - performance standard type, combines high - output GaAs IRED with high sensitive phototransistor.

FEATURES


- PWB direct mount type
- GAP : 3.0mm
- Snap-in mount
- With the installation positioning boss
- Optical axis height from the mounting surface : 20.75mm

APPLICATIONS

- VTR
- Cassette mecha

DIMENSIONS

(Unit : mm)



MAXIMUM RATINGS

(Ta=25)

Item	Symbol	Rating	Unit
Input	P _D	75	mW
	I _F	50	mA
	V _R	5	V
	I _{FP}	0.5	A
Output	P _C	75	mW
	I _C	20	mA
	V _{CEO}	30	V
	V _{ECO}	5	V
Operating temp. ¹	Topr.	- 20 ~ + 85	
Storage temp. ²	Tstg.	- 30 ~ + 100	
Soldering temp. ³	Tsol.	260	

¹. pulse width : t w = 100 sec. period : T=10msec.

². No icebound or dew

³. For MAX.5 seconds at the position of 1mm from the package

ELECTRO-OPTICAL CHARACTERISTICS


(Ta=25)

Item	Symbol	Conditions	Min.	Typ.	Max.	Unit.
Input	V _F	I _F =20mA		1.2	1.4	V
	I _R	V _R =5V			10	µA
	p	I _F =20mA		940		nm
Output	I _{CEO}	V _{CE} =10V		1	100	nA
Transmission	I _C	I _F =20mA, V _E =5V, Non-shading	0.5		5	mA
leakage current	I _{CEO0}	I _F =20mA, V _E =5V(shading)		0.5	10	µA
	V _{CE(sat)}	I _F =20mA, I _C =0.05mA		0.15	0.4	V
Rise time	tr	V _{CC} =5V, I _E =0.1mA, R=1K		50		µsec.
Fall time	tf			50		µsec.


Photointerrupters(Transmissive)

SG - 260


**Collector power dissipation Vs.
Ambient temperature**




**Forward current Vs.
Forward voltage**




**Light current Vs.
Forward current**




**Light current Vs.
Collector-Emitter voltage**




**Relative light current Vs.
Ambient temperature**




**Dark current Vs.
Ambient temperature**




**Switching time Vs.
Load resistance**



**Relative light current Vs.
Moving distance**



Switching time measurement circuit



Method of measuring position detection characteristic

