

## **General Purpose NPN Transistor Arrays**

The CA3045 and CA3046 each consist of five general purpose silicon NPN transistors on a common monolithic substrate. Two of the transistors are internally connected to form a differentially connected pair.


The transistors of the CA3045 and CA3046 are well suited to a wide variety of applications in low power systems in the DC through VHF range. They may be used as discrete transistors in conventional circuits. However, in addition, they provide the very significant inherent integrated circuit advantages of close electrical and thermal matching.

### **Ordering Information**

PART NUMBER (BRAND)	TEMP. RANGE (°C)	PACKAGE	PKG. NO.
CA3045F	-55 to 125	14 Ld CERDIP	F14.3
CA3046	-55 to 125	14 Ld PDIP	E14.3
CA3046M (3046)	-55 to 125	14 Ld SOIC	M14.15
CA3046M96 (3046)	-55 to 125	14 Ld SOIC Tape and Reel	M14.15

### **Pinout**

**CA3045, (CERDIP)  
CA3046 (PDIP, SOIC)  
TOP VIEW**



### **Features**

- Two Matched Transistors
  - $V_{BE}$  Match .....  $\pm 5\text{mV}$
  - $I_{IO}$  Match .....  $2\mu\text{A}$  (Max)
- Low Noise Figure ..... 3.2dB (Typ) at 1kHz
- 5 General Purpose Monolithic Transistors
- Operation From DC to 120MHz
- Wide Operating Current Range
- Full Military Temperature Range

### **Applications**

- Three Isolated Transistors and One Differentially Connected Transistor Pair for Low Power Applications at Frequencies from DC Through the VHF Range
- Custom Designed Differential Amplifiers
- Temperature Compensated Amplifiers
- See Application Note, AN5296 "Application of the CA3018 Integrated-Circuit Transistor Array" for Suggested Applications

**Absolute Maximum Ratings**

Collector-to-Emitter Voltage ( $V_{CEO}$ ) .....	15V
Collector-to-Base Voltage ( $V_{CBO}$ ) .....	20V
Collector-to-Substrate Voltage ( $V_{CIO}$ , Note 1) .....	20V
Emitter-to-Base Voltage ( $V_{EBO}$ ) .....	5V
Collector Current ( $I_C$ ) .....	50mA

**Operating Conditions**

Temperature Range .....	-55°C to 125°C
-------------------------	----------------

**Thermal Information**

Thermal Resistance (Typical, Note 2)	$\theta_{JA}$ (°C/W)	$\theta_{JC}$ (°C/W)
PDIP Package .....	180	N/A
CERDIP Package .....	150	75
SOIC Package .....	220	N/A
Maximum Power Dissipation (Any One Transistor) .....	300mW	
Maximum Junction Temperature (Hermetic Packages) .....	175°C	
Maximum Junction Temperature (Plastic Package) .....	150°C	
Maximum Storage Temperature Range .....	-65°C to 150°C	
Maximum Lead Temperature (Soldering 10s) .....	300°C	
(SOIC - Lead Tips Only)		

CAUTION: Stresses above those listed in "Absolute Maximum Ratings" may cause permanent damage to the device. This is a stress only rating and operation of the device at these or any other conditions above those indicated in the operational sections of this specification is not implied.

## NOTES:

1. The collector of each transistor of the CA3045 and CA3046 is isolated from the substrate by an integral diode. The substrate (Terminal 13) must be connected to the most negative point in the external circuit to maintain isolation between transistors and to provide for normal transistor action.
2.  $\theta_{JA}$  is measured with the component mounted on an evaluation PC board in free air.

**Electrical Specifications**  $T_A = 25^\circ\text{C}$ , characteristics apply for each transistor in CA3045 and CA3046 as specified

PARAMETER	SYMBOL	TEST CONDITIONS		MIN	TYP	MAX	UNITS
<b>DC CHARACTERISTICS</b>							
Collector-to-Base Breakdown Voltage	$V_{(BR)CBO}$	$I_C = 10\mu\text{A}$ , $I_E = 0$		20	60	-	V
Collector-to-Emitter Breakdown Voltage	$V_{(BR)CEO}$	$I_C = 1\text{mA}$ , $I_B = 0$		15	24	-	V
Collector-to-Substrate Breakdown Voltage	$V_{(BR)CIO}$	$I_C = 10\mu\text{A}$ , $I_{CI} = 0$		20	60	-	V
Emitter-to-Base Breakdown Voltage	$V_{(BR)EBO}$	$I_E = 10\mu\text{A}$ , $I_C = 0$		5	7	-	V
Collector Cutoff Current (Figure 1)	$I_{CBO}$	$V_{CB} = 10\text{V}$ , $I_E = 0$		-	0.002	40	nA
Collector Cutoff Current (Figure 2)	$I_{CEO}$	$V_{CE} = 10\text{V}$ , $I_B = 0$		-	See Fig. 2	0.5	$\mu\text{A}$
Forward Current Transfer Ratio (Static Beta) (Note 3) (Figure 3)	$h_{FE}$	$V_{CE} = 3\text{V}$	$I_C = 10\text{mA}$	-	100	-	-
			$I_C = 1\text{mA}$	40	100	-	-
			$I_C = 10\mu\text{A}$	-	54	-	-
Input Offset Current for Matched Pair $Q_1$ and $Q_2$ . $ I_{IO1} - I_{IO2} $ (Note 3) (Figure 4)		$V_{CE} = 3\text{V}$ , $I_C = 1\text{mA}$		-	0.3	2	$\mu\text{A}$
Base-to-Emitter Voltage (Note 3) (Figure 5)	$V_{BE}$	$V_{CE} = 3\text{V}$	$I_E = 1\text{mA}$	-	0.715	-	V
			$I_E = 10\text{mA}$	-	0.800	-	V
Magnitude of Input Offset Voltage for Differential Pair $ V_{BE1} - V_{BE2} $ (Note 3) (Figures 5, 7)		$V_{CE} = 3\text{V}$ , $I_C = 1\text{mA}$		-	0.45	5	mV
Magnitude of Input Offset Voltage for Isolated Transistors $ V_{BE3} - V_{BE4} $ , $ V_{BE4} - V_{BE5} $ , $ V_{BE5} - V_{BE3} $ (Note 3) (Figures 5, 7)		$V_{CE} = 3\text{V}$ , $I_C = 1\text{mA}$		-	0.45	5	mV
Temperature Coefficient of Base-to-Emitter Voltage (Figure 6)	$\frac{\Delta V_{BE}}{\Delta T}$	$V_{CE} = 3\text{V}$ , $I_C = 1\text{mA}$		-	-1.9	-	$\text{mV}/^\circ\text{C}$
Collector-to-Emitter Saturation Voltage	$V_{CES}$	$I_B = 1\text{mA}$ , $I_C = 10\text{mA}$		-	0.23	-	V
Temperature Coefficient: Magnitude of Input Off- set Voltage (Figure 7)	$\frac{ \Delta V_{IO} }{\Delta T}$	$V_{CE} = 3\text{V}$ , $I_C = 1\text{mA}$		-	1.1	-	$\mu\text{V}/^\circ\text{C}$
<b>DYNAMIC CHARACTERISTICS</b>							
Low Frequency Noise Figure (Figure 9)	NF	$f = 1\text{kHz}$ , $V_{CE} = 3\text{V}$ , $I_C = 100\mu\text{A}$ , Source Resistance = $1\text{k}\Omega$		-	3.25	-	dB
Low Frequency, Small Signal Equivalent Circuit Characteristics							
Forward Current Transfer Ratio (Figure 11)	$h_{FE}$	$f = 1\text{kHz}$ , $V_{CE} = 3\text{V}$ , $I_C = 1\text{mA}$		-	110	-	-
Short Circuit Input Impedance (Figure 11)	$h_{IE}$	$f = 1\text{kHz}$ , $V_{CE} = 3\text{V}$ , $I_C = 1\text{mA}$		-	3.5	-	$\text{k}\Omega$

**Electrical Specifications**  $T_A = 25^\circ\text{C}$ , characteristics apply for each transistor in CA3045 and CA3046 as specified **(Continued)**

PARAMETER	SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNITS
Open Circuit Output Impedance (Figure 11)	$h_{OE}$	$f = 1\text{kHz}, V_{CE} = 3\text{V}, I_C = 1\text{mA}$	-	15.6	-	$\mu\text{S}$
Open Circuit Reverse Voltage Transfer Ratio (Figure 11)	$h_{RE}$	$f = 1\text{kHz}, V_{CE} = 3\text{V}, I_C = 1\text{mA}$	-	$1.8 \times 10^{-4}$	-	-
Admittance Characteristics						
Forward Transfer Admittance (Figure 12)	$Y_{FE}$	$f = 1\text{kHz}, V_{CE} = 3\text{V}, I_C = 1\text{mA}$	-	$31 - j1.5$	-	-
Input Admittance (Figure 13)	$Y_{IE}$	$f = 1\text{kHz}, V_{CE} = 3\text{V}, I_C = 1\text{mA}$	-	$0.3 + j0.04$	-	-
Output Admittance (Figure 14)	$Y_{OE}$	$f = 1\text{kHz}, V_{CE} = 3\text{V}, I_C = 1\text{mA}$	-	$0.001 + j0.03$	-	-
Reverse Transfer Admittance (Figure 15)	$Y_{RE}$	$f = 1\text{kHz}, V_{CE} = 3\text{V}, I_C = 1\text{mA}$	-	See Fig. 14	-	-
Gain Bandwidth Product (Figure 16)	$f_T$	$V_{CE} = 3\text{V}, I_C = 3\text{mA}$	300	550	-	MHz
Emitter-to-Base Capacitance	$C_{EB}$	$V_{EB} = 3\text{V}, I_E = 0$	-	0.6	-	pF
Collector-to-Base Capacitance	$C_{CB}$	$V_{CB} = 3\text{V}, I_C = 0$	-	0.58	-	pF
Collector-to-Substrate Capacitance	$C_{CI}$	$V_{CS} = 3\text{V}, I_C = 0$	-	2.8	-	pF

NOTE:

3. Actual forcing current is via the emitter for this test.


**Typical Performance Curves**

FIGURE 1. TYPICAL COLLECTOR-TO-BASE CUTOFF CURRENT  
vs TEMPERATURE FOR EACH TRANSISTOR




FIGURE 2. TYPICAL COLLECTOR-TO-EMITTER CUTOFF  
CURRENT vs TEMPERATURE FOR EACH  
TRANSISTOR




FIGURE 3. TYPICAL STATIC FORWARD CURRENT TRANSFER  
RATIO AND BETA RATIO FOR Q<sub>1</sub> AND Q<sub>2</sub> VS  
EMITTER CURRENT







FIGURE 4. TYPICAL INPUT OFFSET CURRENT FOR  
MATCHED TRANSISTOR PAIR Q<sub>1</sub>Q<sub>2</sub> VS  
COLLECTOR CURRENT

**Typical Performance Curves** (Continued)


**FIGURE 5. TYPICAL STATIC BASE-TO-EMITTER VOLTAGE CHARACTERISTICS AND INPUT OFFSET VOLTAGE FOR DIFFERENTIAL PAIR AND PAIRED ISOLATED TRANSISTORS vs Emitter Current**




**FIGURE 6. TYPICAL BASE-TO-EMITTER VOLTAGE CHARACTERISTIC vs TEMPERATURE FOR EACH TRANSISTOR**




**FIGURE 7. TYPICAL INPUT OFFSET VOLTAGE CHARACTERISTICS FOR DIFFERENTIAL PAIR AND PAIRED ISOLATED TRANSISTORS vs TEMPERATURE**




**FIGURE 8. TYPICAL NOISE FIGURE vs COLLECTOR CURRENT**




**FIGURE 9. TYPICAL NOISE FIGURE vs COLLECTOR CURRENT**




**FIGURE 10. TYPICAL NOISE FIGURE vs COLLECTOR CURRENT**

**Typical Performance Curves** (Continued)


**FIGURE 11. TYPICAL NORMALIZED FORWARD CURRENT TRANSFER RATIO, SHORT CIRCUIT INPUT IMPEDANCE, OPEN CIRCUIT OUTPUT IMPEDANCE, AND OPEN CIRCUIT REVERSE VOLTAGE TRANSFER RATIO vs COLLECTOR CURRENT**




**FIGURE 12. TYPICAL FORWARD TRANSFER ADMITTANCE vs FREQUENCY**




**FIGURE 13. TYPICAL INPUT ADMITTANCE vs FREQUENCY**



**FIGURE 14. TYPICAL OUTPUT ADMITTANCE vs FREQUENCY**



**FIGURE 15. TYPICAL REVERSE TRANSFER ADMITTANCE vs FREQUENCY**



**FIGURE 16. TYPICAL GAIN BANDWIDTH PRODUCT vs COLLECTOR CURRENT**