


## BXB100 Series Single output

**Total Power:** 66 - 100 W  
**Input Voltage:** 18 - 36 V  
36 - 75 V  
**# of Outputs:** Single



## Special Features

- Industry standard footprint
- High power density (36.5 W/in<sup>3</sup>)
- MTBF >1.4 million hours (Bellcore 332)
- Input voltage to ETS300-132-2
- Adjustable output voltage
- No minimum load required
- Separate case ground pin
- Undervoltage lockout (UVLO)
- UL, VDE and CSA safety approvals
- 2 year warranty

## Safety

VDE0805/EN60950/IEC950

UL1950

CSA C22.2 No. 950

## Electrical Specifications

Input		
Input voltage range:	24 Vin nominal 48 Vin nominal	18 - 36 Vdc 36 - 75 Vdc
Input current:	No load Remote OFF	100 mA max. 20 mA max.
Input current (max.): (See note 4)	48 V models	4 A max. @ Io max. and Vin = 0 to 75 V
Input reflected ripple:	(See note 6)	5 mA pk-pk
Active low remote ON/OFF: Logic compatibility:		(See note 7) Open collector ref to -input
ON:		1.2 Vdc max.
OFF:		Open circuit
Undervoltage lockout:	24 Vin: power-up 24 Vin: power-down 48 Vin: power-up 48 Vin: power-down	17 V 16 V 34 V 32.5 V
Start-up time: (see note 8)	Power up Remote ON/OFF	20 ms 20 ms
Output		
Voltage adjustability:		60% to 110%
Setpoint accuracy:		±1.0%
Line regulation:	Low line to high line	±0.05%
Load regulation:	Full load to min. load	±0.10%
Minimum load:		0 %
Overshoot:	At turn on and turn-off	None
Undershoot:		None
Ripple and noise:	3.3 V and 5 V 5 Hz - 20 MHz (see note 1)	75 mV pk-pk, 20 mV rms
	12V and 15 V	100 mV pk-pk, 30 mV rms



Output Continued		
Ripple and noise: 5 Hz - 20 MHz (see note 1)	3.3 V and 5 V	75 mV pk-pk, 20 mV rms
	12V and 15 V	100 mV pk-pk, 30 mV rms
Temperature coefficient:		±0.01% / °C
Transient response: (see note 2)		±2.0% max. deviation 170 µs recovery to within ±1.0%
Remote Sense:		0.5 Vds transmission line drop compensation

EMC Characteristics		
Conducted emissions: (see note 3)	EN55022 (See note 3)	Level A
	FCC part 15	Level A
	EN55022, CISPR22	Level A

General Specifications		
Efficiency:		See table
Isolation voltage:	Input/case	1500 Vdc
	Input/output	1500 Vdc
	Output/case	1500 Vdc
Switching frequency:	Fixed	500 kHz typ.
Approvals and standards: (see note 5)		VDE0805, EN60950, IEC950 UL1950, CSA C22.2 No. 950
Case material:	Aluminum baseplate with plastic case	
Material flammability:		UL94V-0
Weight:		110 g (3.88 oz)
MTBF:	Bellcore 332	1,400,000 hours
	MIL-HDBK-217F	580,000 hours min.
	@ 40 °C, 100% load	

Protection		
Short-circuit:		Continuous, automatic recovery
Overvoltage:		Non-latching
Undervoltage:		Non-latching
Thermal:		110 °C baseplate, automatic recovery

Telecom Specifications		
Central office interface A:		ETS300-132-2

## Environmental Specifications


Thermal performance:	Operating case temp.	-40 °C to +100 °C
	Non-operating	-55 °C to +125 °C
Altitude:	Operating	10,000 feet max.
	Non-operating	40,000 feet max.
Vibration:	5 - 500 Hz	2.4 G rms (approx.)

## Ordering Information

Output Power (Max.)	Input Voltage	OVP	Output Voltage	Output Current (Min.)	Output Current (Max.)	Efficiency (Typ.)	Regulation		Model Number
							Line	Load	
100 W	18 - 36 Vdc	14.5 Vdc	12 V	0 A	8.33 A	85%	±0.05%	±0.1%	BXB100-24S12FLTJ
100 W	36 - 75 Vdc	6.5 Vdc	5 V	0 A	20 A	83%	±0.05%	±0.1%	BXB100-48S05FLTJ
100 W	36 - 75 Vdc	14.5 Vdc	12 V	0 A	8.33 A	86%	±0.05%	±0.1%	BXB100-48S12FLTJ

### External Output Trimming

Output can be externally trimmed by using the method shown.




### Pin Connections

Pin Number	Function
1	+Vin
2	Remote ON/OFF
3	Case
4	-Vin
5	-Vout
6	-Sense
7	Trim
8	+Sense
9	+Vout

### Notes

- 1 Measured with 10  $\mu$ F tantalum capacitor and 1  $\mu$ F ceramic capacitor across output.
- 2  $di/dt = 0.1$  A/1  $\mu$ s,  $V_{in} = 48$  Vdc,  $T_c = 25$  °C, load change = 0.5 lo max. to 0.75 lo max. and 0.75 lo max. to 0.5 lo max.
- 3 Units should be characterised within systems. External components required.
- 4 Input fusing is recommended based on surge current and maximum input current.
- 5 This product is only for inclusion by professional installers within other equipment and must not be operated as a stand alone product.
- 6 Simulated source impedance of 12  $\mu$ H. 12  $\mu$ H inductor in series with +Vin.
- 7 Active high remote on/off option is available (standard product is active low), designate with the suffix 'FHT' e.g. **BXB100-48S05FHTJ**. Consult factory for further details and options.
- 8 Start-up into resistive load.
- 9 "J" suffix designation for RoHS 6/6.

## Mechanical Drawing



ALL DIMENSIONS IN INCHES (mm)  
Tolerance : x.xx 0.02in. (0.51mm)  
x.xxx 0.010in. (0.254mm)

### Americas

5810 Van Allen Way  
Carlsbad, CA 92008  
USA  
Telephone: +1 760 930 4600  
Facsimile: +1 760 930 0698

### Europe (UK)

Waterfront Business Park  
Merry Hill, Dudley  
West Midlands, DY5 1LX  
United Kingdom  
Telephone: +44 (0) 1384 842 211  
Facsimile: +44 (0) 1384 843 355

### Asia (HK)

14/F, Lu Plaza  
2 Wing Yip Street  
Kwun Tong, Kowloon  
Hong Kong  
Telephone: +852 2176 3333  
Facsimile: +852 2176 3888

For global contact, visit:

[www.powerconversion.com](http://www.powerconversion.com)  
[techsupport.embeddedpower@emerson.com](mailto:techsupport.embeddedpower@emerson.com)

While every precaution has been taken to ensure accuracy and completeness in this literature, Emerson Network Power assumes no responsibility, and disclaims all liability for damages resulting from use of this information or for any errors or omissions.

**Emerson Network Power.**  
The global leader in enabling  
business-critical continuity.

- AC Power
- Connectivity
- DC Power
- Embedded Computing
- Embedded Power
- Monitoring
- Outside Plant
- Power Switching & Controls
- Precision Cooling
- Racks & Integrated Cabinets
- Services
- Surge Protection

**EmersonNetworkPower.com**

Emerson Network Power and the Emerson Network Power logo are trademarks and service marks of Emerson Electric Co. ©2008 Emerson Electric Co.