


# Schottky PowerMod

## CPT20035 — CPT20050



Dim.	Inches		Millimeters		Notes
	Min.	Max.	Min.	Max.	
A	---	3.630	---	92.20	
B	0.700	0.800	17.78	20.32	
C	---	0.630	---	16.00	
E	0.120	0.130	3.05	3.30	
F	0.490	0.510	12.45	12.95	
G	1.375	BSC	34.92	BSC	
H	0.010	---	0.25	---	
N	---	---	---	---	1/4-20
Q	0.275	0.290	6.99	7.37	Dia.
R	3.150	BSC	80.01	BSC	
U	0.600	---	15.24	---	
V	0.312	0.340	7.92	8.64	
W	0.180	0.195	4.57	4.95	Dia.

Microsemi Catalog Number	Industry Part Number	Working Reverse Voltage	Peak Reverse Voltage	Repetitive Peak Reverse Voltage
CPT20035*	201CNQ035	35V	35V	
CPT20040*	201CNQ040	40V	40V	
CPT20045*	201CNQ045	45V	45V	
	MBRP20045CT			
CPT20050*		50V	50V	

\*Add Suffix A for Common Anode, D for Doubler

- Schottky Barrier Rectifier
- Guard Ring Protection
- Common Cathode Center Tap
- 200 Amperes/35 to 50 Volts
- 175°C Junction Temperature
- Reverse Energy Tested

### Electrical Characteristics

Average forward current per pkg	I F(AV) 200 Amps	T <sub>C</sub> = 143°C Square wave, R <sub>θJC</sub> = 0.25°C/W
Average forward current per leg	I F(AV) 100 Amps	T <sub>C</sub> = 143°C, Square wave, R <sub>θJC</sub> = 0.5°C/W
Maximum surge current per leg	I FSM 2000 Amps	8.3ms, half sine, T <sub>J</sub> = 175°C
Maximum repetitive reverse current per leg	I R(OV) 2 Amps	f = 1 KHZ, 25°C, 1 usec square wave
Max peak forward voltage per leg	V FM 0.80 Volts	I FM = 200A: T <sub>J</sub> = 25°C*
Max peak forward voltage per leg	V FM 0.60 Volts	I FM = 200A: T <sub>J</sub> = 175°C*
Max peak reverse current per leg	I RM 75mA	V <sub>RRM</sub> , T <sub>J</sub> = 125°C*
Max peak reverse current per leg	I RM 4.0mA	V <sub>RRM</sub> , T <sub>J</sub> = 25°C
Typical junction capacitance per leg	C <sub>J</sub> 4600pF	V <sub>R</sub> = 5.0V, T <sub>J</sub> = 25 °C


\*Pulse test: Pulse width 300 μsec, Duty cycle 2%

### Thermal and Mechanical Characteristics


Storage temp range	T <sub>STG</sub>	-55°C to 175°C
Operation junction temp range	T <sub>J</sub>	-55°C to 175°C
Max thermal resistance per leg	R <sub>θJC</sub>	0.5°C/W Junction to case
Max thermal resistance per pkg	R <sub>θJC</sub>	0.25°C/W Junction to case
Typical thermal resistance (greased)	R <sub>θCS</sub>	0.08°C/W Case to sink
Terminal Torque		35–50 inch pounds
Mounting Base Torque (outside holes)		30–40 inch pounds
Mounting Base Torque (center hole) center bolt must be torqued first		8–10 inch pounds
Weight		2.8 ounces (75 grams) typical

# CPT20035 — CPT20050


**Figure 1**  
Typical Forward Characteristics — Per Leg




**Figure 2**  
Typical Reverse Characteristics — Per Leg



**Figure 3**  
Typical Junction Capacitance — Per Leg



**Figure 4**  
Forward Current Derating — Per Leg



**Figure 5**  
Maximum Forward Power Dissipation — Per Leg

