

TRIPLE DIFFUSED PLANER TYPE HIGH SPEED SWITCHING


■ Features

- High speed switching
- High reliability

■ Applications

- Switching regulators
- Ultrasonic generators
- High frequency inverters
- General purpose power amplifiers

■ Outline Drawings



■ Maximum ratings and characteristics

- Absolute maximum ratings ($T_c=25^\circ\text{C}$ unless otherwise specified)

Item	Symbol	Ratings	Unit
Collector-Base voltage	V_{CB0}	250	V
Collector-Emitter voltage	V_{CE0}	200	V
Collector-Emitter voltage	$V_{CE0(SUS)}$	200	V
Emitter-Base voltage	V_{EB0}	7	V
Collector current	I_C	6	A
Base current	I_B	1.5	A
Collector power dissipation	P_C	40	W
Operating junction temperature	T_j	+150	$^\circ\text{C}$
Storage temperature	T_{stg}	-55 to +150	$^\circ\text{C}$


- Electrical characteristics ($T_c = 25^\circ\text{C}$ unless otherwise specified)

Item	Symbol	Test Conditions	Min.	Typ.	Max.	Units
Collector-Base voltage	V_{CB0}	$I_{CB0} = 0.1\text{mA}$	250			V
Collector-Emitter voltage	V_{CE0}	$I_{CE0} = 10\text{mA}$	200			V
Collector-Emitter voltage	$V_{CE0(SUS)}$	$I_C = 1\text{A}$	200	-		V
Emitter-Base voltage	V_{EB0}	$I_{EB0} = 0.1\text{mA}$	7	-		V
Collector-Base leakage current	I_{CB0}	$V_{CB0} = 250\text{V}$		-	0.1	mA
Emitter-Base leakage current	I_{EB0}	$V_{EB0} = 7\text{V}$		-	0.1	mA
D.C. current gain	h_{FE}	$I_C = 1\text{A}, V_{CE} = 5\text{V}$	20			
Collector-Emitter saturation voltage	$V_{CE(Sat)}$	$I_C = 2\text{A}, I_B = 0.8\text{A}$			0.5	V
Base-Emitter saturation voltage	$V_{BE(Sat)}$				1.2	V
*1	t_{on}	$I_C = 4\text{A}, I_{B1} = 0.4\text{A}$ $I_{B2} = -0.4\text{A}, R_L = 20\ \text{ohm}$ $P_W = 20\ \mu\text{s}$ Duty<2%			1.0	μs
Switching time	t_{stg}				2.0	μs
	t_f				1.0	μs


- Thermal characteristics

Item	Symbol	Test Conditions	Min.	Typ.	Max.	Units
Thermal resistance	$R_{th(j-c)}$	Junction to case			3.0	$^\circ\text{C/W}$


Characteristics




Collector Output Characteristics




DC Current Gain



Base and Collector Saturation Voltage



Safe Operating Area



Switching Time

*1 Switching Time Test Circuit

