

ELECTRICAL CHARACTERISTICS ($T_c = 25^\circ\text{C}$ unless otherwise noted)

Characteristic	Symbol	Min	Max	Unit
----------------	--------	-----	-----	------

OFF CHARACTERISTICS

Collector - Emitter Sustaining Voltage ($I_C = 100 \text{ mA}, I_B = 0$)	MJ10013 MJ10014	$V_{CEO(sus)}$	550 600	V
Collector Cutoff Current ($V_{CE} = \text{Rated } V_{CEV}, R_{BE} = 50 \text{ ohm}, T_C = 100^\circ\text{C}$)		I_{CER}	5.0	mA
Collector Cutoff Current ($V_{CEV} = \text{Rated Value}, V_{BE(OFF)} = 1.5 \text{ V}$) ($V_{CEV} = \text{Rated Value}, V_{BE(OFF)} = 1.5 \text{ V}, T_C = 100^\circ\text{C}$)		I_{CEV}	0.3 5.0	mA
Emitter Cutoff Current ($V_{EB} = 2.0 \text{ V}, I_C = 0$)		I_{EBO}	175	mA

ON CHARACTERISTICS (1)

DC Current Gain ($I_C = 5.0 \text{ A}, V_{CE} = 5.0 \text{ V}$) ($I_C = 10 \text{ A}, V_{CE} = 5.0 \text{ V}$)		hFE	20 10	500 250	
Collector - Emitter Saturation Voltage ($I_C = 10 \text{ A}, I_B = 2.0 \text{ A}$) ($I_C = 10 \text{ A}, I_B = 2.0 \text{ A}, T_C = 100^\circ\text{C}$)		$V_{CE(sat)}$		2.5 2.6	V
Base - Emitter Saturation Voltage ($I_C = 10 \text{ A}, I_B = 2.0 \text{ A}$) ($I_C = 10 \text{ A}, I_B = 2.0 \text{ A}, T_C = 100^\circ\text{C}$)		$V_{BE(sat)}$		3.0 3.0	V
Diode Forward Voltage ($I_F = 10 \text{ A}$)		V_F		5.0	V

DYNAMIC CHARACTERISTICS


Small-Signal Current Gain(2) ($I_C = 1.0 \text{ A}, V_{CE} = 10 \text{ V}, f = 1.0 \text{ MHz}$)		$ h_{fe} $	10		
Output Capacitance ($V_{CB} = 10 \text{ V}, I_E = 0, f = 100 \text{ kHz}$)		C_{ob}	100		pF

SWITCHING CHARACTERISTICS


Delay Time	$V_{CC} = 250 \text{ V}, I_C = 10 \text{ A}$ $I_{B1} = 400 \text{ mA}, V_{BE(off)} = 5.0 \text{ V}$ $t_p = 50 \mu\text{s}, \text{Duty Cycle} \leq 2\%$	t_d	0.2	us
Rise Time		t_r	2.0	us
Storage Time		t_s	4.0	us
Fall Time		t_f	1.0	us

(1) Pulse Test: Pulse width = 300 us , Duty Cycle $\leq 2.0\%$ (2) $f_T = |h_{fe}| \cdot f_{test}$


DC CURRENT GAIN




COLLECTOR SATURATION REGION




COLLECTOR EMITTER SATURATION VOLTAGE




BASE EMITTER VOLTAGE




COLLECTOR CUT-OFF REGION




OUTPUT CAPACITANCES




TURN-ON TIME



TURN-OFF TIME



ACTIVE REGION SAFE OPERATING AREA



REVERSE BIAS SWITCHING SAFE OPERATING AREA

