



(TABLE 1)

TYPE	PART NO.	WIRE SIZE(mm)	Insulation DIA(mm)	Applicable WIRE(Reference)	FINISH
MTII	0-962875-1	0.2-0.5	1.2-1.6	AVSSXF 0.5 Max	CuSn4
	0-962875-3	0.5-1.0	1.4-2.1	AVSSXF 0.85 Max	CuSn4(GOLD)
	0-962876-1	0.5-1.0	1.4-2.1	AVSSXF 0.85 Max	CuSn4
JPT	0-927770-3	0.5-1.0	1.4-2.1	FLK 1.0 Max	CuSn4
	0-927766-3	1.0-2.5	2.2-3.0	AVSS 2.0 Max or FLR 2.5 Max	CuSn4(GOLD)
	2-927766-1	1.0-2.5	2.2-3.0	AVSS 2.0 Max or FLR 2.5 Max	CuSn4



ISOMETRIC VIEW

(TABLE 2)

TYPE	PART NO.	WIRE INSULATION DIAMETER(mm)	COLOR
MTII	964971-1	1.2-1.6	RED
	963530-1	1.4-1.9	GRAY
	964972-1	1.9-2.1	YELLOW
JPT	963531-1	CAVITY PLUG	WHITE
	828904-2	1.2-2.1	BLUE
	828905-1	2.2-3.0	WHITE
	828922-1	CAVITY PLUG	NATURAL

- NOTE
 1. GENERAL TOLERANCE: ±0.3, ±3*
 2. DELIVERY CONDITION
 3. APPLIED CAP P/NX-189703-X
 4. APPLIED WIRE COVER P/NX-1897014-X
 5. APPLICABLE RECEPTACLE CONTACT P/N/TABLE 1
 6. APPLICABLE WIRE SEAL P/N/TABLE 2

NO	REV	DATE	DESCRIPTION	QTY
1			INNER SEAL	1
2			LEVER	1
3			MAIN PLUG	1
4			FRONT PLUG	1
5				

DIMENSIONS: MM		TOLERANCES UNLESS OTHERWISE SPECIFIED		DRAWING NO. 1897009-2	
0.15	0.25	0.15	0.25	DATE	REV
0.5	0.75	0.5	0.75	PRODUCT SPEC	
1.0	1.5	1.0	1.5	APPLICATION SPEC	
2.0	3.0	2.0	3.0	WEIGHT	
3.0	4.5	3.0	4.5	CUSTOMER DRAWING	
4.0	6.0	4.0	6.0	SCALE	2:1
5.0	7.5	5.0	7.5	SHEET	1 OF 1
6.0	9.0	6.0	9.0	REV	A

AMP KOREA
 Electronics
 PLUG ASSY FOR MTII/JPT SEALED 26P CONVR
 1897009