THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION -.-.-
© COPYRIGHT - BY TYCO ELECTRONICS CORPORATION. ALL RIGHTS RESERVED.

LOC	DIST
DF	DO

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
-	L	REV PER ECO 05-014965	4-10-06	CT	DM







1. THIS PLUG WILL MATE WITH ANY 15 POSN.,SIZE 2 RECEPTACLE IN AMPLIMITE SERIES.
2. MAXIMUM WIRE INSULATION TO BE USED WITH THIS PLUG IS Ø.068 [1.73]
3. SST RETENTION CLIPS ARE INCLUDED IN INSERTS.
4. THIS PLUG IS DESIGNED TO CONFORM TO THE LATEST ISSUE OF MIL-C-24308.
5. 445006-1, -2 & 5--1 ARE SUPPLIED WITHOUT CONTACTS, 445006-3 & -4 SUPPLIED WITH CONTACTS.
6. THIS PLUG WILL ACCEPT SIZE 20 DM PIN CONTACT M39029/64-369 OR ANY AMP SIZE 20 DF PIN CONTACT.

7. FINISH: PLATED CADMIUM PER QQ-P-416, YELLOW CHROMATE.
8. FINISH: TIN PLATED PER MIL-T-10727.
9. FINISH: ZINC PLATED PER ASTM-B-633 .000200 MIN THK WITH SUPPLEMENTARY CHROMATE (Cr3+).

CONTACT FINISH	DIM A REF	REAR SHELL PLATING	FRONT SHELL PLATING	PART NUMBER
NO CONTACTS	–	9	9	5-445006-1
GOLD PER ASTM-B-488 OVER NICKEL PER QQ-N-290	.030 [0.76]	7	8	445006-4
GOLD PER ASTM-B-488 OVER COPPER PER AMS2410	.018 [0.46]	7	7	445006-3
NO CONTACTS	–	7	8	445006-2
NO CONTACTS	–	7	7	445006-1

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS: INCHES

TOLERANCES UNLESS OTHERWISE SPECIFIED:
X ±.02
.XX ±.01
.XXX ±.005
ANGLES ±2°
.005 [0.13] ±.002 [0.05]

MATERIAL –
FINISH –

DRN	C.C.THOMAS	9/19/06
CHK	J.NORTON	9-19-06
APVD	J.NORTON	9-19-06
PRODUCT SPEC	–	
APPLICATION SPEC	–	
WEIGHT	–	

CUSTOMER DRAWING

Tyco Electronics Corporation
Harrisburg, PA 17105-3608

TITLE: PLUG ASSY,AMPLIMITE,15 POSN.
SIZE 2,SERIES 109,BLINDMATE

SIZE	CAGE CODE	DRAWING NO	RESTRICTED TO
A1	00779	C-445006	–

SCALE 4:1 SHEET 1 OF 1 REV L

Downloaded from Elcodis.com electronic components distributor