



1. THE CONNECTOR DESCRIBED IN THIS DOCUMENT WILL MATE WITH ANY RECEPTACLE CONNECTOR WITH THE SAME INSERT ARRANGEMENT.
- MARKED WITH 047-062 (119-157) HIGH CHARACTERS, FAR SIDE REFERS TO THE WIDE SIDE OF THE KEYSTONE, NEAR SIDE REFERS TO THE NARROW SIDE OF THE KEYSTONE, WHEN SPACE IS LIMITED MARKING CAN BE SPLIT BETWEEN FRONT AND REAR SHELL.
- UL/CSA DESIGNATION STAMPED IN THIS AREA.
- CONNECTOR ASSEMBLY WITHOUT CONTACTS, TE P/N 205089-1, MUST BE ORDERED SEPARATELY.
- CONNECTOR ASSEMBLY SUPPLIED WITH CONTACTS, TE P/N 205089-1, PACKAGED IN A SEPARATE CONTAINER, QTY = NO. OF POSN. (SEE TABLE).

| REMARKS | MILITARY P/N ON PACKAGE | MILITARY P/N ON CONNECTOR | MARKED TE PART NUMBER | L | J | H | G | F | E | D | C | B | A | INSERT ARRANGEMENT | ND OF POS | SHELL SIZE | PART NUMBER |
|---------|-------------------------|---------------------------|-----------------------|-------------|--------------|---------------|-------------|--------------|--------------|--------------|---------------|---------------|---------------|--------------------|-----------|------------|-------------|
| | M24308/4-306 | M24308/4-306 | 1-1757821-0 | .049 (1.24) | .544 (13.82) | 2.188 (55.58) | .236 (5.99) | .436 (11.07) | .620 (15.75) | .446 (11.33) | 2.411 (61.24) | 2.084 (52.93) | 2.650 (67.31) | MS1827-1 | 50 | 5 | 1-1757821-0 |
| | M24308/4-305 | M24308/4-305 | 1757821-9 | .049 (1.24) | .544 (13.82) | 2.188 (55.58) | .236 (5.99) | .436 (11.07) | .620 (15.75) | .446 (11.33) | 2.411 (61.24) | 2.084 (52.93) | 2.650 (67.31) | MS1827-1 | 37 | 4 | 1757821-9 |
| | M24308/4-304 | M24308/4-304 | 1757821-8 | .049 (1.24) | .544 (13.82) | 2.188 (55.58) | .236 (5.99) | .436 (11.07) | .620 (15.75) | .446 (11.33) | 2.411 (61.24) | 2.084 (52.93) | 2.650 (67.31) | MS1827-1 | 25 | 3 | 1757821-8 |
| | M24308/4-303 | M24308/4-303 | 1757821-7 | .049 (1.24) | .544 (13.82) | 2.188 (55.58) | .236 (5.99) | .436 (11.07) | .620 (15.75) | .446 (11.33) | 2.411 (61.24) | 2.084 (52.93) | 2.650 (67.31) | MS1827-1 | 15 | 2 | 1757821-7 |
| | M24308/4-302 | M24308/4-302 | 1757821-6 | .049 (1.24) | .544 (13.82) | 2.188 (55.58) | .236 (5.99) | .436 (11.07) | .620 (15.75) | .446 (11.33) | 2.411 (61.24) | 2.084 (52.93) | 2.650 (67.31) | MS1827-1 | 9 | 1 | 1757821-6 |
| | M24308/4-328 | M24308/4-306 | 1-1757821-0 | .049 (1.24) | .544 (13.82) | 2.188 (55.58) | .236 (5.99) | .436 (11.07) | .620 (15.75) | .446 (11.33) | 2.411 (61.24) | 2.084 (52.93) | 2.650 (67.31) | MS1827-1 | 50 | 5 | 1757821-0 |
| | M24308/4-327 | M24308/4-305 | 1757821-9 | .049 (1.24) | .544 (13.82) | 2.188 (55.58) | .236 (5.99) | .436 (11.07) | .620 (15.75) | .446 (11.33) | 2.411 (61.24) | 2.084 (52.93) | 2.650 (67.31) | MS1827-1 | 37 | 4 | 1757821-9 |
| | M24308/4-326 | M24308/4-304 | 1757821-8 | .049 (1.24) | .544 (13.82) | 2.188 (55.58) | .236 (5.99) | .436 (11.07) | .620 (15.75) | .446 (11.33) | 2.411 (61.24) | 2.084 (52.93) | 2.650 (67.31) | MS1827-1 | 25 | 3 | 1757821-8 |
| | M24308/4-325 | M24308/4-303 | 1757821-7 | .049 (1.24) | .544 (13.82) | 2.188 (55.58) | .236 (5.99) | .436 (11.07) | .620 (15.75) | .446 (11.33) | 2.411 (61.24) | 2.084 (52.93) | 2.650 (67.31) | MS1827-1 | 15 | 2 | 1757821-7 |
| | M24308/4-324 | M24308/4-302 | 1757821-6 | .049 (1.24) | .544 (13.82) | 2.188 (55.58) | .236 (5.99) | .436 (11.07) | .620 (15.75) | .446 (11.33) | 2.411 (61.24) | 2.084 (52.93) | 2.650 (67.31) | MS1827-1 | 9 | 1 | 1757821-6 |

THIS DRAWING IS A CONTROLLED DOCUMENT. IT IS THE PROPERTY OF TTI ELECTRONICS CORPORATION. IT IS TO BE KEPT IN CONFIDENCE AND NOT TO BE REPRODUCED OR TRANSMITTED IN ANY FORM OR BY ANY MEANS, ELECTRONIC OR MECHANICAL, INCLUDING PHOTOCOPYING, RECORDING, OR BY ANY INFORMATION STORAGE AND RETRIEVAL SYSTEM.

DATE: 01/07/79
 DRAWING NO: 1757821
 CUSTOMER DRAWING