



- THIS RCPT. IS DESIGNED TO CONFORM TO THE LATEST ISSUE OF MIL-C-24308
 - MAX WIRE INSUL. TO BE USED WITH THIS RCPT IS .068 DIA
 - STAINLESS STEEL RETENTION CLIPS ARE INCLUDED IN INSERTS
 - PACKAGE STAMPED M24308/2-293F
 - THIS RCPT. WILL ACCEPT SIZE 20 SOCKET CONTACT M24308/10 OR AMP # 205090
- AMP PART NO. STAMPED ON CONNECTOR REPRESENTS KIT NUMBER WITH CONTACTS
 UL/CSA DESIGNATION STAMPED IN THIS AREA.

OBSOLETE	BRASS	205417-2
	STEEL PER ASTM-A-109	205417-1
	SHELL MAT'L	PART NO

DO NOT SCALE PRINT DIMENSIONS SPECIFIED DIMENSIONS IN FIGURES DIMENSIONS ON SCALE SEE 4 SCALE SEE 4 DIMENSIONS MATERIAL	BY 12-9-87 C.C. THOMAS CHK 12-10-87 PC BALLEW III APP'D 12-10-87 SJM PRODUCT SPEC APPLICATION SPEC WEIGHT	AMP INCORPORATED AMPLINITE RCPT. FOR SOCKET CONTACTS HI-DENSITY "HOM-20" CONNECTOR SIZE 2 (15 POSN) SERIES 109 WITH FLOAT BUSHINGS SIZE: FCN NO. 00779 DRAWING NO. 205417 SHEET 1 OF 1
--	---	---

CUSTOMER DRAWING