



1. THIS RECEPTACLE WILL MATE WITH ANY 25 POSN., SIZE 3 PLUG IN AMPLIMITE SERIES.
 2. MAXIMUM WIRE INSULATION TO BE USED WITH THIS RECEPTACLE IS .058 DIA.
 3. SST RETENTION CLIPS ARE INCLUDED IN INSERTS.
- ⚠ PACKAGE STAMPED M2430B/2-484 & AMP P/N 211527-1
 - ⚠ PACKAGE STAMPED M2430B/2-344 & AMP P/N 211527-2
 - ⚠ PACKAGE STAMPED M2430B/2-355 & AMP P/N 211527-3
 - ⚠ AMP P/N 205090-1; MIL P/N 63-35B, INCLUDED IN KIT.
 - ⚠ AMP P/N 91067-2; MIL P/N HB1969/1-02.
 - ⚠ CONNECTOR SUPPLIED WITHOUT CONTACTS; SHOWN FOR ILLUSTRATION ONLY.
 - ⚠ UL/CSA DESIGNATION STAMPED IN THIS AREA.

DO NOT SCALE PRINT.		OR 5-18-55	AMP INCORPORATED New York, N.Y. 10008
UNLESS SPECIFIED		D 5-18-55	
DIMENSIONS IN INCHES		DR 4-18-55	RECEPTACLE ASS'Y., AMPLIMITE 25 POSN., SIZE 3, SERIES 109, W/DUAL FLOAT BUSHINGS
UNLESS SPECIFIED		R. 04/25/55	
2 PLG DEC *		APPO 9-25-55	SIZE D 00773
3 PLG DEC *		L. 04/25/55	
ANGLES ± 9°30'		8. 04/25/55	DRAWING NO 211527
MATERIAL		6. 04/25/55	
FINISH		PRODUCT SPEC	SHEET 1 OF 1
SEE CALLOUT		APPLICATION SPEC	
SEE CALLOUT		WEIGHT	SCALE NTS

CUSTOMER DRAWING