



1. CONNECTOR MEETS ALL APPLICABLE REQUIREMENTS OF MIL-C-55302.
- AMP, AMP PART NO. & DATE CODE MARKED IN THIS APPROXIMATE AREA.
- NUMBERS INDICATING END POSITIONS MARKED THIS SIDE ONLY.
- MINIMUM PAD LENGTH ON CIRCUIT BOARD.
- CONTACT FINISH, .000050 (0.0013) GOLD IN CONTACT AREA, TIN-LEAD ON CONTACT TAILS; ALL OVER NICKEL UNDERPLATE.
- HOUSING MATERIAL: LIQUID CRYSTAL POLYMER PER MIL-M-24519, GLCP-30F; COLOR: GRAY
- PIN TO BE FLUSH TO .010 RECESS. THIS SURFACE: -2 ONLY
- JACKSCREW AND SPIRAL PIN USED ON -2 ONLY.

1 & 80	2.400 [60.36]	1.790 [45.47]	1.950 [49.53]	39	2.325 [58.46]	4.650 [118.11]	4.190 [106.43]	4.890 [124.21]	5.050 [128.27]	160	447439-2
1 & 80	2.400 [60.36]	1.790 [45.47]	1.950 [49.53]	39	2.325 [58.46]	4.650 [118.11]	4.190 [106.43]	4.890 [124.21]	5.050 [128.27]	160	447439-1
CAVITY IDENT.	I	H	S	F	E	D	C	B	A	POSN.	PART NUMBER

AMP Incorporated
 Harrisburg, PA 17105-3608

AMP

PIN HEADER ASSEMBLY,
 EXTENDED MINI-80X,
 160 POSN. CARD EXTENDER

AMP Part No. 447439
 DATE 3-94