


- TRUE POSITION TOLERANCE OF THE POST TIPS APPLIES WHEN THE HEADERS ARE HELD FLAT AGAINST THE PRINTED CIRCUIT BOARD
 - ASSEMBLY MAY BE BROKEN TO THE DESIRED NUMBER OF POSITIONS
- ▲ .000100-.000200 MATTE TIN-LEAD OVER .000050 NICKEL.
 - ▲ .000100-.000200 BRIGHT TIN OVER .000050 NICKEL.
 - ▲ PRELIMINARY PART - NOT RELEASED FOR PRODUCTION.
 - ▲ HOUSING MATERIAL: FLAME RETARDANT THERMOPLASTIC; COLOR-BLACK.
 - ▲ OBSOLETE PARTS: OBSOLETE CIS STREAMLINING PER D.RENAUD/D.SINISI



PLATING	C	B	A	NO OF POSN	PART NUMBER
▲	▲	▲	▲	16 34	4-103328-9
▲	▲	▲	▲	12 26	4-103328-8
▲	▲	▲	▲	8 18	4-103328-7
▲	▲	▲	▲	5 12	4-103328-6
▲	▲	▲	▲	39 80	4-103328-5
▲	▲	▲	▲	9 20	4-103328-4
▲	▲	▲	▲	6 14	4-103328-3
▲	▲	▲	▲	2 6	4-103328-2
▲	▲	▲	▲	2	4-103328-1
▲	▲	▲	▲	39 80	4-103328-0
▲	▲	▲	▲	38 78	3-103328-9
▲	▲	▲	▲	37 76	3-103328-8
▲	▲	▲	▲	36 74	3-103328-7
▲	▲	▲	▲	35 72	3-103328-6
▲	▲	▲	▲	34 70	3-103328-5
▲	▲	▲	▲	33 68	3-103328-4
▲	▲	▲	▲	32 66	3-103328-3
▲	▲	▲	▲	31 64	3-103328-2
▲	▲	▲	▲	30 62	3-103328-1
▲	▲	▲	▲	29 60	3-103328-0
▲	▲	▲	▲	28 58	2-103328-9
▲	▲	▲	▲	27 56	2-103328-8
▲	▲	▲	▲	26 54	2-103328-7
▲	▲	▲	▲	25 52	2-103328-6
▲	▲	▲	▲	24 50	2-103328-5
▲	▲	▲	▲	23 48	2-103328-4
▲	▲	▲	▲	22 46	2-103328-3
▲	▲	▲	▲	21 44	2-103328-2
▲	▲	▲	▲	20 42	2-103328-1
▲	▲	▲	▲	19 40	2-103328-0
▲	▲	▲	▲	17 36	1-103328-8
▲	▲	▲	▲	16 34	1-103328-7
▲	▲	▲	▲	15 32	1-103328-6
▲	▲	▲	▲	14 30	1-103328-5
▲	▲	▲	▲	13 28	1-103328-4
▲	▲	▲	▲	12 26	1-103328-3
▲	▲	▲	▲	11 24	1-103328-2
▲	▲	▲	▲	10 22	1-103328-1
▲	▲	▲	▲	9 20	1-103328-0
▲	▲	▲	▲	8 18	103328-9
▲	▲	▲	▲	7 16	103328-8
▲	▲	▲	▲	6 14	103328-7
▲	▲	▲	▲	5 12	103328-6
▲	▲	▲	▲	4 10	103328-5
▲	▲	▲	▲	3 8	103328-4
▲	▲	▲	▲	2 6	103328-3
▲	▲	▲	▲	1 4	103328-2
▲	▲	▲	▲	2	103328-1

▲ SUPERSEDED BY 6-146254-1

THIS DRAWING IS A CONTROLLED DOCUMENT. DATE: 10/19/93 BY: J.MATTELLI

TE Connectivity

ASSEMBLY, HEADER, BREAKAWAY, MOD II, DOUBLE ROW, 100 X 100 C/L, VERTICAL, WITH .025 SQUARE POSTS

SIZE: 100779 (G=103328)

CUSTOMER DRAWING