THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION -.-.-
© COPYRIGHT - By - ALL RIGHTS RESERVED

REVISIONS						
LOC	DIST	P	LTR	DESCRIPTION	DATE	DWN	APVD
AD	00		S4	REVISED PER ECO-11-004587	11MAR11	RK	HMR



12 OBSOLETE		1, 4	1, 4	16.71 [.658]	3	8	7-534204-2 10
12 OBSOLETE		1,3	1,3	14.17 [.558]	2	6	7-534204-1 10
12 OBSOLETE		1, 2, 50, 51, 99, 100	1, 2, 50, 51, 99, 100	260.55 [10.258]	99	200	7-534204-0 10
12 OBSOLETE		1, 2, 40, 41, 79, 80	1, 2, 40, 41, 79, 80	209.75 [8.258]	79	160	6-534204-9 10
12 OBSOLETE		1, 2, 35, 36, 69, 70	1, 2, 35, 36, 69, 70	184.35 [7.258]	69	140	6-534204-8 10
12 OBSOLETE		1, 2, 32, 33, 64, 65	1, 2, 32, 33, 64, 65	171.65 [6.758]	64	130	6-534204-7 10
		1, 2, 27, 28, 54, 55	1, 2, 27, 28, 54, 55	146.25 [5.758]	54	110	6-534204-6 10
12 OBSOLETE		1, 2, 47, 48	1, 2, 47, 48	128.47 [5.058]	47	96	6-534204-5 10
		1, 2, 35, 36	1, 2, 35, 36	97.99 [3.858]	35	72	6-534204-4 10
		1, 2, 34, 35	1, 2, 34, 35	95.45 [3.758]	34	70	6-534204-3 10
	9	1, 2, 19, 20	1, 2, 19, 20	57.35 [2.258]	19	40	6-534204-2 10
		1, 2, 11, 12	1, 2, 11, 12	37.03 [1.458]	11	24	6-534204-1 10
12 OBSOLETE		1, 2, 7, 8	1, 2, 7, 8	26.87 [1.058]	7	16	6-534204-0 10
		1, 2, 9, 10	1, 2, 9, 10	31.95 [1.258]	9	20	5-534204-9 10
		1, 2, 39, 40	1, 2, 39, 40	108.15 [4.258]	39	80	5-534204-8 10
12 OBSOLETE		1, 2, 30, 31, 59, 60	1, 2, 30, 31, 59, 60	158.95 [6.258]	59	120	5-534204-7 10
12 OBSOLETE		1, 2, 25, 26, 49, 50	1, 2, 25, 26, 49, 50	133.55 [5.258]	49	100	5-534204-6 10
		1, 2, 29, 30	1, 2, 29, 30	82.75 [3.258]	29	60	5-534204-5 10
		1, 2, 14, 15	1, 2, 14, 15	44.65 [1.758]	14	30	5-534204-4 10
		1, 2, 17, 18	1, 2, 17, 18	52.27 [2.058]	17	36	5-534204-3 10
		1, 2, 5, 6	1, 2, 5, 6	21.79 [.858]	5	12	5-534204-2 10
		1, 2, 24, 25	1, 2, 24, 25	70.05 [2.758]	24	50	5-534204-1 10
	8	1, 4	1, 4	16.71 [.658]	3	8	2-534204-2
	8	1,3	1,3	14.17 [.558]	2	6	2-534204-1
12 OBSOLETE		1, 2, 50, 51, 99, 100	1, 2, 50, 51, 99, 100	260.55 [10.258]	99	200	2-534204-0
OBSOLETE		1, 2, 40, 41, 79, 80	1, 2, 40, 41, 79, 80	209.75 [8.258]	79	160	1-534204-9
OBSOLETE		1, 2, 35, 36, 69, 70	1, 2, 35, 36, 69, 70	184.35 [7.258]	69	140	1-534204-8
12 OBSOLETE		1, 2, 32, 33, 64, 65	1, 2, 32, 33, 64, 65	171.65 [6.758]	64	130	1-534204-7
		1, 2, 27, 28, 54, 55	1, 2, 27, 28, 54, 55	146.25 [5.758]	54	110	1-534204-6
12 OBSOLETE		1, 2, 47, 48	1, 2, 47, 48	128.47 [5.058]	47	96	1-534204-5
		1, 2, 35, 36	1, 2, 35, 36	97.99 [3.858]	35	72	1-534204-4
		1, 2, 34, 35	1, 2, 34, 35	95.45 [3.758]	34	70	1-534204-3
		1, 2, 19, 20	1, 2, 19, 20	57.35 [2.258]	19	40	1-534204-2
		1, 2, 11, 12	1, 2, 11, 12	37.03 [1.458]	11	24	1-534204-1
	4	1, 2, 7, 8	1, 2, 7, 8	26.87 [1.058]	7	16	1-534204-0
		1, 2, 9, 10	1, 2, 9, 10	31.95 [1.258]	9	20	534204-9
		1, 2, 39, 40	1, 2, 39, 40	108.15 [4.258]	39	80	534204-8
12 OBSOLETE		1, 2, 30, 31, 59, 60	1, 2, 30, 31, 59, 60	158.95 [6.258]	59	120	534204-7
12 OBSOLETE		1, 2, 25, 26, 49, 50	1, 2, 25, 26, 49, 50	133.55 [5.258]	49	100	534204-6
		1, 2, 29, 30	1, 2, 29, 30	82.75 [3.258]	29	60	534204-5
		1, 2, 14, 15	1, 2, 14, 15	44.65 [1.758]	14	30	534204-4
		1, 2, 17, 18	1, 2, 17, 18	52.27 [2.058]	17	36	534204-3
		1, 2, 5, 6	1, 2, 5, 6	21.79 [.858]	5	12	534204-2
		1, 2, 24, 25	1, 2, 24, 25	70.05 [2.758]	24	50	534204-1
FINISH		ROW M	ROW N	B	A	NO OF POSN	PART NUMBER
		POSITION WITH BOARD RETENTION					

1. "AMP", "CSA", "▼" AND "DATE CODE" WITH .062 ±015 HIGH CHARACTERS WHERE SIZE PERMITS.
2. HOUSING: 1–70 POSITION SIZES MAY BE PPS, GLASS–FILLED OR PCT, GLASS–FILLED, POSITION SIZES GREATER THAN 70 WILL BE PPS, GLASS–FILLED.
3. CONTACT: PHOSPHOR BRONZE.
4. CONTACT FINISH: DUPLEX PLATED 0.00076 [.000030] GOLD IN CONTACT AREA, 0.00127–0.00254 [.000050–.000100] BRIGHT TIN–LEAD ON SOLDER TAILS, ALL OVER 0.00127 [.000050] NICKEL.
5. THESE DIMENSIONS PERTAIN TO CAVITY ℄'S ONLY, NOT TO CONTACT LOCATIONS.
6. POINT OF MEASUREMENT FOR PLATING THICKNESS (INSIDE CONTACT BEAMS).
7. CSA LOGO INK STAMPED WHITE ON HOUSING.

A. PRELIMINARY PART – NOT RELEASED FOR PRODUCTION
9. CONTACT FINISH: DUPLEX PLATED 0.00076 [.000030] GOLD IN CONTACT AREA, 0.00127–0.00254 [.000050–.000100] MATTE TIN ON SOLDER TAILS, ALL OVER 0.00127 [.000050] NICKEL.
10. ROHS 2002/95/EC COMPLIANT.
11. RECESSED AREA AROUND MOLD GATE IS OPTIONAL. THIS FEATURE IS ALLOWABLE ON EITHER SIDE OF HOUSING OR MAY NOT BE PRESENT AT ALL.
12. OBSOLETE PARTS: OBSOLETE CIS STREAMLINING PER D.RENAUD/D.SINISI

THIS DRAWING IS A CONTROLLED DOCUMENT.
ORIG: HOFFMAN 4/28/98
CHK: A. CABANY 5/7/98
APVD: –
PRODUCT SPEC: –
APPLICATION SPEC: –
WEIGHT: –
CUSTOMER DRAWING

DIMENSIONS: mm [INCHES]
TOLERANCES UNLESS OTHERWISE SPECIFIED: 0 PLC ± –, 1 PLC ± .X ± 0.13 [.005], 2 PLC ± .XX ± –, 3 PLC ± .XXX ± –, ANGLES ± –
MATERIAL 2 3
FINISH SEE TABLE

TE Connectivity

RECEPTACLE ASSY, MOD II, DBL ROW, 2.54 X 2.54 [.100 X .100] CL, GUIDE PIN EARS, CLOSED ENTRY,

SIZE A1 | CAGE CODE 00779 | DRAWING NO C-534204 | RESTRICTED TO –
SCALE 6:1 | SHEET 1 OF 1 | REV S4

4805 (3/11)

Downloaded from Elcodis.com electronic components distributor