



- ▲ HOUSING: FLAME RETARDANT THERMOPLASTIC; COLOR: BLACK.
- ▲ POST: COPPER ALLOY.
- ▲ POST FINISH: 0.00076 [0.00030] GOLD IN AREA G, 0.00254-0.00508 [0.00100-0.00200] BRIGHT TIN-LEAD IN AREA H, ALL OVER 0.00127 [0.00050] NICKEL.
- ▲ POINT OF MEASUREMENT FOR PLATING THICKNESS.
- ▲ RECESSED DATE CODE.
- 6. CSA LOGO HOT STAMPED WHITE ON HOUSING.
- ▲ BOARD RETENTION WHERE INDICATED.
- ▲ PRELIMINARY PART - NOT RELEASED FOR PRODUCTION
- ▲ POST FINISH: 0.00076 [0.00030] GOLD IN AREA G, 0.00254-0.00508 [0.00100-0.00200] MATTE TIN IN AREA H, ALL OVER 0.00127 [0.00050] NICKEL.
- ▲ ROHS 2002/95/EC COMPLIANT
- ▲ OBSOLETE PARTS: OBSOLETE CIS STREAMLINING PER D.RENAUD/D.SINISI

REV	DATE	DESCRIPTION	BY	CHK	APP			
1	1, 4	19.81 [0.780] 17.02 [0.670] 17.78 [0.700]						
1,3	1,3	17.27 [0.680] 14.48 [0.570] 16.24 [0.600]						
2,22,43,64	2,22,43,64	174.75 [6.880] 171.96 [6.770] 172.72 [6.800]		64	130			
2,17,33,39	2,17,33,39	136.65 [5.380] 133.86 [5.270] 134.62 [5.300]		49	100			
2, 24, 47	2, 24, 47	151.57 [5.980] 148.78 [5.900] 149.54 [5.930]		47	96			
2, 3, 4	2, 3, 4	24.89 [0.980] 22.10 [0.870] 22.86 [0.900]		5	12			
2, 18, 34	2, 18, 34	98.55 [3.880] 95.76 [3.770] 96.52 [3.800]		34	70			
2, 23, 47, 69	2, 23, 47, 69	182.05 [7.180] 159.26 [6.270] 160.02 [6.300]		69	140			
2, 20, 40, 59	2, 20, 40, 59	182.05 [7.180] 159.26 [6.270] 160.02 [6.300]		59	120			
2, 18, 37, 54	2, 18, 37, 54	149.35 [5.880] 146.56 [5.770] 147.32 [5.800]		54	110			
2, 20, 39	2, 20, 39	111.25 [4.380] 108.46 [4.270] 109.22 [4.300]		39	80			
2, 18, 35	2, 18, 35	101.09 [3.980] 98.30 [3.870] 99.06 [3.900]		35	72			
2, 15, 29	2, 15, 29	85.85 [3.380] 83.06 [3.270] 83.82 [3.300]		29	60			
8, 13, 18	8, 13, 18	73.15 [2.880] 70.36 [2.770] 71.12 [2.800]		24	50			
5, 10, 15	5, 10, 15	60.45 [2.380] 57.66 [2.270] 58.42 [2.300]		19	40			
4, 9, 14	4, 9, 14	53.37 [2.100] 50.58 [2.000] 51.34 [2.030]		17	36			
3, 8, 13	3, 8, 13	47.75 [1.880] 44.96 [1.770] 45.72 [1.800]		14	30			
5, 6, 7	5, 6, 7	40.13 [1.580] 37.34 [1.470] 38.10 [1.500]		11	24			
4, 5, 6	4, 5, 6	35.05 [1.380] 32.26 [1.270] 33.02 [1.300]		9	20			
3, 4, 5	3, 4, 5	29.97 [1.180] 27.18 [1.070] 27.94 [1.100]		7	16			
2, 33, 67, 99	2, 33, 67, 99	283.85 [10.380] 260.86 [10.270] 261.62 [10.300]		99	200			
1, 4	1, 4	19.81 [0.780] 17.02 [0.670] 17.78 [0.700]		3	8			
1,3	1,3	17.27 [0.680] 14.48 [0.570] 16.24 [0.600]		2	6			
2,22,43,64	2,22,43,64	174.75 [6.880] 171.96 [6.770] 172.72 [6.800]		64	130			
2,17,33,39	2,17,33,39	136.65 [5.380] 133.86 [5.270] 134.62 [5.300]		49	100			
2, 24, 47	2, 24, 47	151.57 [5.980] 148.78 [5.900] 149.54 [5.930]		47	96			
2, 3, 4	2, 3, 4	24.89 [0.980] 22.10 [0.870] 22.86 [0.900]		5	12			
2, 18, 34	2, 18, 34	98.55 [3.880] 95.76 [3.770] 96.52 [3.800]		34	70			
2, 23, 47, 69	2, 23, 47, 69	182.05 [7.180] 159.26 [6.270] 160.02 [6.300]		69	140			
2, 20, 40, 59	2, 20, 40, 59	182.05 [7.180] 159.26 [6.270] 160.02 [6.300]		59	120			
2, 18, 37, 54	2, 18, 37, 54	149.35 [5.880] 146.56 [5.770] 147.32 [5.800]		54	110			
2, 20, 39	2, 20, 39	111.25 [4.380] 108.46 [4.270] 109.22 [4.300]		39	80			
2, 18, 35	2, 18, 35	101.09 [3.980] 98.30 [3.870] 99.06 [3.900]		35	72			
2, 15, 29	2, 15, 29	85.85 [3.380] 83.06 [3.270] 83.82 [3.300]		29	60			
8, 13, 18	8, 13, 18	73.15 [2.880] 70.36 [2.770] 71.12 [2.800]		24	50			
5, 10, 15	5, 10, 15	60.45 [2.380] 57.66 [2.270] 58.42 [2.300]		19	40			
4, 9, 14	4, 9, 14	53.37 [2.100] 50.58 [2.000] 51.34 [2.030]		17	36			
3, 8, 13	3, 8, 13	47.75 [1.880] 44.96 [1.770] 45.72 [1.800]		14	30			
5, 6, 7	5, 6, 7	40.13 [1.580] 37.34 [1.470] 38.10 [1.500]		11	24			
4, 5, 6	4, 5, 6	35.05 [1.380] 32.26 [1.270] 33.02 [1.300]		9	20			
3, 4, 5	3, 4, 5	29.97 [1.180] 27.18 [1.070] 27.94 [1.100]		7	16			
2, 33, 67, 99	2, 33, 67, 99	283.85 [10.380] 260.86 [10.270] 261.62 [10.300]		99	200			
FINISH	ROW M	ROW N	K	J	B	A	NO OF POSN	PART NUMBER

OBSOLETE

THIS DRAWING IS A CONTROLLED DOCUMENT. IN CLOSURE/ALTER/REVISION

TE Connectivity

HEADER ASSY, MOD II, DOUBLE ROW, 2.54 X 2.54 [100 X 100] CL.

0.64 [0.25] SQUARE POST/BOARD RETENTION FEATURE

CUSTOMER DRAWING 100779 534978