



RECOMMENDED HOLE LAYOUT

- ASSEMBLY MAY BE BROKEN TO THE DESIRED NUMBER OF POSITIONS
 - TRUE POSITION TOLERANCE OF THE POST TIPS APPLIES WHEN THE HEADER IS HELD FLAT AGAINST THE PRINTED CIRCUIT BOARD
- △ THE NOTED DIMENSIONS APPLY AT THE INTERSECTION OF THE POST AND HOUSING
 △ HOUSING: FLAME RETARDANT THERMOPLASTIC; COLOR: BLACK.
 △ FINISH: 0.00254-0.00508 [0.000100-.000200] MATTE TIN-LEAD OVER 0.00127 [0.000050] NICKEL ENTIRE POST.
 △ FINISH: 0.00254-0.00508 [0.000100-.000200] MATTE TIN OVER 0.00127 [0.000050] NICKEL ENTIRE POST.

△	101.19	99.08	39	40	9-146456-0
△	3.984	3.900	38	39	8-146456-9
△	98.66	96.52	38	39	8-146456-9
△	3.784	3.700	37	38	8-146456-8
△	95.1	93.96	37	38	8-146456-8
△	93.57	91.44	36	37	8-146456-7
△	3.684	3.600	35	36	8-146456-6
△	91.03	89.88	35	36	8-146456-6
△	3.584	3.500	34	35	8-146456-5
△	88.49	86.36	34	35	8-146456-5
△	3.484	3.400	33	34	8-146456-4
△	85.95	83.82	33	34	8-146456-4
△	3.384	3.300	32	33	8-146456-3
△	83.41	81.28	32	33	8-146456-3
△	3.284	3.200	31	32	8-146456-2
△	80.87	78.74	31	32	8-146456-2
△	3.184	3.100	30	31	8-146456-1
△	78.33	76.20	30	31	8-146456-1
△	3.084	3.000	29	30	8-146456-0
△	75.79	73.66	29	30	8-146456-0
△	2.984	2.900	28	29	7-146456-9
△	73.25	71.12	28	29	7-146456-9
△	2.884	2.800	27	28	7-146456-8
△	70.71	68.58	27	28	7-146456-8
△	2.784	2.700	26	27	7-146456-7
△	68.17	66.04	26	27	7-146456-7
△	2.684	2.600	25	26	7-146456-6
△	65.63	63.50	25	26	7-146456-6
△	2.584	2.500	24	25	7-146456-5
△	63.09	60.96	24	25	7-146456-5
△	2.484	2.400	23	24	7-146456-4
△	60.55	58.42	23	24	7-146456-4
△	2.384	2.300	22	23	7-146456-3
△	58.01	55.88	22	23	7-146456-3
△	2.284	2.200	21	22	7-146456-2
△	55.47	53.34	21	22	7-146456-2
△	2.184	2.100	20	21	7-146456-1
△	52.93	50.80	20	21	7-146456-1
△	2.084	2.000	19	20	7-146456-0
△	50.39	48.26	19	20	7-146456-0
△	1.984	1.900	18	19	6-146456-9
△	47.85	45.72	18	19	6-146456-9
△	1.884	1.800	17	18	6-146456-8
△	45.31	43.18	17	18	6-146456-8
△	1.784	1.700	16	17	6-146456-7
△	42.77	40.64	16	17	6-146456-7
△	1.684	1.600	15	16	6-146456-6
△	40.23	38.10	15	16	6-146456-6
△	1.584	1.500	14	15	6-146456-5
△	37.69	35.56	14	15	6-146456-5
△	1.484	1.400	13	14	6-146456-4
△	35.15	33.02	13	14	6-146456-4
△	1.384	1.300	12	13	6-146456-3
△	32.61	30.48	12	13	6-146456-3
△	1.284	1.200	11	12	6-146456-2
△	30.07	27.94	11	12	6-146456-2
△	1.184	1.100	10	11	6-146456-1
△	27.53	25.40	10	11	6-146456-1
△	1.084	1.000	9	10	6-146456-0
△	24.99	22.86	9	10	6-146456-0
△	[.884	[.800]	8	9	5-146456-9
△	22.45	20.32	8	9	5-146456-9
△	[.784	[.700]	7	8	5-146456-8
△	19.91	17.78	7	8	5-146456-8
△	[.684	[.600]	6	7	5-146456-7
△	17.37	15.24	6	7	5-146456-7
△	[.584	[.500]	5	6	5-146456-6
△	14.83	12.70	5	6	5-146456-6
△	[.484	[.400]	4	5	5-146456-5
△	12.29	10.16	4	5	5-146456-5
△	[.384	[.300]	3	4	5-146456-4
△	9.75	7.62	3	4	5-146456-4
△	[.284	[.200]	2	3	5-146456-3
△	7.21	5.08	2	3	5-146456-3
△	[.184	[.100]	1	2	5-146456-2
△	4.67	2.54	1	2	5-146456-2
△	[.084	-	-	1	5-146456-1
△	2.13	-	-	1	5-146456-1

△	101.19	99.08	39	40	4-146456-0
△	3.984	3.900	38	39	3-146456-9
△	98.66	96.52	38	39	3-146456-9
△	3.784	3.700	37	38	3-146456-8
△	95.1	93.96	37	38	3-146456-8
△	93.57	91.44	36	37	3-146456-7
△	3.684	3.600	35	36	3-146456-6
△	91.03	89.88	35	36	3-146456-6
△	3.584	3.500	34	35	3-146456-5
△	88.49	86.36	34	35	3-146456-5
△	3.484	3.400	33	34	3-146456-4
△	85.95	83.82	33	34	3-146456-4
△	3.384	3.300	32	33	3-146456-3
△	83.41	81.28	32	33	3-146456-3
△	3.284	3.200	31	32	3-146456-2
△	80.87	78.74	31	32	3-146456-2
△	3.184	3.100	30	31	3-146456-1
△	78.33	76.20	30	31	3-146456-1
△	3.084	3.000	29	30	3-146456-0
△	75.79	73.66	29	30	3-146456-0
△	2.984	2.900	28	29	2-146456-9
△	73.25	71.12	28	29	2-146456-9
△	2.884	2.800	27	28	2-146456-8
△	70.71	68.58	27	28	2-146456-8
△	2.784	2.700	26	27	2-146456-7
△	68.17	66.04	26	27	2-146456-7
△	2.684	2.600	25	26	2-146456-6
△	65.63	63.50	25	26	2-146456-6
△	2.584	2.500	24	25	2-146456-5
△	63.09	60.96	24	25	2-146456-5
△	2.484	2.400	23	24	2-146456-4
△	60.55	58.42	23	24	2-146456-4
△	2.384	2.300	22	23	2-146456-3
△	58.01	55.88	22	23	2-146456-3
△	2.284	2.200	21	22	2-146456-2
△	55.47	53.34	21	22	2-146456-2
△	2.184	2.100	20	21	2-146456-1
△	52.93	50.80	20	21	2-146456-1
△	2.084	2.000	19	20	2-146456-0
△	50.39	48.26	19	20	2-146456-0
△	1.984	1.900	18	19	1-146456-9
△	47.85	45.72	18	19	1-146456-9
△	1.884	1.800	17	18	1-146456-8
△	45.31	43.18	17	18	1-146456-8
△	1.784	1.700	16	17	1-146456-7
△	42.77	40.64	16	17	1-146456-7
△	1.684	1.600	15	16	1-146456-6
△	40.23	38.10	15	16	1-146456-6
△	1.584	1.500	14	15	1-146456-5
△	37.69	35.56	14	15	1-146456-5
△	1.484	1.400	13	14	1-146456-4
△	35.15	33.02	13	14	1-146456-4
△	1.384	1.300	12	13	1-146456-3
△	32.61	30.48	12	13	1-146456-3
△	1.284	1.200	11	12	1-146456-2
△	30.07	27.94	11	12	1-146456-2
△	1.184	1.100	10	11	1-146456-1
△	27.53	25.40	10	11	1-146456-1
△	1.084	1.000	9	10	1-146456-0
△	24.99	22.86	9	10	1-146456-0
△	[.884	[.800]	8	9	146456-9
△	22.45	20.32	8	9	146456-9
△	[.784	[.700]	7	8	146456-8
△	19.91	17.78	7	8	146456-8
△	[.684	[.600]	6	7	146456-7
△	17.37	15.24	6	7	146456-7
△	[.584	[.500]	5	6	146456-6
△	14.83	12.70	5	6	146456-6
△	[.484	[.400]	4	5	146456-5
△	12.29	10.16	4	5	146456-5
△	[.384	[.300]	3	4	146456-4
△	9.75	7.62	3	4	146456-4
△	[.284	[.200]	2	3	146456-3
△	7.21	5.08	2	3	146456-3
△	[.184	[.100]	1	2	146456-2
△	4.67	2.54	1	2	146456-2
△	[.084	-	-	1	146456-1
△	2.13	-	-	1	146456-1

THIS DRAWING IS A CONTROLLED DOCUMENT. IT IS THE PROPERTY OF TE Connectivity. UNAUTHORIZED REPRODUCTION IS PROHIBITED.

DIMENSIONS: INCHES (mm INCHES)
 UNLESS OTHERWISE SPECIFIED:
 DIMENSIONS ARE TO BE TAKEN TO THE CENTER OF THE HOLE UNLESS OTHERWISE SPECIFIED.
 DIMENSIONS ARE TO BE TAKEN TO THE CENTER OF THE HOLE UNLESS OTHERWISE SPECIFIED.
 DIMENSIONS ARE TO BE TAKEN TO THE CENTER OF THE HOLE UNLESS OTHERWISE SPECIFIED.

CUSTOMER DRAWING: A100779 (G=146456)
 DATE: 11/11/09
 DRAWING NO.: 146456-9
 SHEET: 4.1 OF 1