



RECOMMENDED HOLE LAYOUT

- ASSEMBLY MAY BE BROKEN TO THE DESIRED NUMBER OF POSITIONS.
- BREAKAWAY NOTCH ANGLE CAN BE ORIENTED TO THE RIGHT (AS SHOWN) OR TO THE LEFT
- .000100-.000200 MATTE TIN-LEAD OVER .000050 NICKEL.
- .000100-.000200 MATTE TIN OVER .000050 NICKEL.
- HIGH TEMPERATURE CONFIGURATION
- OBSOLETE PARTS: OBSOLETE CIS STREAMLINING PER D.RENAUD/D.SINISI

REMARKS	PLATING	C	B	A	NO OF POS	PART NUMBER
△ OBSOLETE		3.984	3.900	39	80	9-103324-0
△ OBSOLETE		3.884	3.800	38	78	8-103324-9
△ OBSOLETE		3.784	3.700	37	76	8-103324-8
△ OBSOLETE		3.684	3.600	36	74	8-103324-7
△ OBSOLETE		3.584	3.500	35	72	8-103324-6
△ OBSOLETE		3.484	3.400	34	70	8-103324-5
△ OBSOLETE		3.384	3.300	33	68	8-103324-4
△ OBSOLETE		3.284	3.200	32	66	8-103324-3
△ OBSOLETE		3.184	3.100	31	64	8-103324-2
△ OBSOLETE		3.084	3.000	30	62	8-103324-1
△ OBSOLETE		2.984	2.900	29	60	8-103324-0
△ OBSOLETE		2.884	2.800	28	58	7-103324-9
△ OBSOLETE		2.784	2.700	27	56	7-103324-8
△ OBSOLETE		2.684	2.600	26	54	7-103324-7
△ OBSOLETE		2.584	2.500	25	52	7-103324-6
△ OBSOLETE		2.484	2.400	24	50	7-103324-5
△ OBSOLETE		2.384	2.300	23	48	7-103324-4
△ OBSOLETE		2.284	2.200	22	46	7-103324-3
△ OBSOLETE		2.184	2.100	21	44	7-103324-2
△ OBSOLETE		2.084	2.000	20	42	7-103324-1
△ OBSOLETE		1.984	1.900	19	40	7-103324-0
△ OBSOLETE		1.884	1.800	18	38	6-103324-9
△ OBSOLETE		1.784	1.700	17	36	6-103324-8
△ OBSOLETE		1.684	1.600	16	34	6-103324-7
△ OBSOLETE		1.584	1.500	15	32	6-103324-6
△ OBSOLETE		1.484	1.400	14	30	6-103324-5
△ OBSOLETE		1.384	1.300	13	28	6-103324-4
△ OBSOLETE		1.284	1.200	12	26	6-103324-3
△ OBSOLETE		1.184	1.100	11	24	6-103324-2
△ OBSOLETE		1.084	1.000	10	22	6-103324-1
△ OBSOLETE		.984	.900	9	20	6-103324-0
△ OBSOLETE		.884	.800	8	18	5-103324-9
△ OBSOLETE		.784	.700	7	16	5-103324-8
△ OBSOLETE		.684	.600	6	14	5-103324-7
△ OBSOLETE		.584	.500	5	12	5-103324-6
△ OBSOLETE		.484	.400	4	10	5-103324-5
△ OBSOLETE		.384	.300	3	8	5-103324-4
△ OBSOLETE		.284	.200	2	6	5-103324-3
△ OBSOLETE		.184	.100	1	4	5-103324-2
△ OBSOLETE		.084	---	---	2	5-103324-1

REMARKS	PLATING	C	B	A	NO OF POS	PART NUMBER
△ OBSOLETE		3.984	3.900	39	80	4-103324-0
△ OBSOLETE		3.884	3.800	38	78	3-103324-9
△ OBSOLETE		3.784	3.700	37	76	3-103324-8
△ OBSOLETE		3.684	3.600	36	74	3-103324-7
△ OBSOLETE		3.584	3.500	35	72	3-103324-6
△ OBSOLETE		3.484	3.400	34	70	3-103324-5
△ OBSOLETE		3.384	3.300	33	68	3-103324-4
△ OBSOLETE		3.284	3.200	32	66	3-103324-3
△ OBSOLETE		3.184	3.100	31	64	3-103324-2
△ OBSOLETE		3.084	3.000	30	62	3-103324-1
△ OBSOLETE		2.984	2.900	29	60	3-103324-0
△ OBSOLETE		2.884	2.800	28	58	2-103324-9
△ OBSOLETE		2.784	2.700	27	56	2-103324-8
△ OBSOLETE		2.684	2.600	26	54	2-103324-7
△ OBSOLETE		2.584	2.500	25	52	2-103324-6
△ OBSOLETE		2.484	2.400	24	50	2-103324-5
△ OBSOLETE		2.384	2.300	23	48	2-103324-4
△ OBSOLETE		2.284	2.200	22	46	2-103324-3
△ OBSOLETE		2.184	2.100	21	44	2-103324-2
△ OBSOLETE		2.084	2.000	20	42	2-103324-1
△ OBSOLETE		1.984	1.900	19	40	2-103324-0
△ OBSOLETE		1.884	1.800	18	38	1-103324-9
△ OBSOLETE		1.784	1.700	17	36	1-103324-8
△ OBSOLETE		1.684	1.600	16	34	1-103324-7
△ OBSOLETE		1.584	1.500	15	32	1-103324-6
△ OBSOLETE		1.484	1.400	14	30	1-103324-5
△ OBSOLETE		1.384	1.300	13	28	1-103324-4
△ OBSOLETE		1.284	1.200	12	26	1-103324-3
△ OBSOLETE		1.184	1.100	11	24	1-103324-2
△ OBSOLETE		1.084	1.000	10	22	1-103324-1
△ OBSOLETE		.984	.900	9	20	1-103324-0
△ OBSOLETE		.884	.800	8	18	103324-9
△ OBSOLETE		.784	.700	7	16	103324-8
△ OBSOLETE		.684	.600	6	14	103324-7
△ OBSOLETE		.584	.500	5	12	103324-6
△ OBSOLETE		.484	.400	4	10	103324-5
△ OBSOLETE		.384	.300	3	8	103324-4
△ OBSOLETE		.284	.200	2	6	103324-3
△ OBSOLETE		.184	.100	1	4	103324-2
△ OBSOLETE		.084	---	---	2	103324-1

THIS DRAWING IS A CONTROLLED DOCUMENT.

TE Connectivity

ASSEMBLY, HEADER, BREAKAWAY, MOD II, DOUBLE ROW, .100 X .100 C/L, RIGHT ANGLE, WITH .025 SQUARE POSTS

SIZE: 100 X 100 C/L, RIGHT ANGLE, WITH .025 SQUARE POSTS

REVISED PER EDD-11-004820

DATE: 11/11/11

BY: AD

CHK: RK

APP: HMR