






REV	DATE	DESCRIPTION	BY	CHK
AD 25				
O		RELEASE FOR EC 0012-0082-05	DMANNS	JDF/AMS

- △ HOUSING MATERIAL: GLASS-FILLED POLYMER.
- △ CONTACT MATERIAL: COPPER ALLOY.
- △ PART NUMBER AND DATE CODE, IN THIS APPROXIMATE AREA, ON REVERSE SIDE.
- △ ACTION PIN POSTS REQUIRE 1.57[.062] MINIMUM THICK PC BOARD, RECOMMENDED PC BOARD DRILLED HOLES ARE 1.15±0.025[.0453±.0010] DIAMETER WITH 0.02-0.08[.001-.003] COPPER AND 0.008[.0003] MINIMUM TIN-LEAD PLATING. FINISHED HOLE AFTER PLATING IS 0.94-1.09[.037-.043] DIAMETER.
- △ CONTACT FINISH: DIN 41612 CLASS 2 IN CONTACT AREA. TIN PLATE ON POSTS.
- △ TAIL LENGTH AFTER SEATING IN PC BOARD.
- △ CONTACT POINT AFTER SEATING IN PC BOARD.
- △ MARKING ON THIS SIDE.



5148057-5
PART NO

THIS DRAWING IS A CONTROLLED DOCUMENT.		REV	EDUCATION	ISSUES	Quantity	Teco Electronics Corporation Harrisburg, PA 17105-3608	
INCHES	FRANCE/LEBLES	OR	SHAPE	ISSUES	DATE	ASSEMBLY, RECEPTACLE, EUROCARD, TYPE C, 96 POSITION, 14.0[.554] PRESS-FIT	
1" = 25.4mm	1" = 25.4mm	OR	SHAPE	ISSUES	DATE	SIZE DATE SIZE DRAWING NO. REWORKED TO	
1" = 25.4mm	1" = 25.4mm	OR	SHAPE	ISSUES	DATE	A1 00779 G=5148057	
1" = 25.4mm	1" = 25.4mm	OR	SHAPE	ISSUES	DATE	CUSTOMER DRAWING	