THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION - -.
© COPYRIGHT - By - ALL RIGHTS RESERVED

LOC	DIST
AD	39

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
	A1	REVISED PER ECO-11-004820	11MAR11	RK	HMR





RECOMMENDED HOLE LAYOUT

1. ASSEMBLY MAY BE BROKEN TO THE DESIRED NUMBER OF POSITIONS
2. TRUE POSITION TOLERANCE OF THE POST TIPS APPLIES WHEN THE HEADER IS HELD FLAT AGAINST THE PRINTED CIRCUIT BOARD

△3 THE NOTED DIMENSIONS APPLY AT THE INTERSECTION OF THE POST AND HOUSING

△4 HOUSING: FLAME RETARDANT THERMOPLASTIC; COLOR: BLACK.

△5 FINISH: 0.000381[.000015] GOLD ON CONTACT AREA, 0.00254–0.00508 [.000100–.000200] MATTE TIN–LEAD ON SOLDER TAIL, ALL OVER 0.00127 [.000050] NICKEL.

△6 FINISH: 0.000381[.000015] GOLD ON CONTACT AREA, 0.00254–0.00508 [.000100–.000200] MATTE TIN ON SOLDER TAIL, ALL OVER 0.00127 [.000050] NICKEL.

	G	F	E	NO. OF POSITIONS	PART NUMBER
△6	101.19 [3.984]	99.06 [3.900]	39	40	9-146481-0
△6	98.65 [3.884]	96.52 [3.800]	38	39	8-146481-9
△6	96.11 [3.784]	93.98 [3.700]	37	38	8-146481-8
△6	93.57 [3.684]	91.44 [3.600]	36	37	8-146481-7
△6	91.03 [3.584]	88.90 [3.500]	35	36	8-146481-6
△6	88.49 [3.484]	86.36 [3.400]	34	35	8-146481-5
△6	85.95 [3.384]	83.82 [3.300]	33	34	8-146481-4
△6	83.41 [3.284]	81.28 [3.200]	32	33	8-146481-3
△6	80.87 [3.184]	78.74 [3.100]	31	32	8-146481-2
△6	78.33 [3.084]	76.20 [3.000]	30	31	8-146481-1
△6	75.79 [2.984]	73.66 [2.900]	29	30	8-146481-0
△6	73.25 [2.884]	71.12 [2.800]	28	29	7-146481-9
△6	70.71 [2.784]	68.58 [2.700]	27	28	7-146481-8
△6	68.17 [2.684]	66.04 [2.600]	26	27	7-146481-7
△6	65.63 [2.584]	63.50 [2.500]	25	26	7-146481-6
△6	63.09 [2.484]	60.96 [2.400]	24	25	7-146481-5
△6	60.55 [2.384]	58.42 [2.300]	23	24	7-146481-4
△6	58.01 [2.284]	55.88 [2.200]	22	23	7-146481-3
△6	55.47 [2.184]	53.34 [2.100]	21	22	7-146481-2
△6	52.93 [2.084]	50.80 [2.000]	20	21	7-146481-1
△6	50.39 [1.984]	48.26 [1.900]	19	20	7-146481-0
△6	47.85 [1.884]	45.72 [1.800]	18	19	6-146481-9
△6	45.31 [1.784]	43.18 [1.700]	17	18	6-146481-8
△6	42.77 [1.684]	40.64 [1.600]	16	17	6-146481-7
△6	40.23 [1.584]	38.10 [1.500]	15	16	6-146481-6
△6	37.69 [1.484]	35.56 [1.400]	14	15	6-146481-5
△6	35.15 [1.384]	33.02 [1.300]	13	14	6-146481-4
△6	32.61 [1.284]	30.48 [1.200]	12	13	6-146481-3
△6	30.07 [1.184]	27.94 [1.100]	11	12	6-146481-2
△6	27.53 [1.084]	25.40 [1.000]	10	11	6-146481-1
△6	24.99 [.984]	22.86 [.900]	9	10	6-146481-0
△6	22.45 [.884]	20.32 [.800]	8	9	5-146481-9
△6	19.91 [.784]	17.78 [.700]	7	8	5-146481-8
△6	17.37 [.684]	15.24 [.600]	6	7	5-146481-7
△6	14.83 [.584]	12.70 [.500]	5	6	5-146481-6
△6	12.29 [.484]	10.16 [.400]	4	5	5-146481-5
△6	9.75 [.384]	7.62 [.300]	3	4	5-146481-4
△6	7.21 [.284]	5.08 [.200]	2	3	5-146481-3
△6	4.67 [.184]	2.54 [.100]	1	2	5-146481-2
△6	2.13 [.084]	– –	–	1	5-146481-1
PLATING	G	F	E	NO. OF POSITIONS	PART NUMBER

	G	F	E	NO. OF POSITIONS	PART NUMBER
△5	101.19 [3.984]	99.06 [3.900]	39	40	4-146481-0
△5	98.65 [3.884]	96.52 [3.800]	38	39	3-146481-9
△5	96.11 [3.784]	93.98 [3.700]	37	38	3-146481-8
△5	93.57 [3.684]	91.44 [3.600]	36	37	3-146481-7
△5	91.03 [3.584]	88.90 [3.500]	35	36	3-146481-6
△5	88.49 [3.484]	86.36 [3.400]	34	35	3-146481-5
△5	85.95 [3.384]	83.82 [3.300]	33	34	3-146481-4
△5	83.41 [3.284]	81.28 [3.200]	32	33	3-146481-3
△5	80.87 [3.184]	78.74 [3.100]	31	32	3-146481-2
△5	78.33 [3.084]	76.20 [3.000]	30	31	3-146481-1
△5	75.79 [2.984]	73.66 [2.900]	29	30	3-146481-0
△5	73.25 [2.884]	71.12 [2.800]	28	29	2-146481-9
△5	70.71 [2.784]	68.58 [2.700]	27	28	2-146481-8
△5	68.17 [2.684]	66.04 [2.600]	26	27	2-146481-7
△5	65.63 [2.584]	63.50 [2.500]	25	26	2-146481-6
△5	63.09 [2.484]	60.96 [2.400]	24	25	2-146481-5
△5	60.55 [2.384]	58.42 [2.300]	23	24	2-146481-4
△5	58.01 [2.284]	55.88 [2.200]	22	23	2-146481-3
△5	55.47 [2.184]	53.34 [2.100]	21	22	2-146481-2
△5	52.93 [2.084]	50.80 [2.000]	20	21	2-146481-1
△5	50.39 [1.984]	48.26 [1.900]	19	20	2-146481-0
△5	47.85 [1.884]	45.72 [1.800]	18	19	1-146481-9
△5	45.31 [1.784]	43.18 [1.700]	17	18	1-146481-8
△5	42.77 [1.684]	40.64 [1.600]	16	17	1-146481-7
△5	40.23 [1.584]	38.10 [1.500]	15	16	1-146481-6
△5	37.69 [1.484]	35.56 [1.400]	14	15	1-146481-5
△5	35.15 [1.384]	33.02 [1.300]	13	14	1-146481-4
△5	32.61 [1.284]	30.48 [1.200]	12	13	1-146481-3
△5	30.07 [1.184]	27.94 [1.100]	11	12	1-146481-2
△5	27.53 [1.084]	25.40 [1.000]	10	11	1-146481-1
△5	24.99 [.984]	22.86 [.900]	9	10	1-146481-0
△5	22.45 [.884]	20.32 [.800]	8	9	146481-9
△5	19.91 [.784]	17.78 [.700]	7	8	146481-8
△5	17.37 [.684]	15.24 [.600]	6	7	146481-7
△5	14.83 [.584]	12.70 [.500]	5	6	146481-6
△5	12.29 [.484]	10.16 [.400]	4	5	146481-5
△5	9.75 [.384]	7.62 [.300]	3	4	146481-4
△5	7.21 [.284]	5.08 [.200]	2	3	146481-3
△5	4.67 [.184]	2.54 [.100]	1	2	146481-2
△5	2.13 [.084]	– –	–	1	146481-1
PLATING	G	F	E	NO. OF POSITIONS	PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.

DRN	C. BRANDBERG	11-MAR-97
CHK	G. DUBNICZKI	11-MAR-97
APVD	G. DUBNICZKI	11-MAR-97
PRODUCT SPEC	–	
APPLICATION SPEC	–	
WEIGHT	–	

DIMENSIONS: mm [INCHES]
UNLESS OTHERWISE SPECIFIED:
0 PLC ± –
1 PLC ± –
2 PLC ± 0.25[.01]
3 PLC ± 0.127[.005]
4 PLC ± 0.05[.002]
ANGLES ± 2°
MATERIAL △4
FINISH SEE TABLE

TE Connectivity

NAME: HEADER ASSEMBLY, MOD II, STACKING, SINGLE ROW, .025 SQ. POST, UNSHROUDED

SIZE	CAGE CODE	DRAWING NO	RESTRICTED TO
A1	00779	C-146481	–

CUSTOMER DRAWING | SCALE 4:1 | SHEET 1 OF 1 | REV A1

4805 (3/11)

Downloaded from Elcodis.com electronic components distributor