



- THE NOTED DIMENSIONS APPLY AT THE INTERSECTION OF THE POST AND HOUSING
- HOUSING: FLAME RETARDANT THERMOPLASTIC; COLOR: BLACK
- FINISH: 0.00254-.00508 [0.00100-.00200] MATTE TIN-LEAD  
OVER 0.00127 [0.00050] NICKEL ENTIRE POST
- FINISH: 0.00254-.00508 [0.00100-.00200] MATTE TIN  
OVER 0.00127 [0.00050] NICKEL ENTIRE POST

△	101	99.08				
△	3,984	3,900	39	40	4	1-146455-0
△	98.68	96.52	38	39	3	1-146455-9
△	3,884	3,800	37	38	3	1-146455-8
△	96.13	93.98	37	38	3	1-146455-9
△	3,784	3,700	36	37	3	1-146455-7
△	93.57	91.44	36	37	3	1-146455-7
△	3,684	3,600	35	36	3	1-146455-6
△	91.03	88.90	35	36	3	1-146455-6
△	3,584	3,500	34	35	3	1-146455-5
△	88.49	86.36	34	35	3	1-146455-5
△	3,484	3,400	33	34	3	1-146455-4
△	85.95	83.82	33	34	3	1-146455-4
△	3,384	3,300	32	33	3	1-146455-3
△	83.41	81.28	32	33	3	1-146455-3
△	3,284	3,200	31	32	3	1-146455-2
△	80.87	78.74	31	32	3	1-146455-2
△	3,184	3,100	30	31	3	1-146455-1
△	78.33	76.20	30	31	3	1-146455-1
△	3,084	3,000	29	30	3	1-146455-0
△	75.79	73.66	29	30	3	1-146455-0
△	2,984	2,900	28	29	2	1-146455-9
△	73.25	71.12	28	29	2	1-146455-9
△	2,884	2,800	27	28	2	1-146455-8
△	70.71	68.58	27	28	2	1-146455-8
△	2,784	2,700	26	27	2	1-146455-7
△	68.17	66.04	26	27	2	1-146455-7
△	2,684	2,600	25	26	2	1-146455-6
△	65.63	63.50	25	26	2	1-146455-6
△	2,584	2,500	24	25	2	1-146455-5
△	63.09	60.96	24	25	2	1-146455-5
△	2,484	2,400	23	24	2	1-146455-4
△	60.55	58.42	23	24	2	1-146455-4
△	2,384	2,300	22	23	2	1-146455-3
△	58.01	55.88	22	23	2	1-146455-3
△	2,284	2,200	21	22	2	1-146455-2
△	55.47	53.34	21	22	2	1-146455-2
△	2,184	2,100	20	21	2	1-146455-1
△	52.93	50.80	20	21	2	1-146455-1
△	2,084	2,000	19	20	2	1-146455-0
△	50.39	48.26	19	20	2	1-146455-0
△	1,984	1,900	18	19	1	1-146455-9
△	47.85	45.72	18	19	1	1-146455-9
△	1,884	1,800	17	18	1	1-146455-8
△	45.31	43.18	17	18	1	1-146455-8
△	1,784	1,700	16	17	1	1-146455-7
△	42.77	40.64	16	17	1	1-146455-7
△	1,684	1,600	15	16	1	1-146455-6
△	40.23	38.10	15	16	1	1-146455-6
△	1,584	1,500	14	15	1	1-146455-5
△	37.69	35.56	14	15	1	1-146455-5
△	1,484	1,400	13	14	1	1-146455-4
△	35.15	33.02	13	14	1	1-146455-4
△	1,384	1,300	12	13	1	1-146455-3
△	32.61	30.48	12	13	1	1-146455-3
△	1,284	1,200	11	12	1	1-146455-2
△	30.07	27.94	11	12	1	1-146455-2
△	1,184	1,100	10	11	1	1-146455-1
△	27.53	25.40	10	11	1	1-146455-1
△	1,084	1,000	9	10	1	1-146455-0
△	24.99	22.86	9	10	1	1-146455-0
△	999	900	8	9	1	1-146455-9
△	22.45	20.32	8	9	1	1-146455-9
△	884	800	7	8	1	1-146455-8
△	19.91	17.78	7	8	1	1-146455-7
△	784	700	7	8	1	1-146455-8
△	17.37	15.24	6	7	1	1-146455-6
△	684	600	5	6	1	1-146455-5
△	15.83	13.70	5	6	1	1-146455-5
△	12.29	10.16	4	5	1	1-146455-4
△	484	400	4	5	1	1-146455-6
△	13.75	11.62	3	4	1	1-146455-4
△	975	700	3	4	1	1-146455-4
△	11.21	9.08	2	3	1	1-146455-3
△	262	500	2	3	1	1-146455-3
△	4.67	2.54	1	2	1	1-146455-2
△	184	100	1	2	1	1-146455-2
△	1.13	0				1-146455-1
△	084	-				
PLATING	G	F	E	NO. OF POSITIONS		PART NUMBER

[illegible]