


216X Ø 0.39±0.05  
 PLATED THRU HOLE  
 216X Ø 0.48±0.013  
 DRILL HOLE  
 Ø 0.10

RECOMMENDED PCB LAYOUT  
 MIN BOARD THICKNESS 1.0

REV	DATE	DESCRIPTION	BY	CHK	APP
AD	00				
B		REVISED PER ECO-12-000423			

- △ MATERIAL:  
 HOUSING: LCP, GLASS FILLED, UL94V-0.  
 TERMINALS: HIGH PERFORMANCE COPPER ALLOY.
  - △ FINISH:  
 30µ" SELECTIVE GOLD IN CONTACT AREA, SELECTIVE TIN  
 ON PCB TAILS, NICKEL OVERALL.
  - △ FINISH:  
 30µ" SELECTIVE GOLD IN CONTACT AREA, SELECTIVE TIN-LEAD  
 ON PCB TAILS, NICKEL OVERALL.
4. CONNECTORS SUPPLIED WITH MOUNTING SCREWS.



SCALE 4:1

REFER TO WWW.TE.COM  
 FOR PRODUCT AVAILABILITY

NONE	△	2132722-5
NONE	△	2132722-1
KEY POSITION	FINISH	PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT. DATE: 2011-07-20  
 DRAWN BY: S. BILSON DATE: 2011-07-20  
 CHECKED BY: S. BILSON DATE: 2011-07-20  
 APPROVED BY: S. BILSON DATE: 2011-07-20  
 MATERIAL: SEE TABLE  
 APPLICATION SPEC: IMPACT, ORTHOGONAL, 6 PAIR, DAUGHTERBOARD, 12 COLUMN, RIGHT GUIDED, SIGNAL MODULE, 0.39" C/PITCH  
 SIZE: CASE CODE (DRAWING NO): A | 00779 | 2132722  
 CUSTOMER DRAWING: DATE: 5/11 BY: 1042 B