



B	A	NO OF POSN	FINISH	PART NO.
81.28 [3,200]	31	64	△	8-102398-0
76.20 [3,000]	29	60	△	7-102398-8
68.58 [2,700]	26	54	△	7-102398-5
63.50 [2,500]	24	50	△	7-102398-3
50.80 [2,000]	19	40	△	6-102398-8
43.18 [1,700]	16	34	△	6-102398-5
40.64 [1,600]	15	32	△	6-102398-4
38.10 [1,500]	14	30	△	6-102398-3
35.56 [1,400]	13	28	△	6-102398-2
33.02 [1,300]	12	26	△	6-102398-1
30.48 [1,200]	11	24	△	6-102398-0
27.94 [1,100]	10	22	△	5-102398-9
25.40 [1,000]	9	20	△	5-102398-8
22.86 [900]	8	18	△	5-102398-7
20.32 [800]	7	16	△	5-102398-6
17.78 [700]	6	14	△	5-102398-5
15.24 [600]	5	12	△	5-102398-4
12.70 [500]	4	10	△	5-102398-3
10.16 [400]	3	8	△	5-102398-2
7.62 [300]	2	6	△	5-102398-1

REV	DATE	DESCRIPTION	BY	CHK	APP
00					
01		REVISED PER EDD-11-004587			
02					
03					
04					
05					
06					
07					
08					
09					
10					
11					
12					
13					
14					
15					
16					
17					
18					
19					
20					
21					
22					
23					
24					
25					
26					
27					
28					
29					
30					
31					
32					
33					
34					
35					
36					
37					
38					
39					
40					
41					
42					
43					
44					
45					
46					
47					
48					
49					
50					
51					
52					
53					
54					
55					
56					
57					
58					
59					
60					
61					
62					
63					
64					
65					
66					
67					
68					
69					
70					
71					
72					
73					
74					
75					
76					
77					
78					
79					
80					
81					
82					
83					
84					
85					
86					
87					
88					
89					
90					
91					
92					
93					
94					
95					
96					
97					
98					
99					
100					

- △ MATERIAL—HOUSING: PBT, UL94-V0 RATED, COLOR— BLACK
- △ CONTACTS: COPPER ALLOY PER ASTM B103
- △ AMP TRADEMARK (EITHER SIDE).
- △ 0.00076[000030] MIN. GOLD IN CONTACT AREA, 0.00127-0.00254[000050-000100] TIN—LEAD IN AREA E, ALL OVER 0.00127[000050] MIN. NICKEL.
- △ 0.00076[000030] MIN. GOLD IN CONTACT AREA, 0.00127 - 0.00254 [000050 - .000100] TIN IN AREA E, ALL OVER 0.00127[000050] MIN. NICKEL.
- 5. USE WITH 22-26 AWG WIRE SIZE, 1.27[050] MAX INSULATION DIA., 0.381[015] MAX INSULATION WALL THICKNESS.
- △ CONTACT IDENTIFICATION NUMBER "Z" LOCATED IN THIS AREA.
- △ MOLDED CIRCUIT #1 IDENTIFIER IN LOCATION SHOWN.
- △ OBSOLETE PART NUMBER.
- △ OBSOLETE PARTS: OBSOLETE CIS STREAMLINING PER D.RENAUD/D.SINISI

THIS DRAWING IS A CONTROLLED DOCUMENT.

TE Connectivity

AMPMODU MT, RECEPTACLE ASSEMBLY
 STANDARD-PRESSURE CONTACTS
 FOR 22-26 AWG WIRE SIZE

114-25032

100779

102398

4-1